





625 Cochrane Drive, 5th Floor Markham, ON, L3R 9R9 Canada T | 905 470 0015 F | 905 470 0030 WWW.LEA.CA

February 11, 2025

Reference Number:

25253 - 1544 & 1546 Four Mile Creek Rd, Niagara-on-the-Lake (Noise)

On The Lake Developments Inc.

976 Four Mile Creek Road, Niagara-on-the-Lake, ON LOS 1J0 Attn: Stephen Aghaei, Associate Email: stephen@timegroup.ca

RE: **Noise Impact Study**

> **Proposed Residential and Commercial Development** 1544 & 1546 Four Mile Creek Road, Town of Niagara-on-the-Lake

Dear Mr. Aghaei:

LEA Consulting Ltd. is pleased to present the findings of this Noise Impact Study (NIS) for the proposed residential and commercial development located at the municipal address 1544 & 1546 Four Mile Creek Road, in the Town of Niagara-on-the-Lake.

The report concludes that no noise mitigation measures are recommended or need to be implemented for the subject site.

Should you have any questions regarding this NIS, please do not hesitate to contact us.

100227784

Yours truly,

LEA CONSULTING LTD.

Daniel Eduardo Adarve Villanueva, P. Eng. ROVINCE OF ONTARIO

Project Manager

Noise and Vibration Engineer

Ian Dinsmore

Noise Technologist

Encl.

Proposed Mixed-Use Development 1544 & 1545 Four Mile Creek Road, Niagara-on-the-Lake

Distribution List

No. of Copies	Association / Company	Note
1	On The Lake Developments Inc.	PDF

Disclaimer

This Report represents the work of LEA Consulting Ltd ("LEA") solely for the client identified above and is to be used exclusively for the purpose set out in the Report. This Report may not be relied upon for detailed implementation, or any other purpose not specifically identified within this Report. The material in this Report reflects the judgment of LEA based on the information available to them at the time of preparation. Unless manifested incorrectly, LEA assumes information provided by others is accurate. Changed conditions or information occurring or becoming known after the date of this report could affect the results and conclusions presented. Unless otherwise required by law or regulation, this Report shall not be shared with any third party without the written consent of LEA. This Document is confidential and prepared solely for the use of On The Lake Developments Inc. Neither LEA, its sub-consultants nor their respective employees assume any liability for any reason, including, but not limited to, negligence, to any party other than On The Lake Developments Inc. for any information or representation herein. This report permits the Town of Niagara-on-the-Lake to make reliance on the findings and conclusions presented in the report.

CANADA | INDIA | AFRICA | ASIA | MIDDLE EAST



TABLE OF CONTENTS

1		Introd	uction	2
2		Noise	Sources	2
	2.1	Trans	portation Noise Sources	2
	2.	1.1	Road Traffic	2
	2.	1.2	Rail Sources	2
	2.	1.3	Air Traffic	2
	2.2	Statio	nary Noise Sources	2
3		Noise	Criteria	3
	3.1	Trans	portation Noise	3
	3.	1.1	Indoors	3
	3.	1.2	Outdoors	4
	3.2	Statio	nary Noise	4
4		Noise	Impact Assessment	4
	4.1	Trans	portation Noise Assessment	4
	4.	1.1	Road Traffic Data	5
	4.	1.2	Transportation Noise Predictions	5
	4.2	Statio	nary Noise Assessment	6
	4.	2.1	Stationary Noise Data	7
	4.	2.2	Stationary Noise Predictions	8
5		Noise	Abatement Requirements	9
	5.1	Indoo	r Living Areas and AC/Ventilation Requirements	9
	5.	1.1	Building Façade Constructions	9
	5.	1.2	Ventilation Requirements	9
6		Conclu	usions & Recommendations	10
7		Warni	ng Clauses	. 11
8		Refere	ences	12



LIST OF TABLES AND FIGURES

Table 1: MECP Sound Level Limits for Indoor Spaces	3
Table 2: MECP Ventilation Requirements	3
Table 3: MECP Sound Level Limits for Outdoor Living Area	4
Table 4: MECP Sound Level Limits (1-hour Equivalent) for Stationary Noise Sources in Class 2 Area	4
Table 5: Summary of Traffic Data	5
Table 7: Predicted (Unattenuated) Transportation Sound Levels (Plane of Window)	€
Table 8: Receptor Details for Stationary Noise Assessment	7
Table 9: HVAC RTUs Octave Band Sound Power Data	8
Table 10: Predicted Stationary Noise Impact Levels	8

Figure 1: Key Plan showing Site Location and Area

Figure 2: Transportation Noise Receptor Locations – Site Plan

Figure 3: Stationary Noise Source and Receptor Locations

APPENDICES

APPENDIX A COPY OF THE SITE PLAN

APPENDIX B TRAFFIC DATA

APPENDIX C DETAILED STAMSON ANALYSIS

APPENDIX D CADNA/A SAMPLE CALCULATIONS



SUMMARY

LEA Consulting Ltd. (LEA) has been retained by On The Lake Developments Inc. to prepare a Noise Impact Study (NIS) in support of the proposed residential, commercial and office development located at 1544 & 1546 Four Mile Creek Road in the Town of Niagara-on-the-Lake. This study examined the future noise environment in the development area and evaluated its impact potential on future noise-sensitive receptors. Transportation noise assessment was accomplished based on the Ontario Road Noise Analysis Method for Environment and Transportation (ORNAMENT) using the Ontario Ministry of the Environment, Conservation and Parks (MECP) STAMSON noise prediction software. The stationary sound level predictions were modelled using the computer software Cadna/A, which incorporates the MECP-approved ISO 9613-2 method of prediction. Based on the analysis, the noise impact from the environment on the proposed development is within the applicable MECP limits. Mitigative measures are not required to meet the MECP limits.

Transportation Noise Sources – Outdoor:

► The at-grade outdoor patio area was not considered as outdoor living area receptors in this study due to shielding from the commercial/office building, the location of the outdoor patio area is not directly exposed to vehicular traffic along Four Mile Creek Road. Therefore, these OLA receptors were not considered for the proposed development.

Transportation Noise Sources – Indoor:

- ▶ OBC compliant exterior window and wall construction are sufficient for the mixed-use development on all façades of the proposed residential and commercial/office buildings;
- The office units on the northerly, easterly and southerly façades of the proposed development must be provided with forced-air heating with the provision for future air-conditioning and should include Warning Clause Type 'C' in its Agreements of Purchase/Sale or Lease/Rental agreements. However, it is anticipated that the development will provide a central air conditioning system; thus, the forced-air heating with the provision for future air-conditioning is expected to be met;
- Should any of the plans or information used in the completion of this report change, a detailed review should be completed by an acoustical consultant to ensure the sound level limits are met.

Stationary Noise Sources:

No mitigation measures are required for points of reception affected by stationary noise sources.

CANADA | INDIA | AFRICA | ASIA | MIDDLE EAST



1 INTRODUCTION

LEA Consulting Ltd. (LEA) has been retained by On The Lake Developments Inc. to prepare a Noise Impact Study (NIS) in support of the proposed residential, commercial and office development located at 1544 & 1546 Four Mile Creek Road in the Town of Niagara-on-the-Lake.

The proposed development has an approximate total Gross Floor Area (GFA) of 7,338 m² and is currently occupied by two (2) single-detached dwellings. The proposed development consists of a four (4) storey residential building with a GFA of 3,640 m², a two (2) storey commercial/office building with a GFA of 3,698 m², and surface-level parking spaces, which includes one (1) level of below-grade parking.

The subject site is located on the western side of Four Mile Creek Road, north of Line 2 Road. The surrounding land is mixed-use, including residential buildings to the south and east, commercial buildings and sports facilities to the north, and commercial, industrial, and residential buildings to the west.

This study examined the existing and future noise environment in the development area and evaluated its potential impact on future noise-sensitive receptors. This report investigates the noise control measures that are required in order for the development to meet the noise guidelines of the Ontario Ministry of the Environment, Conservation and Parks (MECP) and to satisfy the requirements of the Town of Niagara-on-the-Lake. This noise report is based on the methodology and approach outlined in the MECP guideline NPC-300 "Stationary and Transportation Sources – Approval and Planning" (August 2013).

Figure 1 provides a key plan showing the location of the proposed development.

This report is based on the site plan prepared by Icke Brochu Architects Inc., dated December 3rd, 2024. A copy of the site plan is shown in **Appendix A**.

2 NOISE SOURCES

2.1 TRANSPORTATION NOISE SOURCES

2.1.1 Road Traffic

Vehicular traffic along Four Mile Creek Road and Niagara Stone Road are the dominant sources of transportation noise that could impact the subject site. Due to the low vehicular traffic on Line 2 Road, it was deemed acoustically insignificant and will no longer be included in this study.

2.1.2 Rail Sources

This development is not impacted by rail noise sources.

2.1.3 Air Traffic

The development is not impacted by aircraft noise sources.

2.2 STATIONARY NOISE SOURCES

As indicated in the client-provided architectural plans, the Heating, Ventilation, and Air Conditioning (HVAC) Rooftop Units (RTUs) systems related to the proposed development will be contained inside a mechanical



1544 & 1545 Four Mile Creek Road, Niagara-on-the-Lake

penthouse. Thus, the subject site does not include stationary noise sources that could impact the nearby noise-sensitive areas.

Our preliminary review indicated that the site may be impacted by noise generated from the rooftop Heating, Ventilation, and Air Conditioning (HVAC) units related to the existing buildings surrounding the subject site. These have been identified as the dominant potential sources of stationary noise that could impact the noise-sensitive areas of the proposed development. Accordingly, a stationary noise assessment was also conducted.

3 NOISE CRITERIA

3.1 TRANSPORTATION NOISE

3.1.1 Indoors

The indoor noise level impact due to road traffic was examined as per the noise criteria outlined in the MECP guidelines. The indoor sound level limit due to road traffic for a living or dining room area during the daytime (07:00-23:00) and nighttime (23:00-07:00) hours are a $L_{eq-16hr}$ and L_{eq-8hr} of 45 dBA, respectively. The indoor sound level limit due to road traffic for a bedroom during the daytime is a $L_{eq-16hr}$ of 45 dBA and during the nighttime hours is an L_{eq-8hr} of 40 dBA. To satisfy the limits set out by the MECP guidelines, the MECP has provided a basis for the type of windows, doors, and exterior walls that will be required based on projected outdoor noise levels.

The required limits as per NPC-300 guidelines are summarised in **Table 1**. Moreover, the ventilation requirements from transportation noise sources as per NPC-300 guidelines are presented in **Table 2**.

Table 1: MECP Sound Level Limits for Indoor Spaces

T	Time Desired	Sound Level Limits			
Type of Space	Time Period	Road			
Living/Dining, Den Areas of Residences	07:00 - 23:00	L _{eq (16 hours)} : 45 dBA			
Living/Dining, Den Areas of Residences	23:00 - 07:00	L _{eq (8 hours)} : 45 dBA			
Clooning quarters	07:00 - 23:00	L _{eq (16 hours)} : 45 dBA			
Sleeping quarters	23:00 - 07:00	L _{eq (8 hours)} : 40 dBA			

Table 2: MECP Ventilation Requirements

Plane of Window Sound Level (L _{eq})	Ventilation Requirement	Warning Clause Requirement							
	Daytime (07:00 to 23:00)								
≤55 dBA	None	None							
55 ≤65 dBA	Forced air heating with provisions for the installation of central air conditioning	Recommended							
> 65 dBA	Central air conditioning	Required							
	Nighttime (23:00 to 07:00)								
≤50 dBA	None	None							
50 ≤60 dBA	Forced air heating with provisions for the installation of central air conditioning.	Recommended							
> 60 dBA	Central air conditioning	Required							



3.1.2 Outdoors

Guidelines set out by the MECP recommend that equivalent noise levels (i.e., $L_{eq-16hr}$) in outdoor living areas should not exceed 55 dBA. If the predicted $L_{eq-16hr}$ is greater than 60 dBA, noise control measures should be implemented to reduce the level to 55 dBA. If it is not technically, economically, or administratively feasible to achieve a level of 55 dBA, noise levels between 55 dBA and 60 dBA may be acceptable, provided that the future occupants of the dwellings are made aware of the potential noise problems through a warning clause. The required limits are summarised in **Table 3**.

Table 3: MECP Sound Level Limits for Outdoor Living Area

Tune of Space	Time Period	Sound Level Limits		
Type of Space	Time Periou	Road	Rail	
Outdoor Living Area (OLA)	07:00 – 23:00	L _{eq (16 hours)} : 55 dBA (may meas L _{eq (16 hours)} : 60 dBA (nois requ	sures)	

3.2 STATIONARY NOISE

The noise assessment criteria for stationary noise are based on the Ministry of the Environment, Conservation and Parks (MECP) Publication NPC-300 "Environmental Noise Guideline, Stationary and Transportation Sources - Approval and Planning" dated 2013.

In accordance with the MECP Guideline NPC-300, the surrounding area is considered to be located in a Class 2 acoustical environment. In a Class 2 area, the background sound levels during the daytime (07:00 to 19:00) periods are dominated by the activities of people; usually, road traffic often referred to as "urban hum". However, the background sound levels in a Class 2 area during the evening (19:00 to 23:00) and nighttime (23:00 to 07:00) hours are defined by the natural environment and infrequent human activities. The sound level limits for stationary noise sources are summarised in **Table 4** below.

Table 4: MECP Sound Level Limits (1-hour Equivalent) for Stationary Noise Sources in Class 2 Area

Time Period	Time of Day	Class 2 Area - Sound Level Limits ¹ L _{eq-1hr} (dBA)
Outdoor Points of Reception	07:00 – 19:00 (Daytime)	50
Outdoor Foirits of Reception	19:00 – 23:00 (Evening)	45
DI CAN I	07:00 – 19:00 (Daytime)	50
Plane of Window of Noise Sensitive Spaces	19:00 – 23:00 (Evening)	50
Noise Sensitive Spaces	23:00-07:00 (Nighttime)	45

⁽¹⁾ or the minimum existing hourly background level Leq, whichever is higher

The MECP sound level limit is determined by the exclusion limit listed above in **Table 4** or the minimum hourly equivalent background sound level, whichever is higher.

4 NOISE IMPACT ASSESSMENT

4.1 TRANSPORTATION NOISE ASSESSMENT

As noted in **Section 2.1.1**, the study area's dominant transportation traffic noise source is traffic noise generated by Niagara Stone Road and Four Mile Creek Road. Niagara Stone Road is located to the north of the



subject site with a posted speed limit of 50 km/h. Four Mile Creek Road is located to the east of the subject site with a posted speed limit of 50 km/h to the north of Line 2 Road and 60 km/h to the south of Line 2 Road.

Noise level calculations were performed in accordance with the methodology outlined in MECP guidelines, including the Ontario Road Noise Analysis Method for Environment and Transportation (ORNAMENT).

4.1.1 Road Traffic Data

LEA personnel collected traffic data related to Niagara Stone Road and Four Mile Creek Road on Tuesday December 17, 2024. Traffic data was also collected at Four Mile Creek Road, Arena Road, Four Mile Creek Road and Line 2 Road. The highest traffic volumes at Niagara Stone Road and Four Mile Creek Road were used in the analysis. This data was escalated to the year 2034 with a yearly growth rate of 2%.

The medium/heavy truck percentages were calculated using turning movement counts dated December 17, 2024, for the Niagara Stone Road and Four Mile Creek Road intersection during the weekday AM and PM peak periods, respectively. All buses were considered to be medium trucks, while the heavy/medium truck split within the "trucks" classification was determined based on the "Ministry of Transportation Ontario (MTO) Environmental Guide for Noise", dated February 2022. The day/night traffic volume splits were assumed to be ninety (90) per cent in the day and ten (10) per cent at night. All roadways were modelled as one (1) segment for the purpose of STAMSON transportation analysis. Sound level distance adjustments were applied to receptors wherever applicable.

Road traffic noise predictions were based on the road traffic data outlined in **Table 5**. Road traffic data is included in **Appendix B**.

Table 5: Summary of Traffic Data

Traffic Data	Future AADT	Day/Night Ratio	Percentage of Medium Trucks	Percentage of Heavy Trucks	Posted Speed Limit
Niagara Stone Road	12,860	90/10 ¹	0.33%	0.52%	50 km/h
Four Mile Creek Road	6,205	90/10 ¹	0.96%	1.53%	50 & 60 km/h

⁽¹⁾ Assumed

4.1.2 Transportation Noise Predictions

Noise impact assessments on the proposed development were performed with consideration of the predicted future volume of traffic. Daytime and nighttime impacts from transportation noise were investigated. Distance adjustment corrections were applied wherever applicable.

As noted in **Section 1**, the proposed development consists of a four (4) storey residential building with one (1) level of below-grade parking spaces and a two (2) storey commercial/office building. The latest site plan identified an at-grade outdoor patio area that can be considered an Outdoor Living Area (OLA) that may be negatively impacted by road traffic; however, due to shielding from the commercial/office building, the location of the outdoor patio area is not directly exposed to vehicular traffic along Four Mile Creek Road. Therefore, OLA receptors were not considered for the proposed development.

It should be noted that a balcony/terrace that is less than four (4) meters in depth is not considered an OLA in accordance with the MECP NPC-300 noise guidelines. The locations of the façade receptors are shown in **Figure 2**.

Table 6 shows the unattenuated daytime and nighttime predicted L_{eq} 's due to road traffic at the noise-sensitive receptors within the proposed development. Nighttime L_{eq} 's are only required for sleeping



quarters; therefore, the commercial and office receptors do not include nighttime noise level values. Receptors near Line 2 Road were modelled with two (2) segments for Four Mile Creek Road due to the change in posted speed on Four Mile Creek Road to the south of Line 2 Road. Façade receptors are labelled as R01 to R10 in **Figure 2**. Detailed sound-level calculations are provided in **Appendix C**.

Table 6: Predicted (Unattenuated) Transportation Sound Levels (Plane of Window)

Receptor	Receptor Height (m)	Description	Source	Distance (m)	Overall L _{eq} (dBA) Day	Overall L _{eq} (dBA) Night	
DO1	12.75 ¹	Residential Building	Niagara Stone Road	280	54	40	
R01	12./5	North Façade	Four Mile Creek Road	51	54	48	
R02	12.75 ¹	Residential Building West Façade North Corner			47	41	
		Residential Building	Four Mile Creek Road	72			
R03	12.75 ¹	South Façade	Four Mile Creek Road (60km/h)	123	52	44	
R04	7.00^{2}	Office Building North	Niagara Stone Road	280	59		
N04	7.00	Façade East Corner	Four Mile Creek Road	15	39	-	
	5 7.00 ²	7.00 ² Office Building West Façade	Four Mile Creek Road	25	53	1	
R05			Four Mile Creek Road (60km/h)	73			
		Office Building South	Four Mile Creek Road	14		-	
R06	7.00 ²	Façade	Four Mile Creek Road (60km/h)	68	59		
			Niagara Stone Road	304			
R07	7.00 ²	7.00 ²	7.00 ² Office Building East	Four Mile Creek Road	12	61	-
_		North Corner Façade	Four Mile Creek Road (60km/h)	144	01		
			Niagara Stone Road	385			
R08	7.00^{2}	Office Building East	Four Mile Creek Road	11	62	-	
	7.00	Façade South Corner	Four Mile Creek Road (60km/h)	76			
R09	7.00 ² Office Building North	Niagara Stone Road	281	56			
NUS	7.00	Façade West Corner	Four Mile Creek Road	29	56	-	
R10	12.75 ¹	Residential Building West Façade South Corner	Niagara Stone Road	350	46	40	

⁽¹⁾ Based on the residential building Level 4 elevation of 11.25 metres plus receptor height of 1.5 metres.

4.2 STATIONARY NOISE ASSESSMENT

The stationary noise assessment is based on the ISO 9613-2 standard: "Acoustics-Attenuation of sound during propagation outdoors – Part 2: General method of calculation" (1996). Sound levels due to sources of stationary sound were calculated using the Cadna/A computer software, Version 2020.



⁽²⁾ Based on the office building level 2 elevation of 5.5 metres plus receptor height of 1.5 metres.

1544 & 1545 Four Mile Creek Road, Niagara-on-the-Lake

As stated before, in **Section 2.2**, the HVAC RTUs systems related to the proposed development will be contained inside a mechanical penthouse. Thus, the subject site does not include stationary noise sources that could impact the nearby noise-sensitive areas as well as itself. However, the noise generated from the rooftop HVAC RTUs related to the existing mixed-use buildings in the proximity of the subject site may have an adverse impact on the noise-sensitive spaces within the site, and a stationary noise assessment is required.

Sound levels were modelled for the worst-case daytime and nighttime hour at the noise-sensitive receptors wherever noise exposure was considered maximum. Locations of the critical noise receptors are shown in **Figure 3**. The details related to the receptor locations and heights used in the assessment are summarised in **Table 7**. The directivity of noise emission for applicable noise sources was considered. Sample calculations are available in **Appendix D**.

Table 7: Receptor Details for Stationary Noise Assessment

Receptor	Description	Receptor Elevation (m)		
RP01	Residential Building North Façade	12.75 ¹		
RP02	Residential Building West Façade	12.75 ¹		
RP03	Residential Building South Façade	12.75 ¹		
RP04	Office Building North Façade	7.00 ²		
RP05	Office Building West Façade	7.00 ²		
RP06	Office Building South Façade	7.00 ²		
RP07	Office Building East Façade	7.00 ²		

⁽¹⁾ Based on the residential building Level 4 elevation of 11.25 metres plus receptor height of 1.5 metres.

No additional stationary noise sources were identified. Further details regarding the above-noted stationary noise sources are provided below.

4.2.1 Stationary Noise Data

As mentioned in **Section 2.2** of this report, the impact of RTUs mounted on the rooftop of the existing buildings in proximity to the subject site were investigated.

Reference sound power data related to the HVAC mounted on the rooftop of the existing buildings surrounding the subject site were obtained from the manufacturer. As LEA was unable to obtain the exact model number of the existing RTUs, the RTU reference data was conservatively selected based on the RTUs with the largest tonnage, given the number of observed fans. For example, an RTU with three (3) fans and a medium footprint was observed in the existing residential building to the east of the proposed development, and one of the smaller RTUs with three (3) fans for a building with that GFA is thirty (30) tons. Thus, a thirty (30) ton RTU was selected to model sound levels at that existing residential building. For the purposes of the noise assessment, conservatively, the duty cycles for all the rooftop mechanical equipment, including HVAC RTUs related to the surrounding buildings, were assumed to be a hundred (100) per cent during daytime hours (07:00-19:00) and evening hours (19:00-23:00) and fifty (50) per cent during the nighttime hours (23:00-07:00). The sound data inputs utilised for this noise modelling assessment are shown in **Table 8**.



⁽²⁾ Based on the office building level 2 elevation of 5.5 metres plus receptor height of 1.5 metres.

1544 & 1545 Four Mile Creek Road, Niagara-on-the-Lake

Table 8: HVAC RTUs Octave Band Sound Power Data

			Octave Band Linear Sound Power Level (dB)						
Source ID	Description	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	Sound Power Level (dBA)
S09, S12, S16, S17, S22, S23, S29, S30, S38	HVAC RTU 10 Ton	92	88	87	83	79	72	67	88
S05-S08, S10, S11, S15, S18-S21, S26, S27, S31, S32, S34, S35	HVAC RTU 15 Ton	96	93	90	89	84	77	71	93
S14, S24, S25, S28, S36	HVAC RTU 20 Ton	77	81	87	89	86	80	67	92
S13	HVAC RTU 25 Ton	91	89	86	82	79	76	72	88
S01-S04	HVAC RTU 30 Ton	90	88	86	82	80	77	73	88
S33	HVAC RTU 50 Ton	94	92	90	87	84	80	75	92
S37	Cooling Tower	86	80	83	76	74	73	62	83

4.2.2 Stationary Noise Predictions

Sound levels were modelled for the worst-case daytime and nighttime hour at the noise-sensitive receptors wherever noise exposure was considered maximum. Locations of the critical noise receptors are shown in **Figure 3**. The predicted sound levels at the noise-sensitive receptors due to stationary noise emanating from the environment are summarised in **Table 9**. The directivity of noise emission for applicable noise sources was considered. Sample calculations are available in **Appendix D**.

Table 9: Predicted Stationary Noise Impact Levels

Receptor	Period	Predicted Sound Level (Leq 1 hour, dBA)	Sound Level Limit (L _{eq 1 hour} , dBA)	Exceeds Sound Level Limit?
RP01	Daytime (07:00-23-00)	39	50	NO
RPUI	Nighttime (23:00-07:00)	36	45	NO
DD03	Daytime (07:00-23-00)	34	50	NO
RP02	Nighttime (23:00-07:00)	31	45	NO
DD03	Daytime (07:00-23-00)	32	50	NO
RP03	Nighttime (23:00-07:00)	29	45	NO
RP04	Daytime (07:00-23-00)	41	50	NO
KPU4	Nighttime (23:00-07:00)	38	45	NO
RP05	Daytime (07:00-23-00)	31	50	NO
KPUS	Nighttime (23:00-07:00)	28	45	NO
RP06	Daytime (07:00-23-00)	31	50	NO
KPUb	Nighttime (23:00-07:00)	28	45	NO
RP07	Daytime (07:00-23-00)	41	50	NO
KPU/	Nighttime (23:00-07:00)	38	45	NO

Figure 3 illustrates the predicted sound level contours at 7m in the proximity of the subject site's noise-sensitive receptors for the daytime period. Based on the figure, stationary sound levels are expected to be below the MECP sound level limits. Thus, mitigation measures are not required for stationary noise sources.



5 NOISE ABATEMENT REQUIREMENTS

5.1 INDOOR LIVING AREAS AND AC/VENTILATION REQUIREMENTS

Indoor sound levels have been examined with respect to MECP Guidelines, as summarised in **Section 3.1.1** of this report. The recommendations discussed below should be verified upon the final detailed review of the architectural design of the proposed development.

5.1.1 Building Façade Constructions

According to NPC-300 guideline:

"If the nighttime sound level outside the bedroom or living/dining room windows exceeds **60 dBA** or the daytime sound level outside the bedroom or living/dining area windows exceeds **65 dBA**, building components including windows, walls and doors, where applicable, should be designed so that the indoor sound levels comply with the sound level limits."

Based on the predicted outdoor façade sound levels shown in **Table 6** and the statement above from NPC-300 guideline, window and wall upgrades for all façades are not required to meet the MECP indoor sound level limits shown in **Table 1**.

The exterior window and wall STC values show that the following are required to mitigate road traffic sound levels to the MECP and Town of Niagara-on-the-Lake indoor sound level criteria:

▶ OBC compliant exterior window and wall construction are sufficient for the mixed-use development on all façades of the proposed residential and commercial/office buildings.

5.1.2 Ventilation Requirements

Based on the unattenuated noise levels shown in **Table 6** and the ventilation requirements in **Table 2**, the façades do require warning clauses for future occupants in their Agreements of Purchase/Sale.

➤ The office units on the northerly, easterly and southerly façades of the proposed development must be provided with forced-air heating with the provision for future air-conditioning and should include Warning Clause Type 'C' in its Agreements of Purchase/Sale or Lease/Rental agreements. However, it is anticipated that the development will provide a central air conditioning system; thus, the forced-air heating with the provision for future air-conditioning is expected to be met.



1544 & 1545 Four Mile Creek Road, Niagara-on-the-Lake

CONCLUSIONS & RECOMMENDATIONS

According to the NPC-300 noise guidelines, the implementation of all required noise control measures should be verified by a qualified Acoustical Consultant. All relevant builder's plans should be certified by an Acoustic Consultant as being in conformance with the recommendations of the approved Noise Impact Study. Further, prior to the final inspection and release for occupancy, the recommended noise control measures within the subject site should be inspected by an Acoustic Consultant. The intent is to ensure that the recommendations and builder's plans are compliant with the approved Noise Impact Study.

Based on the analysis, the impact from the environment on the proposed development is within the applicable MECP limits. The following is a summary of our noise analysis:

- No mitigation measures are required for points of reception affected by stationary noise sources;
- The at-grade outdoor patio area was not considered as outdoor living area receptors in this study due to shielding from the commercial/office building, the location of the outdoor patio area is not directly exposed to vehicular traffic along Four Mile Creek Road. Therefore, these OLA receptors were not considered for the proposed development.
- OBC compliant exterior window and wall construction are sufficient for the mixed-use development on all façades of the proposed residential and commercial/office buildings;
- The office units on the northerly, easterly and southerly façades of the proposed development must be provided with forced-air heating with the provision for future air-conditioning and should include Warning Clause Type 'C' in its Agreements of Purchase/Sale or Lease/Rental agreements. However, it is anticipated that the development will provide a central air conditioning system; thus, the forced-air heating with the provision for future air-conditioning is expected to be met;
- Should any of the plans or information used in the completion of this report change, a detailed review should be completed by an acoustical consultant to ensure the sound level limits are met.



7 WARNING CLAUSES

The following warning clause should be included in all offers of purchase and sale relating to:

▶ The office units on the northerly, easterly and southerly façades of the proposed development;

Warning Clause Type C:


"This dwelling unit has been designed with the provision for adding central air conditioning at the occupant's discretion. Installation of central air conditioning by the occupant in low and medium density developments will allow windows and exterior doors to remain closed, thereby ensuring that the indoor sound levels are within the sound levels limits of the Town of Niagara-on-the-Lake and the Ministry of the Environment, Conservation and Parks."





8 REFERENCES

- 1. ORNAMENT "Ontario Road Noise Analysis Method for Environmental and Transportation", Ontario Ministry of the Environment, October 1989.
- 2. International Standard, ISO 9613-2, "Acoustics Attenuation of Sound During Propagation Outdoors Part 2: General Method of Calculation", Dec 1996.
- 3. "Noise Guideline, Stationary and Transportation Sources Approval and Planning, Publication NPC-300", Ontario Ministry of the Environment, Aug 2013.










APPENDIX A

COPY OF THE SITE PLAN





SITE PLAN
PROJECT NO. 23.11
SCALE 1:600 DATE DECEMBER 3, 2024



APPENDIX B


TRAFFIC DATA



Intersection: Four Mile Creek Road & Niagara Stone Road Survey Date: December 17, 2024 Project No.: 25253.01 Count ID: 24465

Turning Movement Count - Four Mile Creek Road & Niagara Stone Road

			Four Mile Creek Ro					Stone Roa	ıd					Creek Road										
			Southbound						Westbound			Northbound									astbound			
Start Time	U-Turn	Left	Thru Right	Peds	App. Total	U-Turn	Left	Thru	Right	Peds	App. Total	U-Turn	Left	Thru	Right	Peds	App. Total	U-Turn	Left	Thru	Right	Peds	App. Total	Grand Total
7:00	0	0	6 5	1	11	0	4	25	1	0	30	0	2	7	5	0	14	0	3	33	2	0	38	93
7:15	0	2	8 3	0	13	0	11	33	4	0	48	0	4	10	21	0	35	0	5	41	4	0	50	146
7:30	0	4	9 5	0	18	0	15	33	1	0	49	0	6	11	31	0	48	0	3	50	14	0	67	182
7:45	0	2	11 4	0	17	0	11	34	2	1	47	0	13	11	33	1	57	0	5	63	5	0	73	194
Hourly Total	0	8	34 17	1	59	0	41	125	8	1	174	0	25	39	90	1	154	0	16	187	25	0	228	615
8:00	0	2	10 5	0	17	0	9	42	0	0	51	0	9	7	18	0	34	0	4	49	6	0	59	161
8:15	0	3	9 6	0	18	0	12	49	4	0	65	0	13	10	16	0	39	0	3	71	17	0	91	213
8:30	0	5	10 8	0	23	0	15	51	3	2	69	0	9	7	19	0	35	0	2	64	11	0	77	204
8:45	0	3	11 7	0	21	0	20	66	0	0	86	0	14	11	35	0	60	0	7	72	9	0	88	255
Hourly Total	0	13	40 26	0	79	0	56	208	7	2	271	0	45	35	88	0	168	0	16	256	43	0	315	833
9:00	0	1	6 11	2	18	0	21	59	1	0	81	0	11	11	33	0	55	0	10	72	16	0	98	252
9:15	0	8	14 6	. 0	28	0	17	59	1	0	77 158	0	15	6	38	0	59	0	4	71	10	0	85	249
Hourly Total	0	9	20 17	2	46	0	38	118	2	0		0	26	17	71	0	114	0	14	143	26	0	183	501
45.00			45 44				- 24	405	-			eak *	- 20	26	25		- 00			03	43		440	272
16:00	0	6	15 11	0	32	0	31	105	6	0	142	0	28	26	35	1	89	0	6	92	12	1	110	373
16:15	0	3	8 12 16 8	0	23	0	38	160	2	0	200	0	12	11	25	0	48	0	5	78	19	0	102	373 356
16:30	0	9		0	33	0	22	114	2	0	138	0	26	21	41	0	88	0	4	73	20	0	97	
16:45	0	8	12 4	. 1	24	0	22	91	4	0	117	0	8	22	22	0	52	0	10	66	17	0	93	286
Hourly Total	0	26	51 35 21 6	1	112	0	113	470	14	0	597	0	74	80	123	1	277	0	25	309	68	1	402	1388
17:00	0	4 5	21 6 16 8	0 2	31 29	0	40 34	108 103	2	1	153 139	0	19 14	9 13	26 27	0	54 54	0	11 7	66 71	15 10	0	92 88	330 310
17:15		6		0						······			7	9	21		37	0	,	57				237
17:30 17:45	0	0	8 1 9 5	3	15 14	0	26 21	86 55	4	1 0	116 77	0	7	9 19	21	0	37 50	0	5	5/ 54	10 7	0	69 66	237
Hourly Total	0	15	54 20	5	89	0	121	352	12	3	485	0	47	50	98	1	195	0	25	248	42	0	315	1084
18:00	0	2	4 10	1	16	0	22	56	6	0	84	0	6	11	21	0	38	0	4	52 52	14	0	70	208
18:15	0	5	4 3	1 1	12	0	13	45	2	0	60	0	11	4	26	0	38 41	0	0	33	9	0	42	155
Hourly Total	0	7	8 13	2	28	0	35	101	8	0	144	0	17	15	47	0	79	0	4	85	23	0	112	363
Grand Total	0	78	207 128	11	413	0	404	1374	51	6	1829	0	234	236	517	3	987	0	100	1228	227	1	1555	4784
Approach %	0.0%	18.9%	50.1% 31.0%	- 11	- 413	0.0%	22.1%	75.1%	2.8%	-	1023	0.0%	23.7%	23.9%	52.4%	-	- 367	0.0%	6.4%	79.0%	14.6%	-		4/04
	• • • • • • • • • • • • • • • • • • • •	••••••	····		······································	† ······	÷		• • • • • • • • • • • • • • • • • • • •	······	·		÷	! 	.	÷·····				• • • • • • • • • • • • • • • • • • • •				
Total %	0.0%	1.6%	4.3% 2.7%		8.6%	0.0%	8.4%	28.7%	1.1%	ļ	38.2%	0.0%	4.9%	4.9%	10.8%		20.6%	0.0%	2.1%	25.7%	4.7%		32.5%	-
Lights	0	76	197 120		393	0	398	1347	51	<u> </u>	1796	0	226	222	506	<u> </u>	954	0	95	1199	216	-	1510	4653
% Lights	-	97.4%	95.2% 93.8%	-	95.2%	l	98.5%	98.0%	100.0%		98.2%	-	96.6%	94.1%	97.9%	-	96.7%	-	95.0%	97.6%	95.2%	-	97.1%	97.3%
Buses	-	0	3 4	-	7	-	1	11	0	-	12	-	2	2	3	-	7	-	1	8	4	-	13	39
% Buses	-	0.0%	1.4% 3.1%	1	1.7%	1 .	0.2%	0.8%	0.0%	_	0.7%	-	0.9%	0.8%	0.6%		0.7%	-	1.0%	0.7%	1.8%	······	0.8%	0.8%
Trucks		2	7 4	1	13	t	5	16	0.074		21		6	12	8		26		4	21	7		32	92
		••••••				ļ	÷		• • • • • • • • • • • • • • • • • • • •	ļ	·	ļ	÷		.	 				• • • • • • • • • • • • • • • • • • • •			••••••••	
% Trucks		2.6%	3.4% -		3.1%	ļ	1.2%	1.2%	0.0%	ļ	1.1%	· · · · · · · · · · · · · · · · · · ·	2.6%	5.1%	1.5%		2.6%		4.0%	1.7%	3.1%		2.1%	1.9%
Bicycles	-	-		0	0	<u> </u>	-	-	-	0	0			-	-	0	0	-	-	-		0	0	0
Pedestrians	- 1	-		11	-	-	-	-	-	6	-	-	-	-	-	3	-	- 1	-	-		1	1 -	21






LEA Consulting Ltd.

Intersection: Four Mile Creek Road & Niagara Stone Road Survey Date: December 17, 2024 Project No.: 25253 Count ID: 24465

AM Peak Hour - Four Mile Creek Road & Niagara Stone Road

1																						Stone Road			
	Four Mile Creek Road									Stone Roa	d				Four Mile										
			Sout	hbound					We	stbound					North	bound					East	bound			
Start Time	U-Turn	Left	Thru	Right	Peds	App. Total	U-Turn	Left	Thru	Right	Peds	App. Total	U-Turn	Left	Thru	Right	Peds	App. Total	U-Turn	Left	Thru	Right	Peds	App. Total	Grand Total
8:30	0	5	10	8	0	23	0	15	51	3	2	69	0	9	7	19	0	35	0	2	64	11	0	77	204
8:45	0	3	11	7	0	21	0	20	66	0	0	86	0	14	11	35	0	60	0	7	72	9	0	88	255
9:00	0	1	6	11	2	18	0	21	59	1	0	81	0	11	11	33	0	55	0	10	72	16	0	98	252
9:15	0	8	14	6	0	28	0	17	59	1	0	77	0	15	6	38	0	59	0	4	71	10	0	85	249
Hourly Total	0	17	41	32	2	90	0	73	235	5	2	313	0	49	35	125	0	209	0	23	279	46	0	348	960
Approach %	0.0%	18.9%	45.6%	35.6%	-	-	0.0%	23.3%	75.1%	1.6%	-	-	0.0%	23.4%	16.7%	59.8%	-	-	0.0%	6.6%	80.2%	13.2%	-	-	-
Total %	0.0%	1.8%	4.3%	3.3%	-	9.4%	0.0%	7.6%	24.5%	0.5%	-	32.6%	0.0%	5.1%	3.6%	13.0%	-	21.8%	0.0%	2.4%	29.1%	4.8%	-	36.3%	-
PHF	0	0.53	0.73	0.73	-	0.8	0	0.87	0.89	0.42	-	0.91	0	0.82	0.8	0.82	-	0.87	0	0.58	0.97	0.72	-	0.89	0.94
Lights	0	15	40	27	-	82	0	69	228	5	-	302	0	45	30	121	-	196	0	21	267	44	-	332	912
% Lights	-	88.2%	97.6%	84.4%	-	91.1%	-	94.5%	97.0%	100.0%	-	96.5%	-	91.8%	85.7%	96.8%	-	93.8%	-	91.3%	95.7%	95.7%	-	95.4%	95.0%
Buses	-	0	0	2	-	2	-	0	4	0	-	4	-	1	1	0	-	2	-	0	2	2	-	4	12
% Buses	-	0.0%	0.0%	6.3%	-	2.2%	-	0.0%	1.7%	0.0%	-	1.3%	-	2.0%	2.9%	0.0%	-	1.0%	-	0.0%	0.7%	4.3%	-	1.1%	1.3%
Trucks	-	2	1	3	-	6	-	4	3	0	-	7	-	3	4	4	-	11	-	2	10	0	-	12	36
% Trucks	-	11.8%	2.4%	9.4%	-	6.7%	-	5.5%	1.3%	0.0%	-	2.2%	-	6.1%	11.4%	3.2%	-	5.3%	-	8.7%	3.6%	0.0%	-	3.4%	3.8%
Bicycles	-	-	-	-	0	0	-	-	-	-	0	0	-	-	-	-	0	0	-	-	-	-	0	0	0
Pedestrians	-	-	-	-	2	-	-	-	-	-	2	-	-	-	-	-	0	-	-	-	-	-	0	-	4






Intersection: Four Mile Creek Road & Niagara Stone Road Survey Date: December 17, 2024 Project No.: 25253 Count ID: 24465

PM Peak Hour - Four Mile Creek Road & Niagara Stone Road

			Four Mile	Creek Roa	d			Stone Roa		Four Mile Creek Road							Niagara Stone Road									
	Southbound						Westbound						Northbound							Eastbound						
Start Time	U-Turn	Left	Thru	Right	Peds	App. Total	U-Turn	Left	Thru	Right	Peds	App. Total	U-Turn	Left	Thru	Right	Peds	App. Total	U-Turn	Left	Thru	Right	Peds	App. Total	Grand Total	
16:00	0	6	15	11	0	32	0	31	105	6	0	142	0	28	26	35	1	89	0	6	92	12	1	110	373	
16:15	0	3	8	12	0	23	0	38	160	2	0	200	0	12	11	25	0	48	0	5	78	19	0	102	373	
16:30	0	9	16	8	0	33	0	22	114	2	0	138	0	26	21	41	0	88	0	4	73	20	0	97	356	
16:45	0	8	12	4	1	24	0	22	91	4	0	117	0	8	22	22	0	52	0	10	66	17	0	93	286	
Hourly Total	0	26	51	35	1	112	0	113	470	14	0	597	0	74	80	123	1	277	0	25	309	68	1	402	1388	
Approach %	0.0%	23.2%	45.5%	31.3%	-	-	0.0%	18.9%	78.7%	2.3%	-	-	0.0%	26.7%	28.9%	44.4%	-	-	0.0%	6.2%	76.9%	16.9%		-	-	
Total %	0.0%	1.9%	3.7%	2.5%	-	8.1%	0.0%	11.8%	49.0%	1.0%	-	43.0%	0.0%	7.7%	8.3%	12.8%	-	20.0%	0.0%	2.6%	32.2%	7.1%	-	29.0%	-	
PHF	0	0.72	0.8	0.73	-	0.85	0	0.74	0.73	0.58	-	0.75	0	0.66	0.77	0.75	-	0.78	0	0.63	0.84	0.85	-	0.91	0.93	
Lights	0	26	49	35	-	110	0	113	461	14	-	588	0	73	74	123	-	270	0	25	309	64	-	398	1366	
% Lights	-	100.0%	96.1%	100.0%	-	98.2%	-	100.0%	98.1%	100.0%	-	98.5%	-	98.6%	92.5%	100.0%	-	97.5%	-	100.0%	100.0%	94.1%	-	99.0%	98.4%	
Buses	-	0	0	0	-	0	-	0	3	0	-	3	-	0	1	0	-	1	-	0	0	1	-	1	5	
% Buses	-	0.0%	0.0%	0.0%	-	0.0%	-	0.0%	0.6%	0.0%	-	0.5%	-	0.0%	1.3%	0.0%	-	0.4%	-	0.0%	0.0%	1.5%	-	0.2%	0.4%	
Trucks	-	0	1	0	-	1	-	0	6	0	-	6	-	1	5	0	-	6	-	0	0	3	-	3	16	
% Trucks	-	0.0%	2.0%	0.0%	-	0.9%	- 1	0.0%	1.3%	0.0%	-	1.0%	-	1.4%	6.3%	0.0%	-	2.2%	-	0.0%	0.0%	4.4%	-	0.7%	1.2%	
Bicycles	-	-	-	-	0	0	-	-	-	-	0	0	-	-	-	-	0	0	-	-	-	-	0	0	0	
Pedestrians	-	-	-	-	1	-	-	-	-	-	0	-	-	-	-	-	0	-	-	-	-	-	0	-	1	



APPENDIX C

DETAILED STAMSON ANALYSIS

STAMSON 5.0 NORMAL REPORT Date: 11-02-2025 15:06:38 * Refers to calculated road volumes based on the following input: MINISTRY OF ENVIRONMENT AND ENERGY / NOISE ASSESSMENT 24 hr Traffic Volume (AADT or SADT): 5090 Filename: r01.te Time Period: Day/Night 16/8 hours Percentage of Annual Growth : 2.00 : 10.00 Description: Residential Building North Façade Number of Years of Growth Medium Truck % of Total Volume : 0.96 Heavy Truck % of Total Volume : 1.53 Road data, segment # 1: NiagaraStone (day/night) Day (16 hrs) % of Total Volume : 90.00 _____ Car traffic volume : 11476/1275 veh/TimePeriod * Data for Segment # 2: FMC Road (day/night) Medium truck volume : 38/4 veh/TimePeriod * _____ Heavy truck volume : 60/7 veh/TimePeriod * Angle1 Angle2 : -90.00 deg 10.00 deg Posted speed limit : 50 km/h : 0 (No woods.) Wood depth No of house rows : 0 / 0 Surface : 2 Road gradient : 0 % : 2 (Reflective ground surface) Road pavement : 1 (Typical asphalt or concrete) Receiver source distance : 51.00 / 51.00 m Receiver height : 12.75 / 12.75 m * Refers to calculated road volumes based on the following input: : 1 (Flat/gentle slope; no Topography 24 hr Traffic Volume (AADT or SADT): 10550 barrier) Percentage of Annual Growth : 2.00 Reference angle : 0.00 : 10.00 Number of Years of Growth Medium Truck % of Total Volume : 0.33 Results segment # 1: NiagaraStone (day) Heavy Truck % of Total Volume : 0.52 _____ Day (16 hrs) % of Total Volume : 90.00 Source height = 0.85 m Data for Segment # 1: NiagaraStone (day/night) _____ ROAD (0.00 + 49.33 + 0.00) = 49.33 dBAAngle1 Angle2 : -90.00 deg 90.00 deg Angle1 Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj Wood depth : 0
No of house rows : 0 / 0 : 0 (No woods.) B.Adj SubLeq _____ : 2 (Reflective ground surface) Receiver source distance : 280.00 / 280.00 m-90 90 0.00 62.04 0.00 -12.71 0.00 0.00 0.00 Receiver height : 12.75 / 12.75 m 0.00 49.33 : 1 (Flat/gentle slope; no ______ Topography barrier) Reference angle : 0.00 Segment Leg: 49.33 dBA Road data, segment # 2: FMC Road (day/night) _____ Results segment # 2: FMC Road (day) Car traffic volume : 5445/605 veh/TimePeriod * _____ Medium truck volume : 54/6 veh/TimePeriod * Heavy truck volume : 85/9 veh/TimePeriod * Source height = 1.11 m Posted speed limit : 50 km/h

ROAD (0.00 + 52.82 + 0.00) = 52.82 dBA

B.Adj SubLeq

Angle1 Angle2 Alpha RefLeg P.Adj D.Adj F.Adj W.Adj H.Adj

Road gradient : 0 %

: 1 (Typical asphalt or concrete)

Road pavement

-90 10 0.00 60.69 0.00 -5.31 -2.55 0.00 0.00 0.00 52.82 _____ Segment Leq: 52.82 dBA Total Leq All Segments: 54.43 dBA Results segment # 1: NiagaraStone (night) _____ Source height = 0.86 m ROAD (0.00 + 42.84 + 0.00) = 42.84 dBAAnglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq -90 90 0.00 55.55 0.00 -12.71 0.00 0.00 0.00 0.00 42.84 _____ Segment Leg: 42.84 dBA Results segment # 2: FMC Road (night) Source height = 1.10 m ROAD (0.00 + 46.19 + 0.00) = 46.19 dBAAnglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq ______ -90 10 0.00 54.06 0.00 -5.31 -2.55 0.00 0.00 0.00 46.19

Segment Leq: 46.19 dBA

Total Leg All Segments: 47.84 dBA

TOTAL Leq FROM ALL SOURCES (DAY): 54.43 (NIGHT): 47.84

STAMSON 5.0 NORMAL REPORT Date: 11-02-2025 16:02:11 MINISTRY OF ENVIRONMENT AND ENERGY / NOISE ASSESSMENT Filename: r02.te Time Period: Day/Night 16/8 hours Description: Residential Building West Façade North Corner Road data, segment # 1: NiagaraStone (day/night) _____ Car traffic volume : 11476/1275 veh/TimePeriod * Medium truck volume : 38/4 veh/TimePeriod * Heavy truck volume : 60/7 veh/TimePeriod * Posted speed limit : 50 km/h Road gradient : 0 % Road pavement : 1 (Typical asphalt or concrete) * Refers to calculated road volumes based on the following input: 24 hr Traffic Volume (AADT or SADT): 10550 Percentage of Annual Growth : 2.00 Number of Years of Growth : 10.00 Medium Truck % of Total Volume : 0.33 Heavy Truck % of Total Volume : 0.52 Day (16 hrs) % of Total Volume : 90.00 Data for Segment # 1: NiagaraStone (day/night) _____ Angle1 Angle2 : -90.00 deg 20.00 deg Wood depth : 0 (No woods.) No of house rows : 0 / 0 Surface : 2 (Reflective ground surface) Receiver source distance : 284.00 / 284.00 m Receiver height : 12.75 / 12.75 m $\,$: 1 (Flat/gentle slope; no Topography barrier) Reference angle : 0.00 Results segment # 1: NiagaraStone (day) _____ Source height = 0.85 m ROAD (0.00 + 47.13 + 0.00) = 47.13 dBAAngle1 Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq

```
-90 20 0.00 62.04 0.00 -12.77 -2.14 0.00 0.00
0.00 47.13
______
Segment Leg: 47.13 dBA
Total Leq All Segments: 47.13 dBA
Results segment # 1: NiagaraStone (night)
_____
Source height = 0.86 m
ROAD (0.00 + 40.64 + 0.00) = 40.64 dBA
Angle1 Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj
B.Adj SubLeg
______
 -90 20 0.00 55.55 0.00 -12.77 -2.14 0.00 0.00
0.00 40.64
_____
Segment Leq: 40.64 dBA
Total Leg All Segments: 40.64 dBA
TOTAL Leg FROM ALL SOURCES (DAY): 47.13
                (NIGHT): 40.64
```

STAMSON 5.0 NORMAL REPORT Date: 11-02-2025 16:01:53 MINISTRY OF ENVIRONMENT AND ENERGY / NOISE ASSESSMENT Filename: r03.te Time Period: Day/Night 16/8 hours Description: Residential Building South Façade Road data, segment # 1: FMC Road (day/night) _____ Car traffic volume : 5445/605 veh/TimePeriod * Medium truck volume : 54/6 veh/TimePeriod * Heavy truck volume : 85/9 veh/TimePeriod * Posted speed limit : 50 km/h Road gradient : 0 % Road pavement : 1 (Typical asphalt or concrete) * Refers to calculated road volumes based on the following input: 24 hr Traffic Volume (AADT or SADT): 5090 Percentage of Annual Growth : 2.00 Number of Years of Growth : 10.00 Medium Truck % of Total Volume : 0.96 Heavy Truck % of Total Volume : 1.53 Day (16 hrs) % of Total Volume : 90.00 Data for Segment # 1: FMC Road (day/night) _____ Angle1 Angle2 : 10.00 deg 90.00 deg Wood depth : 0 (No woods.) No of house rows : 0 / 0 Surface : 2 (Reflective ground surface) Receiver source distance : 72.00 / 72.00 m Receiver height : 12.75 / 12.75 m $\,$: 1 (Flat/gentle slope; no Topography barrier) Reference angle : 0.00 Results segment # 1: FMC Road (day) _____ Source height = 1.11 m ROAD (0.00 + 50.35 + 0.00) = 50.35 dBAAngle1 Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq

```
10 90 0.00 60.69 0.00 -6.81 -3.52 0.00 0.00
0.00 50.35
______
Segment Leg: 50.35 dBA
Total Leq All Segments: 50.35 dBA
Results segment # 1: FMC Road (night)
_____
Source height = 1.10 m
ROAD (0.00 + 43.73 + 0.00) = 43.73 dBA
Angle1 Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj
B.Adj SubLeq
______
 10 90 0.00 54.06 0.00 -6.81 -3.52 0.00 0.00
0.00 43.73
_____
Segment Leq: 43.73 dBA
Total Leg All Segments: 43.73 dBA
TOTAL Leg FROM ALL SOURCES (DAY): 50.35
                (NIGHT): 43.73
```

STAMSON 5.0 NORMAL REPORT Date: 11-02-2025 16:02:30 MINISTRY OF ENVIRONMENT AND ENERGY / NOISE ASSESSMENT 24 hr Traffic Volume (AADT or SADT): 5090 Percentage of Annual Growth : 2.00 Filename: r04.te Time Period: Day/Night 16/8 hours Number of Years of Growth : 10.00 Description: Office Building North Façade East Corner Medium Truck % of Total Volume : 0.96 Heavy Truck % of Total Volume : 1.53 Road data, segment # 1: NiagaraStone (day/night) Day (16 hrs) % of Total Volume : 90.00 _____ Car traffic volume : 11476/1275 veh/TimePeriod * Data for Segment # 2: FMC Road (day/night) Medium truck volume : 38/4 veh/TimePeriod * Angle1 Angle2 : -90.00 deg 20.00 deg Heavy truck volume : 60/7 veh/TimePeriod * : 0 (No woods.) Posted speed limit : 50 km/h Wood depth No of house rows : 0 / 0 Surface : 2 (Reflective ground surface) Road gradient : 0 % : 1 (Typical asphalt or concrete) Road pavement Receiver source distance : 15.00 / 15.00 m * Refers to calculated road volumes based on the following input: Receiver height : 7.00 / 7.00 m : 1 (Flat/gentle slope; no Topography 24 hr Traffic Volume (AADT or SADT): 10550 barrier) Percentage of Annual Growth : 2.00 Reference angle : 0.00 Number of Years of Growth : 10.00 Medium Truck % of Total Volume : 0.33 Results segment # 1: NiagaraStone (day) Heavy Truck % of Total Volume : 0.52 _____ Day (16 hrs) % of Total Volume : 90.00 Source height = 0.85 m Data for Segment # 1: NiagaraStone (day/night) ROAD (0.00 + 49.33 + 0.00) = 49.33 dBAAngle1 Angle2 : -90.00 deg 90.00 deg Angle1 Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj Wood depth : 0 (No woods.) B.Adj SubLeq No of house rows : 0 / 0
Surface : 2 _____ (Reflective ground surface) Receiver source distance : 280.00 / 280.00 m -90 90 0.00 62.04 0.00 -12.71 0.00 0.00 0.00 Receiver height : 7.00 / 7.00 m 0.00 49.33 : 1 (Flat/gentle slope; no Topography barrier) Reference angle : 0.00 Segment Leq: 49.33 dBA Road data, segment # 2: FMC Road (day/night) _____ Results segment # 2: FMC Road (day) Car traffic volume : 5445/605 veh/TimePeriod * _____ Medium truck volume : 54/6 veh/TimePeriod * Heavy truck volume : 85/9 veh/TimePeriod * Source height = 1.11 m Posted speed limit : 50 km/h ROAD (0.00 + 58.55 + 0.00) = 58.55 dBARoad gradient : 0 % Road pavement : 1 (Typical asphalt or concrete) Anglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq

* Refers to calculated road volumes based on the following input:

20 0.00 60.69 0.00 0.00 -2.14 0.00 0.00 0.00 58.55 _____ Segment Leq: 58.55 dBA Total Leq All Segments: 59.04 dBA Results segment # 1: NiagaraStone (night) _____ Source height = 0.86 m ROAD (0.00 + 42.84 + 0.00) = 42.84 dBAAnglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq -90 90 0.00 55.55 0.00 -12.71 0.00 0.00 0.00 0.00 42.84 _____ Segment Leg: 42.84 dBA Results segment # 2: FMC Road (night) Source height = 1.10 m ROAD (0.00 + 51.92 + 0.00) = 51.92 dBAAnglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq ______ -90 20 0.00 54.06 0.00 0.00 -2.14 0.00 0.00 0.00 51.92

Segment Leq : 51.92 dBA

Total Leg All Segments: 52.43 dBA

TOTAL Leq FROM ALL SOURCES (DAY): 59.04 (NIGHT): 52.43

STAMSON 5.0 NORMAL REPORT Date: 11-02-2025 16:02:54 MINISTRY OF ENVIRONMENT AND ENERGY / NOISE ASSESSMENT 24 hr Traffic Volume (AADT or SADT): 5090 Percentage of Annual Growth : 2.00 Filename: r05.te Time Period: Day/Night 16/8 hours Number of Years of Growth : 10.00 Medium Truck % of Total Volume : 0.96 Description: Office Building West Façade Heavy Truck % of Total Volume : 1.53 Road data, segment # 1: NiagaraStone (day/night) Day (16 hrs) % of Total Volume : 90.00 _____ Car traffic volume : 11476/1275 veh/TimePeriod * Data for Segment # 2: FMC Road (day/night) Medium truck volume : 38/4 veh/TimePeriod * Angle1 Angle2 : 40.00 deg 90.00 deg Heavy truck volume : 60/7 veh/TimePeriod * : 0 (No woods.) Posted speed limit : 50 km/h Wood depth No of house rows : 0 / 0 Surface : 2 (Reflective ground surface) Road gradient : 0 % : 1 (Typical asphalt or concrete) Road pavement Receiver source distance : 25.00 / 25.00 m * Refers to calculated road volumes based on the following input: Receiver height : 7.00 / 7.00 m : 1 (Flat/gentle slope; no Topography 24 hr Traffic Volume (AADT or SADT): 10550 barrier) Percentage of Annual Growth : 2.00 Reference angle : 0.00 Number of Years of Growth : 10.00 Medium Truck % of Total Volume : 0.33 Results segment # 1: NiagaraStone (day) Heavy Truck % of Total Volume : 0.52 _____ Day (16 hrs) % of Total Volume : 90.00 Source height = 0.85 m Data for Segment # 1: NiagaraStone (day/night) ROAD (0.00 + 44.41 + 0.00) = 44.41 dBAAngle1 Angle2 : -90.00 deg -20.00 deg Angle1 Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj Wood depth : 0 (No woods.) B.Adj SubLeq No of house rows : 0 / 0 Surface : 2 _____ (Reflective ground surface) Receiver source distance : 338.00 / 338.00 m -90 -20 0.00 62.04 0.00 -13.53 -4.10 0.00 0.00 Receiver height : 7.00 / 7.00 m 0.00 44.41 : 1 (Flat/gentle slope; no Topography barrier) Reference angle : 0.00 Segment Leg: 44.41 dBA Road data, segment # 2: FMC Road (day/night) _____ Results segment # 2: FMC Road (day) Car traffic volume : 5445/605 veh/TimePeriod * Medium truck volume : 54/6 veh/TimePeriod * Heavy truck volume : 85/9 veh/TimePeriod * Source height = 1.11 m Posted speed limit : 50 km/h ROAD (0.00 + 52.91 + 0.00) = 52.91 dBARoad gradient : 0 % Road pavement : 1 (Typical asphalt or concrete) Anglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq

* Refers to calculated road volumes based on the following input:

40 90 0.00 60.69 0.00 -2.22 -5.56 0.00 0.00 0.00 52.91 _____ Segment Leq: 52.91 dBA Total Leq All Segments: 53.48 dBA Results segment # 1: NiagaraStone (night) _____ Source height = 0.86 m ROAD (0.00 + 37.92 + 0.00) = 37.92 dBAAnglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq -90 -20 0.00 55.55 0.00 -13.53 -4.10 0.00 0.00 0.00 37.92 _____ Segment Leg: 37.92 dBA Results segment # 2: FMC Road (night) Source height = 1.10 m ROAD (0.00 + 46.28 + 0.00) = 46.28 dBAAnglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq ______ 40 90 0.00 54.06 0.00 -2.22 -5.56 0.00 0.00 0.00 46.28

Segment Leq: 46.28 dBA

Total Leg All Segments: 46.87 dBA

TOTAL Leq FROM ALL SOURCES (DAY): 53.48 (NIGHT): 46.87

STAMSON 5.0 NORMAL REPORT Date: 11-02-2025 16:03:12 MINISTRY OF ENVIRONMENT AND ENERGY / NOISE ASSESSMENT 24 hr Traffic Volume (AADT or SADT): 5090 Percentage of Annual Growth : 2.00 Filename: r06.te Time Period: Day/Night 16/8 hours Number of Years of Growth : 10.00 Medium Truck % of Total Volume : 0.96 Description: Office Building South Façade Heavy Truck % of Total Volume : 1.53 Road data, segment # 1: FMC Road (day/night) Day (16 hrs) % of Total Volume : 90.00 _____ Car traffic volume : 5445/605 veh/TimePeriod * Data for Segment # 2: FMC Rd 60 (day/night) Medium truck volume : 54/6 veh/TimePeriod * _____ Heavy truck volume : 85/9 veh/TimePeriod * Angle1 Angle2 : 60.00 deg 90.00 deg Posted speed limit : 50 km/h Wood depth : 0 (No woods.) No of house rows : 0 / 0 Surface : 2 (Reflective ground surface) Road gradient : 0 % : 1 (Typical asphalt or concrete) Road pavement Receiver source distance : 41.00 / 41.00 m * Refers to calculated road volumes based on the following input: Receiver height : 7.00 / 4.50 m : 1 (Flat/gentle slope; no Topography 24 hr Traffic Volume (AADT or SADT): 5090 barrier) Percentage of Annual Growth : 2.00 Reference angle : 0.00 Number of Years of Growth : 10.00 Medium Truck % of Total Volume : 0.96 Results segment # 1: FMC Road (day) Heavy Truck % of Total Volume : 1.53 _____ Day (16 hrs) % of Total Volume : 90.00 Source height = 1.11 m Data for Segment # 1: FMC Road (day/night) ROAD (0.00 + 58.14 + 0.00) = 58.14 dBAAngle1 Angle2 : -10.00 deg 90.00 deg Angle1 Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj Wood depth : 0 (No woods.) B.Adj SubLeq No of house rows : 0 / 0
Surface : 2 (Reflective ground surface) _____ Receiver source distance : 15.00 / 15.00 m -10 90 0.00 60.69 0.00 0.00 -2.55 0.00 0.00 Receiver height : 7.00 / 7.00 m 0.00 58.14 : 1 (Flat/gentle slope; no Topography barrier) Reference angle : 0.00 Segment Leg: 58.14 dBA Road data, segment # 2: FMC Rd 60 (day/night) _____ Results segment # 2: FMC Rd 60 (day) Car traffic volume : 5445/605 veh/TimePeriod * _____ Medium truck volume : 54/6 veh/TimePeriod * Heavy truck volume : 85/9 veh/TimePeriod * Source height = 1.11 m Posted speed limit : 60 km/h ROAD (0.00 + 50.28 + 0.00) = 50.28 dBARoad gradient : 0 % Road pavement : 1 (Typical asphalt or concrete) Anglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq

* Refers to calculated road volumes based on the following input:

60 90 0.00 62.43 0.00 -4.37 -7.78 0.00 0.00 0.00 50.28 _____ Segment Leq: 50.28 dBA Total Leq All Segments: 58.80 dBA Results segment # 1: FMC Road (night) _____ Source height = 1.10 m ROAD (0.00 + 51.51 + 0.00) = 51.51 dBAAnglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq -10 90 0.00 54.06 0.00 0.00 -2.55 0.00 0.00 0.00 51.51 _____ Segment Leg: 51.51 dBA Results segment # 2: FMC Rd 60 (night) _____ Source height = 1.10 m ROAD (0.00 + 43.67 + 0.00) = 43.67 dBAAnglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq ______ 60 90 0.00 55.81 0.00 -4.37 -7.78 0.00 0.00 0.00 43.67

Segment Leq: 43.67 dBA

Total Leg All Segments: 52.17 dBA

TOTAL Leq FROM ALL SOURCES (DAY): 58.80 (NIGHT): 52.17

STAMSON 5.0 NORMAL REPORT Date: 11-02-2025 16:03:34 MINISTRY OF ENVIRONMENT AND ENERGY / NOISE ASSESSMENT 24 hr Traffic Volume (AADT or SADT): 5090 Percentage of Annual Growth : 2.00 Filename: r07.te Time Period: Day/Night 16/8 hours Number of Years of Growth : 10.00 Description: Office Building East North Corner Façade Medium Truck % of Total Volume : 0.96 Heavy Truck % of Total Volume : 1.53 Road data, segment # 1: NiagaraStone (day/night) Day (16 hrs) % of Total Volume : 90.00 _____ Car traffic volume : 11476/1275 veh/TimePeriod * Data for Segment # 2: FMC Road (day/night) Medium truck volume : 38/4 veh/TimePeriod * Angle1 Angle2 : -90.00 deg 90.00 deg Heavy truck volume : 60/7 veh/TimePeriod * : 0 (No woods.) Posted speed limit : 50 km/h Wood depth No of house rows : 0 / 0 Surface : 2 (Reflective ground surface) Road gradient : 0 % : 1 (Typical asphalt or concrete) Road pavement Receiver source distance : 15.00 / 15.00 m * Refers to calculated road volumes based on the following input: Receiver height : 7.00 / 7.00 m : 1 (Flat/gentle slope; no Topography 24 hr Traffic Volume (AADT or SADT): 10550 barrier) Percentage of Annual Growth : 2.00 Reference angle : 0.00 Number of Years of Growth : 10.00 Medium Truck % of Total Volume : 0.33 Results segment # 1: NiagaraStone (day) Heavy Truck % of Total Volume : 0.52 _____ Day (16 hrs) % of Total Volume : 90.00 Source height = 0.85 m Data for Segment # 1: NiagaraStone (day/night) ROAD (0.00 + 46.42 + 0.00) = 46.42 dBAAngle1 Angle2 : -10.00 deg 90.00 deg Angle1 Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj Wood depth : 0 (No woods.) B.Adj SubLeq No of house rows : 0 / 0
Surface : 2 _____ (Reflective ground surface) Receiver source distance : 304.00 / 304.00 m -10 90 0.00 62.04 0.00 -13.07 -2.55 0.00 0.00 Receiver height : 7.00 / 7.00 m 0.00 46.42 : 1 (Flat/gentle slope; no Topography barrier) Reference angle : 0.00 Segment Leq: 46.42 dBA Road data, segment # 2: FMC Road (day/night) _____ Results segment # 2: FMC Road (day) Car traffic volume : 5445/605 veh/TimePeriod * Medium truck volume : 54/6 veh/TimePeriod * Heavy truck volume : 85/9 veh/TimePeriod * Source height = 1.11 m Posted speed limit : 50 km/h ROAD (0.00 + 60.69 + 0.00) = 60.69 dBARoad gradient : 0 % Road pavement : 1 (Typical asphalt or concrete) Anglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq

* Refers to calculated road volumes based on the following input:

90 0.00 60.69 0.00 0.00 0.00 0.00 0.00 0.00 60.69 _____ Segment Leg: 60.69 dBA Total Leq All Segments: 60.85 dBA Results segment # 1: NiagaraStone (night) _____ Source height = 0.86 m ROAD (0.00 + 39.93 + 0.00) = 39.93 dBAAnglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq -10 90 0.00 55.55 0.00 -13.07 -2.55 0.00 0.00 0.00 39.93 _____ Segment Leq: 39.93 dBA Results segment # 2: FMC Road (night) Source height = 1.10 m ROAD (0.00 + 54.06 + 0.00) = 54.06 dBAAnglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq ______ -90 90 0.00 54.06 0.00 0.00 0.00 0.00 0.00 0.00 54.06

Segment Leq: 54.06 dBA

Total Leg All Segments: 54.22 dBA

TOTAL Leq FROM ALL SOURCES (DAY): 60.85 (NIGHT): 54.22

STAMSON 5.0 NORMAL REPORT Date: 11-02-2025 16:03:56 MINISTRY OF ENVIRONMENT AND ENERGY / NOISE ASSESSMENT 24 hr Traffic Volume (AADT or SADT): Percentage of Annual Growth : 2.00 Filename: r08.te Time Period: Day/Night 16/8 hours Number of Years of Growth : 10.00 Description: Office Building East Façade South Corner Medium Truck % of Total Volume : 0.96 Heavy Truck % of Total Volume : 1.53 Road data, segment # 1: NiagaraStone (day/night) Day (16 hrs) % of Total Volume : 90.00 _____ Car traffic volume : 11476/1275 veh/TimePeriod * Data for Segment # 2: FMC Road (day/night) Medium truck volume : 38/4 veh/TimePeriod * Heavy truck volume : 60/7 veh/TimePeriod * : -90.00 deg 90.00 deg Angle1 Angle2 : 0 Posted speed limit : 50 km/h Wood depth (No woods.) : 0 / 0 Road gradient 0 % No of house rows Road pavement Surface : 2 (Reflective ground surface) : 1 (Typical asphalt or concrete) Receiver source distance : 15.00 / 15.00 m * Refers to calculated road volumes based on the following input: Receiver height : 7.00 / 7.00 m : 1 (Flat/gentle slope; no Topography 24 hr Traffic Volume (AADT or SADT): 10550 barrier) Percentage of Annual Growth : 2.00 Reference angle : 0.00 Number of Years of Growth : 10.00 Medium Truck % of Total Volume : 0.33 Road data, segment # 3: FMC Rd 60 (day/night) Heavy Truck % of Total Volume : 0.52 _____ Car traffic volume : 5445/605 veh/TimePeriod * Day (16 hrs) % of Total Volume : 90.00 Medium truck volume : 54/6 veh/TimePeriod * Heavy truck volume : 85/9 veh/TimePeriod * Data for Segment # 1: NiagaraStone (day/night) Posted speed limit : 60 km/h Angle1 Angle2 : -10.00 deg 90.00 deg Road gradient : 0 % Wood depth : 0 (No woods.) Road pavement 1 (Typical asphalt or concrete) No of house rows : 0 / 0 Surface : 2 (Reflective ground surface) * Refers to calculated road volumes based on the following input: Receiver source distance : 385.00 / 385.00 m Receiver height : 7.00 / 7.00 m24 hr Traffic Volume (AADT or SADT): 5090 : 1 (Flat/gentle slope; no Topography Percentage of Annual Growth : 2.00 Number of Years of Growth : 10.00 barrier) Reference angle : 0.00 Medium Truck % of Total Volume : 0.96 Heavy Truck % of Total Volume : 1.53 Road data, segment # 2: FMC Road (day/night) Day (16 hrs) % of Total Volume : 90.00 _____ Car traffic volume : 5445/605 veh/TimePeriod * Data for Segment # 3: FMC Rd 60 (day/night) Medium truck volume : 54/6 veh/TimePeriod * Heavy truck volume : 85/9 veh/TimePeriod * Angle1 Angle2 : 60.00 deg 90.00 deg Posted speed limit : 50 km/h : 0 Wood depth (No woods.) : 0 / 0 Road gradient : 0 % No of house rows : 2 Road pavement : 1 (Typical asphalt or concrete) Surface (Reflective ground surface) Receiver source distance : 51.00 / 51.00 m * Refers to calculated road volumes based on the following input: Receiver height : 7.00 / 4.50 m

barrier)	
Reference angle : 0.00	60 90 0.00 62.43 0.00 -5.31 -7.78 0.00 0.00 0.00 49.33
esults segment # 1: NiagaraStone (day)	
ource height = 0.85 m	Segment Leq: 49.33 dBA
OAD (0.00 + 45.40 + 0.00) = 45.40 dBA	Total Leq All Segments: 61.11 dBA
ngle1 Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj .Adj SubLeq	Results segment # 1: NiagaraStone (night)
-10 90 0.00 62.04 0.00 -14.09 -2.55 0.00 0.00 0.00 0.00 45.40	Source height = 0.86 m
	ROAD $(0.00 + 38.91 + 0.00) = 38.91 \text{ dBA}$
	Anglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq
egment Leq : 45.40 dBA	
esults segment # 2: FMC Road (day)	 -10 90 0.00 55.55 0.00 -14.09 -2.55 0.00 0.00
	0.00 38.91
Source height = 1.11 m	
ROAD (0.00 + 60.69 + 0.00) = 60.69 dBA	Segment Leq: 38.91 dBA
Anglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj	D 1
.Adj SubLeq	Results segment # 2: FMC Road (night)
-90 90 0.00 60.69 0.00 0.00 0.00 0.00 0.0	Source height = 1.10 m
	ROAD $(0.00 + 54.06 + 0.00) = 54.06 \text{ dBA}$
	Anglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj
egment Leg : 60.69 dBA	B.Adj SubLeq
esults segment # 3: FMC Rd 60 (day)	-90 90 0.00 54.06 0.00 0.00 0.00 0.00 0.00 0.00 54.06
Cource height = 1.11 m	
OAD (0.00 + 49.33 + 0.00) = 49.33 dBA	Segment Leq : 54.06 dBA
Anglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj	- 1

Results segment # 3: FMC Rd 60 (night)

Topography

B.Adj SubLeq

: 1 (Flat/gentle slope; no

Source height = 1.10 m

ROAD (0.00 + 42.72 + 0.00) = 42.72 dBA Anglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq

60 90 0.00 55.81 0.00 -5.31 -7.78 0.00 0.00 0.00 42.72

Segment Leq: 42.72 dBA

Total Leq All Segments: 54.49 dBA

TOTAL Leq FROM ALL SOURCES (DAY): 61.11 (NIGHT): 54.49

STAMSON 5.0 NORMAL REPORT Date: 11-02-2025 16:04:15 MINISTRY OF ENVIRONMENT AND ENERGY / NOISE ASSESSMENT 24 hr Traffic Volume (AADT or SADT): 5090 Percentage of Annual Growth : 2.00 Filename: r09.te Time Period: Day/Night 16/8 hours Number of Years of Growth : 10.00 Description: Office Building North Façade West Corner Medium Truck % of Total Volume : 0.96 Heavy Truck % of Total Volume : 1.53 Road data, segment # 1: NiagaraStone (day/night) Day (16 hrs) % of Total Volume : 90.00 _____ Car traffic volume : 11476/1275 veh/TimePeriod * Data for Segment # 2: FMC Road (day/night) Medium truck volume : 38/4 veh/TimePeriod * Angle1 Angle2 : -90.00 deg -10.00 deg Heavy truck volume : 60/7 veh/TimePeriod * : 0 (No woods.) Posted speed limit : 50 km/h Wood depth No of house rows : 0 / 0 Surface : 2 (Reflective ground surface) Road gradient : 0 % : 1 (Typical asphalt or concrete) Road pavement Receiver source distance : 29.00 / 29.00 m * Refers to calculated road volumes based on the following input: Receiver height : 7.00 / 7.00 m : 1 (Flat/gentle slope; no Topography 24 hr Traffic Volume (AADT or SADT): 10550 barrier) Percentage of Annual Growth : 2.00 Reference angle : 0.00 Number of Years of Growth : 10.00 Medium Truck % of Total Volume : 0.33 Results segment # 1: NiagaraStone (day) Heavy Truck % of Total Volume : 0.52 _____ Day (16 hrs) % of Total Volume : 90.00 Source height = 0.85 m Data for Segment # 1: NiagaraStone (day/night) ROAD (0.00 + 49.32 + 0.00) = 49.32 dBAAngle1 Angle2 : -90.00 deg 90.00 deg Angle1 Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj Wood depth : 0 (No woods.) B.Adj SubLeq No of house rows : 0 / 0
Surface : 2 (Reflective ground surface) _____ Receiver source distance : 281.00 / 281.00 m -90 90 0.00 62.04 0.00 -12.73 0.00 0.00 0.00 Receiver height : 7.00 / 7.00 m 0.00 49.32 : 1 (Flat/gentle slope; no Topography barrier) Reference angle : 0.00 Segment Leq: 49.32 dBA Road data, segment # 2: FMC Road (day/night) _____ Results segment # 2: FMC Road (day) Car traffic volume : 5445/605 veh/TimePeriod * _____ Medium truck volume : 54/6 veh/TimePeriod * Heavy truck volume : 85/9 veh/TimePeriod * Source height = 1.11 m Posted speed limit : 50 km/h ROAD (0.00 + 54.30 + 0.00) = 54.30 dBARoad gradient : 0 % Road pavement : 1 (Typical asphalt or concrete) Anglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq

* Refers to calculated road volumes based on the following input:

-90 -10 0.00 60.69 0.00 -2.86 -3.52 0.00 0.000.00 54.30 _____ Segment Leq: 54.30 dBA Total Leq All Segments: 55.50 dBA Results segment # 1: NiagaraStone (night) _____ Source height = 0.86 m ROAD (0.00 + 42.83 + 0.00) = 42.83 dBAAnglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq -90 90 0.00 55.55 0.00 -12.73 0.00 0.00 0.00 0.00 42.83 _____ Segment Leg: 42.83 dBA Results segment # 2: FMC Road (night) Source height = 1.10 m ROAD (0.00 + 47.68 + 0.00) = 47.68 dBAAnglel Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq ______ -90 -10 0.00 54.06 0.00 -2.86 -3.52 0.00 0.000.00 47.68

Segment Leq: 47.68 dBA

Total Leg All Segments: 48.91 dBA

TOTAL Leq FROM ALL SOURCES (DAY): 55.50 (NIGHT): 48.91

STAMSON 5.0 NORMAL REPORT Date: 11-02-2025 16:04:33 MINISTRY OF ENVIRONMENT AND ENERGY / NOISE ASSESSMENT Filename: r10.te Time Period: Day/Night 16/8 hours Description: Residential Building West Façade South Corner Road data, segment # 1: NiagaraStone (day/night) _____ Car traffic volume : 11476/1275 veh/TimePeriod * Medium truck volume : 38/4 veh/TimePeriod * Heavy truck volume : 60/7 veh/TimePeriod * Posted speed limit : 50 km/h Road gradient : 0 % Road pavement : 1 (Typical asphalt or concrete) * Refers to calculated road volumes based on the following input: 24 hr Traffic Volume (AADT or SADT): 10550 Percentage of Annual Growth : 2.00 Number of Years of Growth : 10.00 Medium Truck % of Total Volume : 0.33 Heavy Truck % of Total Volume : 0.52 Day (16 hrs) % of Total Volume : 90.00 Data for Segment # 1: NiagaraStone (day/night) _____ Angle1 Angle2 : -90.00 deg 20.00 deg Wood depth : 0 (No woods.) No of house rows : 0 / 0 Surface : 2 (Reflective ground surface) Receiver source distance : 350.00 / 350.00 m Receiver height : 12.75 / 12.75 m $\,$: 1 (Flat/gentle slope; no Topography barrier) Reference angle : 0.00 Results segment # 1: NiagaraStone (day) _____ Source height = 0.85 m ROAD (0.00 + 46.23 + 0.00) = 46.23 dBAAngle1 Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj B.Adj SubLeq

```
-90 20 0.00 62.04 0.00 -13.68 -2.14 0.00 0.00
0.00 46.23
______
Segment Leg: 46.23 dBA
Total Leq All Segments: 46.23 dBA
Results segment # 1: NiagaraStone (night)
_____
Source height = 0.86 m
ROAD (0.00 + 39.74 + 0.00) = 39.74 dBA
Angle1 Angle2 Alpha RefLeq P.Adj D.Adj F.Adj W.Adj H.Adj
B.Adj SubLeq
______
-90 20 0.00 55.55 0.00 -13.68 -2.14 0.00 0.00
0.00 39.74
_____
Segment Leg: 39.74 dBA
Total Leg All Segments: 39.74 dBA
TOTAL Leg FROM ALL SOURCES (DAY): 46.23
                (NIGHT): 39.74
```

APPENDIX D

SAMPLE CADNA/A ANALYSIS

Project: 1544 & 1546 Four Mile Creek Rd, Niagara-on-the-Lake Project Number: 25253

S15	Source ID	Source Name	Point of Distance to POR (m)	f Reception RP02 Sound Level at POR (dBA) Day		Reception RP01 Sound Level at POR (dBA) Day	Point of Distance to POR (m)	Reception RP04 Sound Level at POR (dBA) Day		f Reception RP05 Sound Level at POR (dBA) Day		Reception RP03 Sound Level at POR (dBA) Day		Reception RP07 Sound Level at POR (dBA) Day		f Reception RP06 Sound Level at POR (dBA) Day
S88	S15	HVAC RTU	245		204		188		252		257		192		253	
SSE	S14	HVAC RTU	248	14	207	26	190	26	254	5	260	3	194	26	254	5
STILL HWACKTU 284 8 247 27 216 28 288 6 293 8 217 28 263 13	S08	HVAC RTU	276	8	239	27	207	28	257	6	283	9	207	28	251	14
SSS	S26	HVAC RTU	282	25	311	12	346	9	321	24	279	26	348	4	333	24
STORY HAMBERTU 287 8 250 277 219 28 270 6 295 6 219 28 224 13 3 3 3 3 3 3 3 3	S11	HVAC RTU	284	8	247	27	216	28	268	6	293	8	217	28	263	13
SSZ		HVAC RTU	286	7			219		257	7	291	9	218		248	16
\$\frac{\cong}{\cong}\$ \text{HAVERTU} 290 22 310 9 346 14 336 21 291 22 349 1 349 12 348	\$10	HVAC RTU	287	8	250	27	219	28	270	6	295	8	219	28	264	13
SSA	S27	HVAC RTU	288	25	319	11	353	8	327	24	286	25	355	3	339	24
Sign	S25	HVAC RTU	290	22	310	9	346	14	336	21	291	22	349	1	349	12
SS6 HARCRIU 300 2 266 23 232 25 276 2 307 3 231 25 269 8 8 S19 HWACRIU 330 24 289 25 274 26 338 8 342 6 278 25 348 9 S21 HWACRIU 331 24 290 25 277 25 341 9 343 7 222 25 342 8 S20 HWACRIU 331 24 290 25 277 25 341 9 343 7 222 25 342 8 S26 HWACRIU 334 6 304 25 269 26 301 6 338 9 266 26 291 15 S27 25 341 9 343 7 222 25 5 342 8 S28 HARCRIU 355 6 306 25 271 26 303 6 339 9 266 26 29 11 S33 HWACRIU 345 5 315 24 279 25 314 6 350 8 277 25 374 15 S28 HARCRIU 345 5 315 24 279 25 314 6 350 8 277 25 305 15 S28 HARCRIU 331 9 289 22 271 26 333 4 6 350 8 277 25 305 15 S28 HARCRIU 331 9 289 22 271 25 344 6 350 8 277 25 305 15 S28 HARCRIU 331 9 289 22 271 24 25 344 20 279 25 314 6 350 8 5 277 25 305 15 S28 HARCRIU 331 9 289 22 271 24 279 25 344 50 225 274 274 274 275 274 275 375 15 S27 HARCRIU 331 9 289 22 271 271 271 271 271 271 271 271 271		HVAC RTU					255		285	7	322		252			16
S19	S18	HVAC RTU	327	24	287	25	276	26	341	11	340	7	281	25	342	8
S21										_						_
S20										10		7				
S05										_						
S06 HWACRTU 335 6 306 25 271 26 303 6 339 9 288 26 26 293 15 \$33 HWACRTU 317 5 288 24 252 25 283 5 321 8 250 25 274 15 \$57 HWACRTU 345 5 315 24 279 25 314 6 350 8 277 25 305 15 \$28 HWACRTU 329 21 362 4 396 2 364 20 325 21 397 1 375 20 \$24 HWACRTU 331 9 289 22 271 23 334 3 342 2 274 23 333 4 \$32 HWACRTU 410 22 428 12 464 21 459 21 412 22 466 5 470 5 470 113 \$31 HWACRTU 410 22 429 11 464 21 459 21 412 22 466 5 470 5 470 113 \$31 HWACRTU 240 13 204 24 187 24 250 6 257 5 100 24 250 7 \$50 HWACRTU 250 3 23 232 17 197 17 206 5 250 8 193 24 195 18 \$50 HWACRTU 309 2 2 293 15 288 15 264 4 308 7 253 21 252 21 252 21 253 21 252 253 254 253 254 254 254 255 255 255 255 255 255 255										9		-				
\$33 HMCRIU 337 5 288 24 252 25 223 5 321 8 250 25 224 15 \$507 HMCRIU 345 5 315 24 279 25 314 6 350 8 277 25 305 15 \$528 HMCRIU 329 21 362 4 396 2 364 20 325 21 397 1 375 20 \$524 HMCRIU 331 9 289 22 271 23 334 3 342 2 274 23 333 4 \$532 HMCRIU 410 22 478 12 464 21 458 21 412 22 468 5 471 13 \$531 HMCRIU 411 22 429 12 464 21 459 21 413 22 468 5 471 13 \$533 HMCRIU 246 13 204 24 187 24 250 6 257 5 190 24 250 7 \$501 HMCRIU 270 3 232 17 197 17 206 5 250 8 193 24 195 18 \$502 HMCRIU 272 3 256 16 221 16 228 5 272 8 216 23 216 18 \$503 HMCRIU 309 2 293 15 258 15 264 4 308 7 253 21 252 21 25 \$516 HMCRIU 158 9 119 29 91 31 147 8 163 6 89 31 145 12 \$517 HMCRIU 158 9 119 29 91 31 149 7 167 6 92 31 147 12 \$516 HMCRIU 158 9 119 29 91 31 149 7 167 6 92 31 147 12 \$509 HMCRIU 268 2 237 17 202 19 239 2 273 3 200 19 230 8 \$517 HMCRIU 268 2 237 17 202 19 239 2 273 3 200 19 230 8 \$518 HMCRIU 264 6 224 23 198 24 255 3 274 5 199 24 251 8 \$520 HMCRIU 337 13 295 20 279 21 344 5 346 359 19 433 1 404 18 18 350 19 433 1 404 18 350 19 433 1 404 18 350 19 433 1 404 18 350 19 433 1 404 18 350 19 433 1 404 18 350 19 433 1 404 18 350 19 433 1 404 18 350 300																
S77												-				
S28										-						
S24																
\$32																
S31 HWACRIU 411 22 429 12 464 21 459 21 413 22 468 5 471 13 S13 HWACRIU 246 13 204 24 167 24 250 6 257 5 190 24 250 7 S01 HWACRIU 250 3 232 17 197 17 206 5 250 8 193 24 195 18 S02 HWACRIU 272 3 256 16 221 16 228 5 272 8 216 23 216 18 S03 HWACRIU 309 2 293 15 258 15 264 4 308 7 253 21 252 16 S17 HWACRIU 154 9 114 29 87 31 147 8 163 6 89 31 145 12 S16 HWACRIU 158 9 119 29 91 31 147 8 163 6 89 31 145 12 S16 HWACRIU 158 9 119 29 91 31 149 7 167 6 92 31 147 12 S17 HWACRIU 158 9 119 29 91 31 149 7 167 6 92 31 147 12 S04 HWACRIU 332 2 237 17 202 19 239 2 273 3 200 19 230 8 S17 HWACRIU 264 6 224 23 198 24 255 3 272 3 3 200 19 230 8 S18 S17 HWACRIU 264 6 224 23 198 24 255 3 272 3 276 5 9 S18 S18 HWACRIU 274 332 2 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3																
S13																
SOI																13
S02																/
S03																
S17										_						
S16				_								-				
SO4 HWAC RTU 332 2 317 14 282 14 287 4 331 7 277 20 275 20 537 HVAC RTU 268 2 237 17 202 19 239 2 273 3 200 19 230 8 512 HVAC RTU 264 6 224 23 198 24 255 3 274 5 199 24 251 8 509 HVAC RTU 290 4 253 22 222 23 272 3 298 5 222 23 265 9 538 HWAC RTU 324 15 283 21 268 21 332 5 366 3 272 21 332 5 522 HVAC RTU 336 14 295 20 290 21 344 5 348 3 264 21 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>_</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>										_						
S37 HWACRIU 268 2 237 17 202 19 239 2 273 3 200 19 230 8 S12 HWACRIU 264 6 224 23 198 24 255 3 274 5 199 24 251 8 S09 HWACRIU 290 4 253 22 23 272 3 298 5 222 23 265 9 S38 HWACRIU 324 15 283 21 268 21 332 5 336 3 277 21 332 5 S22 HWACRIU 336 14 295 20 290 21 344 5 348 3 294 21 344 5 S23 HWACRIU 337 13 295 20 279 21 343 4 349 3 283 21 342 5 S29 HWACRIU 337 19 333 5 414 2 372 18 339 19 414 1 382 18 S29 HWACRIU 336 18 401 5 433 2 394 18 359 19 433 1 404 18				9								0				
S12 HVAC RTU 264 6 224 23 198 24 255 3 274 5 199 24 251 8 509 HVAC RTU 290 4 253 22 222 23 265 9 5 222 23 265 9 538 HVAC RTU 324 15 283 21 268 21 332 5 336 3 272 21 332 5 522 HVAC RTU 336 14 295 20 280 21 344 5 348 3 284 21 344 5 523 HVAC RTU 337 13 295 20 279 21 343 4 349 3 283 21 342 5 529 HVAC RTU 335 19 383 5 414 2 372 18 339 19 414 1 382 <td></td> <td></td> <td></td> <td>2</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>2</td> <td></td> <td></td> <td></td> <td></td>				2								2				
S09 HVAC RTU 290 4 253 22 222 23 272 3 298 5 222 23 265 9 S38 HVAC RTU 324 15 283 21 268 21 332 5 336 3 272 21 332 5 S22 HVAC RTU 336 14 295 20 280 21 344 5 348 3 284 21 344 5 S23 HVAC RTU 337 13 295 20 279 21 343 4 349 3 283 21 342 5 S29 HVAC RTU 345 19 383 5 414 2 372 18 339 19 414 1 382 18 S30 HVAC RTU 365 18 401 5 433 2 394 18 359 19 433 1 404 18																
\$38 HVAC RTU 324 15 283 21 268 21 332 5 336 3 272 21 332 5 \$22 HVAC RTU 336 14 295 20 280 21 344 5 348 3 284 21 344 5 \$23 HVAC RTU 337 13 295 20 279 21 343 4 349 3 283 21 342 5 \$29 HVAC RTU 345 19 383 5 414 2 372 18 339 19 414 1 382 18 \$30 HVAC RTU 365 18 401 5 433 2 394 18 359 19 433 1 404 18										· ·						
S22 HVAC RTU 336 14 295 20 280 21 344 5 348 3 284 21 344 5 S23 HVAC RTU 337 13 295 20 279 21 343 4 349 3 283 21 342 5 S29 HVAC RTU 345 19 383 5 414 2 372 18 339 19 414 1 382 18 S30 HVAC RTU 365 18 401 5 433 2 394 18 359 19 433 1 404 18																
523 HNACRTU 337 13 295 20 279 21 343 4 349 3 283 21 342 5 529 HVACRTU 345 19 383 5 414 2 372 18 339 19 414 1 382 18 530 HVACRTU 365 18 401 5 433 2 394 18 359 19 433 1 404 18										_		_				_
S29 HVACRTU 345 19 383 5 414 2 372 18 339 19 414 1 382 18 S30 HVACRTU 365 18 401 5 433 2 394 18 359 19 433 1 404 18 - 18																
S30 HVACRTU 365 18 401 5 433 2 394 18 359 19 433 1 404 18																_
			303	34	.51	39	.55	41	374	31	337	32	.00	41	.04	31



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	39

Receiver Name	Receiver ID	Х																	
RP01	RP01	17652528.55 m	4786794.33 m	12.75 m															
Source ID	Source Name	X			Refl.	Lw	L/A	Freq	Adiv	K0	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	67	0.0	63	57.2	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-0.9	0.0	12
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	80	0.0	125	57.2	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.7	0.0	21
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	84	0.0	250	57.2	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.7	0.0	21
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	87	0.0	500	57.2	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-9.9	0.0	22
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	89	0.0	1000	57.2	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-10.9	0.0	23
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	85	0.0	2000	57.2	0.0	-3.0	0.0	2.0	0.0	0.0	0.0	-11.9	0.0	17
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	78	0.0	4000	57.2	0.0	-3.0	0.0	6.7	0.0	0.0	0.0	-12.9	0.0	4
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	61	0.0	125	57.3	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.7	0.0	2
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	72	0.0	250	57.3	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.7	0.0	9
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	84	0.0	500	57.3	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-9.9	0.0	19
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	89	0.0	1000	57.3	0.0	-3.0	0.0	0.8	0.0	0.0	0.0	-10.9	0.0	23
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	87	0.0	2000	57.3	0.0	-3.0	0.0	2.0	0.0	0.0	0.0	-11.9	0.0	19
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	81	0.0	4000	57.3	0.0	-3.0	0.0	6.8	0.0	0.0	0.0	-12.9	0.0	7
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	67	0.0	63	58.6	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-0.9	0.0	10
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	80	0.0	125	58.6	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	20
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	84	0.0	250	58.6	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.8	0.0	20
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	87	0.0	500	58.6	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-9.9	0.0	21
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	89	0.0	1000	58.6	0.0	-3.0	0.0	0.9	0.0	0.0	0.0	-10.9	0.0	22
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	85	0.0	2000	58.6	0.0	-3.0	0.0	2.3	0.0	0.0	0.0	-11.9	0.0	15
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	78	0.0	4000	58.6	0.0	-3.0	0.0	7.8	0.0	0.0	0.0	-12.9	0.0	2
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	67	0.0	63	58.8	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-0.9	0.0	10
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	80	0.0	125	58.8	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	19
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	84	0.0	250	58.8	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	20
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	87	0.0	500	58.8	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-9.9	0.0	21
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	89	0.0	1000	58.8	0.0	-3.0	0.0	0.9	0.0	0.0	0.0	-10.9	0.0	21
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	85	0.0	2000	58.8	0.0	-3.0	0.0	2.4	0.0	0.0	0.0	-11.9	0.0	15
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	78	0.0	4000	58.8	0.0	-3.0	0.0	8.1	0.0	0.0	0.0	-12.9	0.0	1
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	67	0.0	63	58.9	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-0.9	0.0	10
\$10	HVAC RTU	17652667.8	4787001.4	5.5	0	80	0.0	125	58.9	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	19
\$10	HVAC RTU	17652667.8	4787001.4	5.5	0	84	0.0	250	58.9	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	19
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	87	0.0	500	58.9	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-9.9	0.0	20
\$10	HVAC RTU	17652667.8	4787001.4	5.5	0	89	0.0	1000	58.9	0.0	-3.0	0.0	0.9	0.0	0.0	0.0	-10.9	0.0	21
\$10	HVAC RTU	17652667.8	4787001.4	5.5	0	85	0.0	2000	58.9	0.0	-3.0	0.0	2.4	0.0	0.0	0.0	-11.9	0.0	15
\$10	HVAC RTU	17652667.8	4787001.4	5.5	0	78	0.0	4000	58.9	0.0	-3.0	0.0	8.2	0.0	0.0	0.0	-12.9	0.0	1
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	67	0.0	63	59.1	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-0.9	0.0	10
\$35	HVAC RTU	17652724.4	4786956.5	5.5	0	80	0.0	125	59.1	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	19
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	84	0.0	250	59.1	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	19
\$35 \$35	HVAC RTU HVAC RTU	17652724.4 17652724.4	4786956.5 4786956.5	5.5 5.5	0	87	0.0	500	59.1 59.1	0.0	-3.0 -3.0	0.0	0.5	0.0	0.0	0.0	-9.9 -10.9	0.0	20
\$35 \$35				5.5	0	89 85	0.0	1000 2000	59.1	0.0	-3.0	0.0	2.5	0.0	0.0	0.0	-10.9	0.0	21
	HVAC RTU	17652724.4	4786956.5		_														15
S35 S18	HVAC RTU HVAC RTU	17652724.4 17652494.0	4786956.5	5.5 5.5	0	78 67	0.0	4000 63	59.1 60.2	0.0	-3.0 -3.0	0.0	8.3 0.0	0.0	0.0	0.0	-12.9 -1.0	0.0	9
\$18 \$18		17652494.0	4787078.9 4787078.9	5.5	0	80	0.0	125	60.2	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-4.8	0.0	18
\$18 \$18	HVAC RTU HVAC RTU		4787078.9	5.5	0	84	0.0	250		0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-8.8	0.0	18
318	HVACKIU	17652494.0	4/0/0/0.9	5.5	U	ō4	0.0	200	60.2	0.0	-3.0	0.0	0.3	U.U	U.U	U.U	-0.0	0.0	10



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	39

Receiver Name	Receiver ID	X																	
RP01	RP01	17652528.55 m	4786794.33 m	12.75 m															
Source ID	Source Name	Х			Refl.	Lw	L/A	Freq	Adiv	KO	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	87	0.0	500	60.2	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	19
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	89	0.0	1000	60.2	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	85	0.0	2000	60.2	0.0	-3.0	0.0	2.8	0.0	0.0	0.0	-12.0	0.0	13
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	67	0.0	63	60.2	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	80	0.0	125	60.2	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	18
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	84	0.0	250	60.2	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	18
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	87	0.0	500	60.2	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	19
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	89	0.0	1000	60.2	0.0	-3.0	0.0	1.1	0.0	0.0	0.0	-11.0	0.0	20
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	85	0.0	2000	60.2	0.0	-3.0	0.0	2.8	0.0	0.0	0.0	-12.0	0.0	13
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	67	0.0	63	60.2	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	80	0.0	125	60.2	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	18
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	84	0.0	250	60.2	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	18
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	87	0.0	500	60.2	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	19
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	89	0.0	1000	60.2	0.0	-3.0	0.0	1.1	0.0	0.0	0.0	-11.0	0.0	20
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	85	0.0	2000	60.2	0.0	-3.0	0.0	2.8	0.0	0.0	0.0	-12.0	0.0	13
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	67	0.0	63	60.2	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	80	0.0	125	60.2	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	18
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	84	0.0	250	60.2	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	18
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	87	0.0	500	60.2	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	19
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	89	0.0	1000	60.2	0.0	-3.0	0.0	1.1	0.0	0.0	0.0	-11.0	0.0	20
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	85	0.0	2000	60.2	0.0	-3.0	0.0	2.8	0.0	0.0	0.0	-12.0	0.0	13
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	67	0.0	63	60.3	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	80	0.0	125	60.3	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	18
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	84	0.0	250	60.3	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	18
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	87	0.0	500	60.3	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	19
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	89	0.0	1000	60.3	0.0	-3.0	0.0	1.1	0.0	0.0	0.0	-11.0	0.0	20
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	85	0.0	2000	60.3	0.0	-3.0	0.0	2.8	0.0	0.0	0.0	-12.0	0.0	13
\$36	HVAC RTU	17652710.3	4786988.4	5.5	0	72	0.0	250	59.5	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	7
S36	HVAC RTU	17652710.3	4786988.4	5.5	0	84	0.0	500	59.5	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-9.9	0.0	17
S36	HVAC RTU	17652710.3	4786988.4	5.5	0	89	0.0	1000	59.5	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-10.9	0.0	21
S36	HVAC RTU	17652710.3	4786988.4	5.5	0	87	0.0	2000	59.5	0.0	-3.0	0.0	2.6	0.0	0.0	0.0	-11.9	0.0	16
\$36	HVAC RTU	17652710.3	4786988.4	5.5	0	81	0.0	4000	59.5	0.0	-3.0	0.0	8.7	0.0	0.0	0.0	-12.9	0.0	3
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	67	0.0	63	60.7	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	8
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	80	0.0	125	60.7	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	17
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	84	0.0	250	60.7	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	18
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	87	0.0	500	60.7	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	19
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	89	0.0	1000	60.7	0.0	-3.0	0.0	1.1	0.0	0.0	0.0	-11.0	0.0	19
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	85	0.0	2000	60.7	0.0	-3.0	0.0	2.9	0.0	0.0	0.0	-12.0	0.0	13
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	67	0.0	63	60.7	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	8
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	80	0.0	125	60.7	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	17
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	84	0.0	250	60.7	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	18
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	87	0.0	500	60.7	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	19
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	89	0.0	1000	60.7	0.0	-3.0	0.0	1.1	0.0	0.0	0.0	-11.0	0.0	19
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	85	0.0	2000	60.7	0.0	-3.0	0.0	3.0	0.0	0.0	0.0	-12.0	0.0	13



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	39

Receiver Name	Receiver ID	X	Υ																
RP01	RP01	17652528.55 m	4786794.33 m	12.75 m															
	<u>'</u>																		
Source ID	Source Name	Y	٧	7	Refl.	Lw	L/A	Freq	Adiv	K0	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	67	0.0	63	60.9	0.0	-3.0	7.5	0.0	0.0	0.0	0.0	-1.0	0.0	0
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	80	0.0	125	60.9	0.0	-3.0	9.6	0.0	0.0	0.0	0.0	-4.8	0.0	8
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	84	0.0	250	60.9	0.0	-3.0	12.2	0.3	0.0	0.0	0.0	-8.8	0.0	5
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	87	0.0	500	60.9	0.0	-3.0	15.1	0.6	0.0	0.0	0.0	-10.0	0.0	3
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	89	0.0	1000	60.9	0.0	-3.0	17.9	1.1	0.0	0.0	0.0	-11.0	0.0	1
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	65	0.0	63	60.2	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	7
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	78	0.0	125	60.2	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	16
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	83	0.0	250	60.2	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	17
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	87	0.0	500	60.2	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	19
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	87	0.0	1000	60.2	0.0	-3.0	0.0	1.1	0.0	0.0	0.0	-11.0	0.0	18
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	85	0.0	2000	60.2	0.0	-3.0	0.0	2.8	0.0	0.0	0.0	-12.0	0.0	13
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	81	0.0	4000	60.2	0.0	-3.0	0.0	9.4	0.0	0.0	0.0	-13.0	0.0	1
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	67	0.0	63	61.0	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	8
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	80	0.0	125	61.0	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	17
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	84	0.0	250	61.0	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	17
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	87	0.0	500	61.0	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	18
				_					-										
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	89	0.0	1000	61.0	0.0	-3.0	0.0	1.2	0.0	0.0	0.0	-11.0	0.0	19
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	85	0.0	2000	61.0	0.0	-3.0	0.0	3.0	0.0	0.0	0.0	-12.0	0.0	12
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	72	0.0	250	60.2	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	6
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	84	0.0	500	60.2	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	16
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	89	0.0	1000	60.2	0.0	-3.0	0.0	1.1	0.0	0.0	0.0	-11.0	0.0	20
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	87	0.0	2000	60.2	0.0	-3.0	0.0	2.8	0.0	0.0	0.0	-12.0	0.0	15
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	81	0.0	4000	60.2	0.0	-3.0	0.0	9.5	0.0	0.0	0.0	-13.0	0.0	1
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	67	0.0	63	61.1	0.0	-3.0	7.7	0.0	0.0	0.0	0.0	-1.0	0.0	0
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	80	0.0	125	61.1	0.0	-3.0	9.8	0.1	0.0	0.0	0.0	-4.8	0.0	7
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	84	0.0	250	61.1	0.0	-3.0	12.5	0.3	0.0	0.0	0.0	-8.8	0.0	5
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	87	0.0	500	61.1	0.0	-3.0	15.3	0.6	0.0	0.0	0.0	-10.0	0.0	3
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	89	0.0	1000	61.1	0.0	-3.0	18.2	1.2	0.0	0.0	0.0	-11.0	0.0	1
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	84	0.0	500	60.8	0.0	-3.0	11.8	0.6	0.0	0.0	0.0	-10.0	0.0	4
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	89	0.0	1000	60.8	0.0	-3.0	14.4	1.1	0.0	0.0	0.0	-11.0	0.0	5
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	62	0.0	63	57.2	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-0.9	0.0	7
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	75	0.0	125	57.2	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.7	0.0	16
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	80	0.0	250	57.2	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.7	0.0	17
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	83	0.0	500	57.2	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-9.9	0.0	18
\$13	HVAC RTU	17652551.9	4786997.1	5.5	0	82	0.0	1000	57.2	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-10.9	0.0	16
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	80	0.0	2000	57.2	0.0	-3.0	0.0	2.0	0.0	0.0	0.0	-11.9	0.0	12
\$13	HVAC RTU	17652551.9	4786997.1	5.5	0	77	0.0	4000	57.2	0.0	-3.0	0.0	6.7	0.0	0.0	0.0	-12.9	0.0	3
S01	HVACRTU	17652754.0	4786849.6	8.0	0	61	0.0	63	58.3	0.0	-3.0	4.2	0.0	0.0	0.0	0.0	-12.9	0.0	0
				_			_	_											
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	74	0.0	125	58.3	0.0	-3.0	4.5	0.1	0.0	0.0	0.0	-4.8	0.0	9
S01	HVACRTU	17652754.0	4786849.6	8.0	0	79	0.0	250	58.3	0.0	-3.0	4.7	0.2	0.0	0.0	0.0	-8.8	0.0	10
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	83	0.0	500	58.3	0.0	-3.0	5.0	0.4	0.0	0.0	0.0	-10.0	0.0	12
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	82	0.0	1000	58.3	0.0	-3.0	5.3	0.8	0.0	0.0	0.0	-11.0	0.0	10
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	81	0.0	2000	58.3	0.0	-3.0	5.9	2.2	0.0	0.0	0.0	-12.0	0.0	6
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	76	0.0	125	52.2	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-4.5	0.0	22



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	39

Receiver Name	Receiver ID	X																	
RP01	RP01	17652528.55 m	4786794.33 m	12.75 m															
Source ID	Source Name	Х			Refl.	Lw	L/A	Freq	Adiv	K0	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	79	0.0	250	52.2	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-8.5	0.0	21
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	84	0.0	500	52.2	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-9.9	0.0	25
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	83	0.0	1000	52.2	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.9	0.0	23
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	79	0.0	2000	52.2	0.0	-3.0	0.0	1.1	0.0	0.0	0.0	-11.9	0.0	17
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	73	0.0	4000	52.2	0.0	-3.0	0.0	3.7	0.0	0.0	0.0	-12.9	0.0	7
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	80	0.0	125	63.6	0.0	-3.0	6.7	0.2	0.0	0.0	0.0	-4.9	0.0	8
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	84	0.0	250	63.6	0.0	-3.0	8.4	0.4	0.0	0.0	0.0	-8.9	0.0	6
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	87	0.0	500	63.6	0.0	-3.0	10.5	8.0	0.0	0.0	0.0	-10.0	0.0	5
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	89	0.0	1000	63.6	0.0	-3.0	13.0	1.6	0.0	0.0	0.0	-11.0	0.0	3
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	80	0.0	125	63.6	0.0	-3.0	6.6	0.2	0.0	0.0	0.0	-4.9	0.0	8
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	84	0.0	250	63.6	0.0	-3.0	8.3	0.4	0.0	0.0	0.0	-8.9	0.0	6
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	87	0.0	500	63.6	0.0	-3.0	10.4	0.8	0.0	0.0	0.0	-10.0	0.0	5
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	89	0.0	1000	63.6	0.0	-3.0	12.8	1.6	0.0	0.0	0.0	-11.0	0.0	3
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	76	0.0	125	52.5	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-4.5	0.0	22
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	79	0.0	250	52.5	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-8.5	0.0	21
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	84	0.0	500	52.5	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-9.9	0.0	24
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	83	0.0	1000	52.5	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.9	0.0	22
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	79	0.0	2000	52.5	0.0	-3.0	0.0	1.2	0.0	0.0	0.0	-11.9	0.0	16
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	73	0.0	4000	52.5	0.0	-3.0	0.0	3.9	0.0	0.0	0.0	-12.9	0.0	7
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	74	0.0	125	59.2	0.0	-3.0	4.5	0.1	0.0	0.0	0.0	-4.9	0.0	8
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	79	0.0	250	59.2	0.0	-3.0	4.8	0.3	0.0	0.0	0.0	-8.9	0.0	9
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	83	0.0	500	59.2	0.0	-3.0	5.1	0.5	0.0	0.0	0.0	-10.0	0.0	11
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	82	0.0	1000	59.2	0.0	-3.0	5.6	0.9	0.0	0.0	0.0	-11.0	0.0	8
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	81	0.0	2000	59.2	0.0	-3.0	6.4	2.5	0.0	0.0	0.0	-12.0	0.0	4
S03	HVAC RTU	17652813.6	4786860.2	8.0	0	74	0.0	125	60.3	0.0	-3.0	4.5	0.1	0.0	0.0	0.0	-4.9	0.0	7
S03	HVAC RTU	17652813.6	4786860.2	8.0	0	79	0.0	250	60.3	0.0	-3.0	4.8	0.3	0.0	0.0	0.0	-8.9	0.0	8
S03	HVAC RTU	17652813.6	4786860.2	8.0	0	83	0.0	500	60.3	0.0	-3.0	5.1	0.6	0.0	0.0	0.0	-10.0	0.0	10
S03	HVAC RTU	17652813.6	4786860.2	8.0	0	82	0.0	1000	60.3	0.0	-3.0	5.5	1.1	0.0	0.0	0.0	-11.0	0.0	7
S03	HVAC RTU	17652813.6	4786860.2	8.0	0	81	0.0	2000	60.3	0.0	-3.0	6.2	2.8	0.0	0.0	0.0	-12.0	0.0	3
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	74	0.0	125	61.0	0.0	-3.0	4.5	0.1	0.0	0.0	0.0	-4.9	0.0	6
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	79	0.0	250	61.0	0.0	-3.0	4.8	0.3	0.0	0.0	0.0	-8.9	0.0	7
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	83	0.0	500	61.0	0.0	-3.0	5.2	0.6	0.0	0.0	0.0	-10.0	0.0	9
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	82	0.0	1000	61.0	0.0	-3.0	5.7	1.2	0.0	0.0	0.0	-11.0	0.0	6
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	81	0.0	2000	61.0	0.0	-3.0	6.5	3.1	0.0	0.0	0.0	-12.0	0.0	2
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	62	0.0	63	58.5	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-0.9	0.0	6
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	70	0.0	125	58.5	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	10
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	72	0.0	250	58.5	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.8	0.0	7
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	79	0.0	500	58.5	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-9.9	0.0	13
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	76	0.0	1000	58.5	0.0	-3.0	0.0	0.9	0.0	0.0	0.0	-10.9	0.0	9
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	75	0.0	2000	58.5	0.0	-3.0	0.0	2.3	0.0	0.0	0.0	-11.9	0.0	5
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	76	0.0	125	58.0	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	16
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	79	0.0	250	58.0	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.8	0.0	15
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	84	0.0	500	58.0	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-9.9	0.0	19
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	83	0.0	1000	58.0	0.0	-3.0	0.0	0.8	0.0	0.0	0.0	-10.9	0.0	16



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	39

Receiver Name	Receiver ID	Х																	
RP01	RP01	17652528.55 m	4786794.33 m	12.75 m															
Source ID	Source Name	V	γ	7	Refl.	Luc	1./^	From	Adiv	KO	Agr	Abor	Actm	Afol	Ahous	Cmet	Dc	RL	lr
		X 47/50/00 0			ReII.	Lw	L/A	Freq		K0	Agr	Abar	Aatm						
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	79	0.0	2000	58.0	0.0	-3.0	0.0	2.2	0.0	0.0	0.0	-11.9	0.0	10
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	76	0.0	125	59.1	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	15
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	79	0.0	250	59.1	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	14
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	84	0.0	500	59.1	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-9.9	0.0	18
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	83	0.0	1000	59.1	0.0	-3.0	0.0	0.9	0.0	0.0	0.0	-10.9	0.0	15
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	79	0.0	2000	59.1	0.0	-3.0	0.0	2.4	0.0	0.0	0.0	-11.9	0.0	9
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	76	0.0	125	60.0	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	14
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	79	0.0	250	60.0	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	13
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	84	0.0	500	60.0	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	17
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	83	0.0	1000	60.0	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	14
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	79	0.0	2000	60.0	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	7
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	76	0.0	125	60.4	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	14
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	79	0.0	250	60.4	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	13
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	84	0.0	500	60.4	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	16
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	83	0.0	1000	60.4	0.0	-3.0	0.0	1.1	0.0	0.0	0.0	-11.0	0.0	14
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	79	0.0	2000	60.4	0.0	-3.0	0.0	2.8	0.0	0.0	0.0	-12.0	0.0	7
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	76	0.0	125	60.4	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	14
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	79	0.0	250	60.4	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	13
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	84	0.0	500	60.4	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	16
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	83	0.0	1000	60.4	0.0	-3.0	0.0	1 1	0.0	0.0	0.0	-11.0	0.0	14
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	79	0.0	2000	60.4	0.0	-3.0	0.0	2.9	0.0	0.0	0.0	-12.0	0.0	7
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	76	0.0	125	62.7	0.0	-3.0	11.3	0.2	0.0	0.0	0.0	-4.9	0.0	0
329	HVACKIU	1/052331.9	4/00400.0	0.0	U	/0	0.0	120	02.7	0.0	-3.0	11.3	U.Z	0.0	0.0	U.U	-4.9	0.0	1 0



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	34

Receiver Name	Receiver ID	X																	
RP02	RP02	17652523.94 m	4786753.00 m	12.75 m															
Source ID	Source Name	Х			Refl.	Lw	L/A	Freq	Adiv	K0	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	67	0.0	63	58.8	0.0	-3.0	4.8	0.0	0.0	0.0	0.0	-0.9	0.0	5
\$15	HVAC RTU	17652538.8	4786997.8	5.5	0	80	0.0	125	58.8	0.0	-3.0	5.4	0.1	0.0	0.0	0.0	-4.8	0.0	14
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	84	0.0	250	58.8	0.0	-3.0	6.1	0.3	0.0	0.0	0.0	-8.8	0.0	13
\$15	HVAC RTU	17652538.8	4786997.8	5.5	0	87	0.0	500	58.8	0.0	-3.0	7.3	0.5	0.0	0.0	0.0	-9.9	0.0	13
\$15	HVAC RTU	17652538.8	4786997.8	5.5	0	89	0.0	1000	58.8	0.0	-3.0	8.9	0.9	0.0	0.0	0.0	-10.9	0.0	13
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	85	0.0	2000	58.8	0.0	-3.0	10.9	2.4	0.0	0.0	0.0	-11.9	0.0	4
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	72	0.0	250	58.9	0.0	-3.0	7.2	0.3	0.0	0.0	0.0	-8.8	0.0	0
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	84	0.0	500	58.9	0.0	-3.0	8.9	0.5	0.0	0.0	0.0	-9.9	0.0	9
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	89	0.0	1000	58.9	0.0	-3.0	11.0	0.9	0.0	0.0	0.0	-10.9	0.0	10
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	87	0.0	2000	58.9	0.0	-3.0	13.4	2.4	0.0	0.0	0.0	-11.9	0.0	4
\$08	HVAC RTU	17652671.6	4786985.8	5.5	0	80	0.0	125	59.8	0.0	-3.0	14.8	0.1	0.0	0.0	0.0	-4.8	0.0	3
\$08	HVAC RTU	17652671.6	4786985.8	5.5	0	84	0.0	250	59.8	0.0	-3.0	18.3	0.3	0.0	0.0	0.0	-8.8	0.0	0
\$26	HVAC RTU	17652295.7	4786588.4	5.5	0	67	0.0	63	60.0	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	80	0.0	125	60.0	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	18
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	84	0.0	250	60.0	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	18
\$26	HVAC RTU	17652295.7	4786588.4	5.5	0	87	0.0	500	60.0	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	19
\$26	HVAC RTU	17652295.7	4786588.4	5.5	0	89	0.0	1000	60.0	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	85	0.0	2000	60.0	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	14
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	80	0.0	125	60.1	0.0	-3.0	14.3	0.1	0.0	0.0	0.0	-4.8	0.0	4
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	84	0.0	250	60.1	0.0	-3.0	17.7	0.3	0.0	0.0	0.0	-8.8	0.0	1
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	80	0.0	125	60.1	0.0	-3.0	15.7	0.1	0.0	0.0	0.0	-4.8	0.0	2
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	80	0.0	125	60.2	0.0	-3.0	14.5	0.1	0.0	0.0	0.0	-4.8	0.0	3
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	84	0.0	250	60.2	0.0	-3.0	17.9	0.3	0.0	0.0	0.0	-8.8	0.0	0
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	67	0.0	63	60.2	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	80	0.0	125	60.2	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	18
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	84	0.0	250	60.2	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	18
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	87	0.0	500	60.2	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	19
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	89	0.0	1000	60.2	0.0	-3.0	0.0	1.1	0.0	0.0	0.0	-11.0	0.0	20
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	85	0.0	2000	60.2	0.0	-3.0	0.0	2.8	0.0	0.0	0.0	-12.0	0.0	13
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	72	0.0	250	60.2	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	6
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	84	0.0	500	60.2	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	16
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	89	0.0	1000	60.2	0.0	-3.0	0.0	1.1	0.0	0.0	0.0	-11.0	0.0	20
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	87	0.0	2000	60.2	0.0	-3.0	0.0	2.8	0.0	0.0	0.0	-12.0	0.0	15
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	81	0.0	4000	60.2	0.0	-3.0	0.0	9.5	0.0	0.0	0.0	-13.0	0.0	1
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	80	0.0	125	61.1	0.0	-3.0	15.7	0.1	0.0	0.0	0.0	-4.8	0.0	1
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	67	0.0	63	61.3	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	8
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	80	0.0	125	61.3	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	17
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	84	0.0	250	61.3	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	17
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	87	0.0	500	61.3	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	18
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	89	0.0	1000	61.3	0.0	-3.0	0.0	1.2	0.0	0.0	0.0	-11.0	0.0	19
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	85	0.0	2000	61.3	0.0	-3.0	0.0	3.2	0.0	0.0	0.0	-12.0	0.0	12
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	67	0.0	63	61.4	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	7
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	80	0.0	125	61.4	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	17
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	84	0.0	250	61.4	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	17



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	34

Receiver Name	Receiver ID	Х	Υ																
RP02	RP02	17652523.94 m	4786753.00 m	12.75 m															
	<u>'</u>																		
Source ID	Source Name	Y	٧	7	Refl.	Lw	L/A	Freq	Adiv	KO	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	87	0.0	500	61.4	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	18
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	89	0.0	1000	61.4	0.0	-3.0	0.0	1.2	0.0	0.0	0.0	-11.0	0.0	19
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	85	0.0	2000	61.4	0.0	-3.0	0.0	3.2	0.0	0.0	0.0	-12.0	0.0	12
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	67	0.0	63	61.4	0.0	-3.0	4.1	0.0	0.0	0.0	0.0	-1.0	0.0	3
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	80	0.0	125	61.4	0.0	-3.0	4.5	0.1	0.0	0.0	0.0	-4.8	0.0	12
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	84	0.0	250	61.4	0.0	-3.0	4.7	0.3	0.0	0.0	0.0	-8.8	0.0	12
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	87	0.0	500	61.4	0.0	-3.0	4.9	0.6	0.0	0.0	0.0	-10.0	0.0	13
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	89	0.0	1000	61.4	0.0	-3.0	5.1	1.2	0.0	0.0	0.0	-11.0	0.0	13
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	85	0.0	2000	61.4	0.0	-3.0	5.4	3.2	0.0	0.0	0.0	-12.0	0.0	6
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	67	0.0	63	61.4	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	7
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	80	0.0	125	61.4	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	17
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	84	0.0	250	61.4	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	17
\$20	HVAC RTU	17652511.2	4787083.5	5.5	0	87	0.0	500	61.4	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	18
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	89	0.0	1000	61.4	0.0	-3.0	0.0	1.2	0.0	0.0	0.0	-11.0	0.0	18
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	85	0.0	2000	61.4	0.0	-3.0	0.0	3.2	0.0	0.0	0.0	-12.0	0.0	12
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	80	0.0	125	61.5	0.0	-3.0	15.6	0.1	0.0	0.0	0.0	-4.8	0.0	1
																			1
608	HVAC RTU	17652777.1	4786972.9	5.5	0	80	0.0	125	61.5	0.0	-3.0	15.6	0.1	0.0	0.0	0.0	-4.8	0.0	
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	80	0.0	125	61.8	0.0	-3.0	15.7	0.1	0.0	0.0	0.0	-4.8	0.0	0
S28	HVAC RTU	17652287.5	4786523.9	5.5	0	72	0.0	250	61.4	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	5
S28	HVAC RTU	17652287.5	4786523.9	5.5	0	84	0.0	500	61.4	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	15
S28	HVAC RTU	17652287.5	4786523.9	5.5	0	89	0.0	1000	61.4	0.0	-3.0	0.0	1.2	0.0	0.0	0.0	-11.0	0.0	19
S28	HVAC RTU	17652287.5	4786523.9	5.5	0	87	0.0	2000	61.4	0.0	-3.0	0.0	3.2	0.0	0.0	0.0	-12.0	0.0	14
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	84	0.0	500	61.4	0.0	-3.0	10.3	0.6	0.0	0.0	0.0	-10.0	0.0	5
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	89	0.0	1000	61.4	0.0	-3.0	12.7	1.2	0.0	0.0	0.0	-11.0	0.0	6
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	67	0.0	63	63.3	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	6
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	80	0.0	125	63.3	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-4.9	0.0	15
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	84	0.0	250	63.3	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-8.9	0.0	15
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	87	0.0	500	63.3	0.0	-3.0	0.0	0.8	0.0	0.0	0.0	-10.0	0.0	16
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	89	0.0	1000	63.3	0.0	-3.0	0.0	1.5	0.0	0.0	0.0	-11.0	0.0	16
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	85	0.0	2000	63.3	0.0	-3.0	0.0	4.0	0.0	0.0	0.0	-12.0	0.0	9
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	67	0.0	63	63.3	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-1.0	0.0	6
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	80	0.0	125	63.3	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-4.9	0.0	15
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	84	0.0	250	63.3	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-8.9	0.0	15
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	87	0.0	500	63.3	0.0	-3.0	0.0	0.8	0.0	0.0	0.0	-10.0	0.0	16
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	89	0.0	1000	63.3	0.0	-3.0	0.0	1.5	0.0	0.0	0.0	-11.0	0.0	16
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	85	0.0	2000	63.3	0.0	-3.0	0.0	4.0	0.0	0.0	0.0	-12.0	0.0	9
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	75	0.0	125	58.8	0.0	-3.0	6.9	0.1	0.0	0.0	0.0	-4.8	0.0	7
S13				5.5	0	80	0.0	250	58.8		-3.0	8.5	0.3		0.0	0.0	-8.8		7
	HVAC RTU	17652551.9	4786997.1				_	_		0.0				0.0				0.0	
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	83	0.0	500	58.8	0.0	-3.0	10.6	0.5	0.0	0.0	0.0	-9.9	0.0	6
S13	HVACRTU	17652551.9	4786997.1	5.5	0	82	0.0	1000	58.8	0.0	-3.0	13.0	0.9	0.0	0.0	0.0	-10.9	0.0	1
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	76	0.0	125	54.7	0.0	-3.0	13.9	0.1	0.0	0.0	0.0	-4.6	0.0	6
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	79	0.0	250	54.7	0.0	-3.0	16.9	0.2	0.0	0.0	0.0	-8.6	0.0	2
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	84	0.0	500	54.7	0.0	-3.0	19.9	0.3	0.0	0.0	0.0	-9.9	0.0	2
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	76	0.0	125	55.0	0.0	-3.0	14.3	0.1	0.0	0.0	0.0	-4.6	0.0	5



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	34

Receiver Name	Receiver ID	X	Υ																
RP02	RP02	17652523.94 m	4786753.00 m	12.75 m															
Source ID	Source Name	X	Υ	7	Refl.	Lw	L/A	Freq	Adiv	KO	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	79	0.0	250	55.0	0.0	-3.0	17.4	0.2	0.0	0.0	0.0	-8.6	0.0	1
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	84	0.0	500	55.0	0.0	-3.0	20.4	0.3	0.0	0.0	0.0	-9.9	0.0	1
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	76	0.0	125	59.4	0.0	-3.0	13.0	0.1	0.0	0.0	0.0	-4.8	0.0	2
\$38	HVAC RTU	17652531.6	4787077.3	5.5	0	76	0.0	125	61.2	0.0	-3.0	4.6	0.1	0.0	0.0	0.0	-4.8	0.0	8
\$38	HVAC RTU	17652531.6	4787077.3	5.5	0	79	0.0	250	61.2	0.0	-3.0	4.9	0.3	0.0	0.0	0.0	-8.8	0.0	7
\$38	HVAC RTU	17652531.6	4787077.3	5.5	0	84	0.0	500	61.2	0.0	-3.0	5.1	0.6	0.0	0.0	0.0	-10.0	0.0	10
\$38	HVAC RTU	17652531.6	4787077.3	5.5	0	83	0.0	1000	61.2	0.0	-3.0	5.5	1.2	0.0	0.0	0.0	-11.0	0.0	7
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	76	0.0	125	61.5	0.0	-3.0	4.5	0.1	0.0	0.0	0.0	-4.8	0.0	8
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	79	0.0	250	61.5	0.0	-3.0	4.7	0.4	0.0	0.0	0.0	-8.8	0.0	7
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	84	0.0	500	61.5	0.0	-3.0	4.9	0.6	0.0	0.0	0.0	-10.0	0.0	10
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	83	0.0	1000	61.5	0.0	-3.0	5.1	1.2	0.0	0.0	0.0	-11.0	0.0	7
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	76	0.0	125	61.5	0.0	-3.0	5.1	0.1	0.0	0.0	0.0	-4.8	0.0	7
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	79	0.0	250	61.5	0.0	-3.0	5.7	0.4	0.0	0.0	0.0	-8.8	0.0	6
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	84	0.0	500	61.5	0.0	-3.0	6.5	0.6	0.0	0.0	0.0	-10.0	0.0	8
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	83	0.0	1000	61.5	0.0	-3.0	7.8	1.2	0.0	0.0	0.0	-11.0	0.0	5
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	76	0.0	125	61.8	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	12
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	79	0.0	250	61.8	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-8.8	0.0	11
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	84	0.0	500	61.8	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-10.0	0.0	15
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	83	0.0	1000	61.8	0.0	-3.0	0.0	1.3	0.0	0.0	0.0	-11.0	0.0	12
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	79	0.0	2000	61.8	0.0	-3.0	0.0	3.3	0.0	0.0	0.0	-12.0	0.0	5
S30	HVAC RTU	17652300.7	4786464.7	5.5	0	76	0.0	125	62.2	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	12
S30	HVAC RTU	17652300.7	4786464.7	5.5	0	79	0.0	250	62.2	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-8.8	0.0	11
S30	HVAC RTU	17652300.7	4786464.7	5.5	0	84	0.0	500	62.2	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-10.0	0.0	14
S30	HVAC RTU	17652300.7	4786464.7	5.5	0	83	0.0	1000	62.2	0.0	-3.0	0.0	1.3	0.0	0.0	0.0	-11.0	0.0	12
S30	HVAC RTU	17652300.7	4786464.7	5.5	0	79	0.0	2000	62.2	0.0	-3.0	0.0	3.5	0.0	0.0	0.0	-12.0	0.0	4



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	32

Receiver Name	Receiver ID	Х																	
RP03	RP03	17652529.24 m	4786741.01 m	12.75 m	Ī														
Source ID	Source Name	Х			Refl.	Lw	L/A	Freq	Adiv	KO	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	80	0.0	125	59.2	0.0	-3.0	15.8	0.1	0.0	0.0	0.0	-4.8	0.0	3
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	67	0.0	63	59.9	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	80	0.0	125	59.9	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	18
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	84	0.0	250	59.9	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	18
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	87	0.0	500	59.9	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	19
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	89	0.0	1000	59.9	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	85	0.0	2000	59.9	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	14
\$08	HVAC RTU	17652671.6	4786985.8	5.5	0	80	0.0	125	60.0	0.0	-3.0	12.9	0.1	0.0	0.0	0.0	-4.8	0.0	5
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	84	0.0	250	60.0	0.0	-3.0	16.6	0.3	0.0	0.0	0.0	-8.8	0.0	2
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	67	0.0	63	60.1	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	80	0.0	125	60.1	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.8	0.0	18
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	84	0.0	250	60.1	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	18
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	87	0.0	500	60.1	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	19
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	89	0.0	1000	60.1	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	85	0.0	2000	60.1	0.0	-3.0	0.0	2.8	0.0	0.0	0.0	-12.0	0.0	13
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	80	0.0	125	60.3	0.0	-3.0	12.0	0.1	0.0	0.0	0.0	-4.8	0.0	6
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	84	0.0	250	60.3	0.0	-3.0	15.7	0.3	0.0	0.0	0.0	-8.8	0.0	2
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	80	0.0	125	60.3	0.0	-3.0	13.1	0.1	0.0	0.0	0.0	-4.8	0.0	5
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	84	0.0	250	60.3	0.0	-3.0	16.9	0.3	0.0	0.0	0.0	-8.8	0.0	1
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	80	0.0	125	60.4	0.0	-3.0	13.0	0.1	0.0	0.0	0.0	-4.8	0.0	5
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	84	0.0	250	60.4	0.0	-3.0	16.8	0.3	0.0	0.0	0.0	-8.8	0.0	1
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	72	0.0	250	60.3	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	6
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	84	0.0	500	60.3	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	16
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	89	0.0	1000	60.3	0.0	-3.0	0.0	1.1	0.0	0.0	0.0	-11.0	0.0	20
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	87	0.0	2000	60.3	0.0	-3.0	0.0	2.8	0.0	0.0	0.0	-12.0	0.0	15
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	81	0.0	4000	60.3	0.0	-3.0	0.0	9.5	0.0	0.0	0.0	-13.0	0.0	1
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	80	0.0	125	61.2	0.0	-3.0	11.3	0.1	0.0	0.0	0.0	-4.8	0.0	5
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	84	0.0	250	61.2	0.0	-3.0	14.9	0.3	0.0	0.0	0.0	-8.8	0.0	2
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	80	0.0	125	61.6	0.0	-3.0	11.6	0.1	0.0	0.0	0.0	-4.8	0.0	5
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	84	0.0	250	61.6	0.0	-3.0	15.1	0.4	0.0	0.0	0.0	-8.8	0.0	2
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	80	0.0	125	61.6	0.0	-3.0	11.5	0.1	0.0	0.0	0.0	-4.8	0.0	5
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	84	0.0	250	61.6	0.0	-3.0	15.1	0.4	0.0	0.0	0.0	-8.8	0.0	2
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	80	0.0	125	61.6	0.0	-3.0	13.8	0.1	0.0	0.0	0.0	-4.8	0.0	3
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	80	0.0	125	61.7	0.0	-3.0	15.8	0.1	0.0	0.0	0.0	-4.8	0.0	0
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	80	0.0	125	61.7	0.0	-3.0	13.9	0.1	0.0	0.0	0.0	-4.8	0.0	2
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	80	0.0	125	61.7	0.0	-3.0	13.9	0.1	0.0	0.0	0.0	-4.8	0.0	2
\$33	HVAC RTU	17652765.8	4786957.2	5.5	0	78	0.0	125	61.1	0.0	-3.0	11.5	0.1	0.0	0.0	0.0	-4.8	0.0	3
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	83	0.0	250	61.1	0.0	-3.0	15.0	0.3	0.0	0.0	0.0	-8.8	0.0	1
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	80	0.0	125	61.9	0.0	-3.0	11.8	0.1	0.0	0.0	0.0	-4.8	0.0	4
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	84	0.0	250	61.9	0.0	-3.0	15.4	0.4	0.0	0.0	0.0	-8.8	0.0	1
S28	HVAC RTU	17652287.5	4786523.9	5.5	0	72	0.0	250	61.2	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-8.8	0.0	5
S28	HVAC RTU	17652287.5	4786523.9	5.5	0	84	0.0	500	61.2	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	15
S28	HVAC RTU	17652287.5	4786523.9	5.5	0	89	0.0	1000	61.2	0.0	-3.0	0.0	1.2	0.0	0.0	0.0	-11.0	0.0	19
S28	HVAC RTU	17652287.5	4786523.9	5.5	0	87	0.0	2000	61.2	0.0	-3.0	0.0	3.1	0.0	0.0	0.0	-12.0	0.0	14



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	32

RP03 RP03 17652529.24 m 4786741.01 m 12.75 m Source ID Source Name X Y Z Refl. \$32 HVAC RTU 17652130.5 4786637.7 5.5 0 \$32 HVAC RTU 17652130.5 4786637.7 5.5 0	I/A Freq Adiv KO Agr Abar Aatm Afol 0.0 63 63.3 0.0 -3.0 0.0 0.1 0.0 0.0 125 63.3 0.0 -3.0 0.0 0.2 0.0 0.0 250 63.3 0.0 -3.0 0.0 0.4 0.0 0.0 500 63.3 0.0 -3.0 0.0 0.8 0.0 0.0 1000 63.3 0.0 -3.0 0.0 1.5 0.0	Ahous Cmet Dc RL Lr 0.0 0.0 -1.0 0.0 6 0.0 0.0 -4.9 0.0 15 0.0 0.0 -8.9 0.0 15
S32 HVAC RTU 17652130.5 4786637.7 5.5 0	0.0 63 63.3 0.0 -3.0 0.0 0.1 0.0 0.0 125 63.3 0.0 -3.0 0.0 0.2 0.0 0.0 250 63.3 0.0 -3.0 0.0 0.4 0.0 0.0 500 63.3 0.0 -3.0 0.0 0.8 0.0	0.0 0.0 -1.0 0.0 6 0.0 0.0 -4.9 0.0 15 0.0 0.0 -8.9 0.0 15
S32 HVAC RTU 17652130.5 4786637.7 5.5 0	0.0 63 63.3 0.0 -3.0 0.0 0.1 0.0 0.0 125 63.3 0.0 -3.0 0.0 0.2 0.0 0.0 250 63.3 0.0 -3.0 0.0 0.4 0.0 0.0 500 63.3 0.0 -3.0 0.0 0.8 0.0	0.0 0.0 -1.0 0.0 6 0.0 0.0 -4.9 0.0 15 0.0 0.0 -8.9 0.0 15
S32 HVAC RTU 17652130.5 4786637.7 5.5 0 S32 HVAC RTU 17652130.5 4786637.7 5.5 0 S32 HVAC RTU 17652130.5 4786637.7 5.5 0	0.0 125 63.3 0.0 -3.0 0.0 0.2 0.0 0.0 250 63.3 0.0 -3.0 0.0 0.4 0.0 0.0 500 63.3 0.0 -3.0 0.0 0.8 0.0	0.0 0.0 -4.9 0.0 15 0.0 0.0 -8.9 0.0 15
S32 HVAC RTU 17652130.5 4786637.7 5.5 0 S32 HVAC RTU 17652130.5 4786637.7 5.5 0	0.0 250 63.3 0.0 -3.0 0.0 0.4 0.0 0.0 500 63.3 0.0 -3.0 0.0 0.8 0.0	0.0 0.0 -8.9 0.0 15
S32 HVACRTU 17652130.5 4786637.7 5.5 0	0.0 500 63.3 0.0 -3.0 0.0 0.8 0.0	
S32 HVAC RTU 17652130.5 4786637.7 5.5 0	0.0 1000 633 0.0 -3.0 0.0 1.5 0.0	0.0 0.0 -10.0 0.0 16
	0.0 1000 00.0 0.0 0.0 1.0 0.0	0.0 0.0 -11.0 0.0 16
S32 HVAC RTU 17652130.5 4786637.7 5.5 0	0.0 2000 63.3 0.0 -3.0 0.0 4.0 0.0	0.0 0.0 -12.0 0.0 9
S31 HVAC RTU 17652128.5 4786640.0 5.5 0	0.0 63 63.3 0.0 -3.0 0.0 0.1 0.0	0.0 0.0 -1.0 0.0 6
S31 HVAC RTU 17652128.5 4786640.0 5.5 0	0.0 125 63.3 0.0 -3.0 0.0 0.2 0.0	0.0 0.0 -4.9 0.0 15
S31 HVAC RTU 17652128.5 4786640.0 5.5 0	0.0 250 63.3 0.0 -3.0 0.0 0.4 0.0	0.0 0.0 -8.9 0.0 15
S31 HVAC RTU 17652128.5 4786640.0 5.5 0	0.0 500 63.3 0.0 -3.0 0.0 0.8 0.0	0.0 0.0 -10.0 0.0 16
S31 HVAC RTU 17652128.5 4786640.0 5.5 0	0.0 1000 63.3 0.0 -3.0 0.0 1.5 0.0	0.0 0.0 -11.0 0.0 16
S31 HVAC RTU 17652128.5 4786640.0 5.5 0	0.0 2000 63.3 0.0 -3.0 0.0 4.0 0.0	0.0 0.0 -12.0 0.0 9
S01 HVAC RTU 17652754.0 4786849.6 8.0 0	0.0 125 58.9 0.0 -3.0 9.4 0.1 0.0	0.0 0.0 -4.9 0.0 4
S01 HVAC RTU 17652754.0 4786849.6 8.0 0	0.0 250 58.9 0.0 -3.0 12.6 0.3 0.0	0.0 0.0 -8.9 0.0 2
SO2 HVAC RTU 17652778.2 4786850.1 8.0 0	0.0 125 59.7 0.0 -3.0 9.1 0.1 0.0	0.0 0.0 -4.9 0.0 3
S02 HVAC RTU 17652778.2 4786850.1 8.0 0	0.0 250 59.7 0.0 -3.0 12.2 0.3 0.0	0.0 0.0 -8.9 0.0 1
S03 HVAC RTU 17652813.6 4786860.2 8.0 0	0.0 125 60.8 0.0 -3.0 8.9 0.1 0.0	0.0 0.0 -4.9 0.0 2
S03 HVAC RTU 17652813.6 4786860.2 8.0 0	0.0 250 60.8 0.0 -3.0 12.0 0.3 0.0	0.0 0.0 -8.9 0.0 1
S04 HVAC RTU 17652837.9 4786861.4 8.0 0	0.0 125 61.4 0.0 -3.0 8.7 0.1 0.0	0.0 0.0 -4.9 0.0 2
S04 HVAC RTU 17652837.9 4786861.4 8.0 0	0.0 250 61.4 0.0 -3.0 11.7 0.3 0.0	0.0 0.0 -8.9 0.0 0
S17 HVAC RTU 17652582.9 4786894.7 5.5 0	0.0 125 55.2 0.0 -3.0 16.7 0.1 0.0	0.0 0.0 -4.7 0.0 2
S16 HVAC RTU 17652589.2 4786896.6 5.5 0	0.0 125 55.4 0.0 -3.0 16.4 0.1 0.0	0.0 0.0 -4.7 0.0 2
S12 HVAC RTU 17652620.9 4786998.7 5.5 0	0.0 125 59.7 0.0 -3.0 13.6 0.1 0.0	0.0 0.0 -4.8 0.0 1
S09 HVAC RTU 17652676.8 4786999.6 5.5 0	0.0 125 60.5 0.0 -3.0 12.9 0.1 0.0	0.0 0.0 -4.8 0.0 1
S29 HVAC RTU 17652331.9 4786466.0 5.5 0	0.0 125 61.6 0.0 -3.0 0.0 0.1 0.0	0.0 0.0 -4.8 0.0 12
S29 HVAC RTU 17652331.9 4786466.0 5.5 0	0.0 250 61.6 0.0 -3.0 0.0 0.4 0.0	0.0 0.0 -8.8 0.0 11
S29 HVAC RTU 17652331.9 4786466.0 5.5 0	0.0 500 61.6 0.0 -3.0 0.0 0.7 0.0	0.0 0.0 -10.0 0.0 15
S29 HVAC RTU 17652331.9 4786466.0 5.5 0	0.0 1000 61.6 0.0 -3.0 0.0 1.2 0.0	0.0 0.0 -11.0 0.0 12
S29 HVAC RTU 17652331.9 4786466.0 5.5 0	0.0 2000 61.6 0.0 -3.0 0.0 3.3 0.0	0.0 0.0 -12.0 0.0 5
S30 HVAC RTU 17652300.7 4786464.7 5.5 0	0.0 125 62.1 0.0 -3.0 0.0 0.1 0.0	0.0 0.0 -4.8 0.0 12
S30 HVAC RTU 17652300.7 4786464.7 5.5 0	0.0 250 62.1 0.0 -3.0 0.0 0.4 0.0	0.0 0.0 -8.8 0.0 11
S30 HVAC RTU 17652300.7 4786464.7 5.5 0	0.0 500 62.1 0.0 -3.0 0.0 0.7 0.0	0.0 0.0 -10.0 0.0 14
S30 HVAC RTU 17652300.7 4786464.7 5.5 0	0.0 1000 62.1 0.0 -3.0 0.0 1.3 0.0	0.0 0.0 -11.0 0.0 12
S30 HVAC RTU 17652300.7 4786464.7 5.5 0	0.0 2000 62.1 0.0 -3.0 0.0 3.5 0.0	0.0 0.0 -12.0 0.0 5



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	41

Receiver Name	Receiver ID	Χ																	
RP04	RP04	17652560.55 m	4786810.62 m	7.00 m															
					-														
Source ID	Source Name	Х			Refl.	Lw	L/A	Freq	Adiv	K0	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	67	0.0	63	56.5	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	12
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	80	0.0	125	56.5	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	21
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	84	0.0	250	56.5	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	22
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	87	0.0	500	56.5	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	23
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	89	0.0	1000	56.5	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-11.0	0.0	24
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	85	0.0	2000	56.5	0.0	-3.0	0.0	1.8	0.0	0.0	0.0	-12.0	0.0	18
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	78	0.0	4000	56.5	0.0	-3.0	0.0	6.2	0.0	0.0	0.0	-13.0	0.0	5
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	67	0.0	63	57.3	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	12
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	80	0.0	125	57.3	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	21
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	84	0.0	250	57.3	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	21
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	87	0.0	500	57.3	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	22
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	89	0.0	1000	57.3	0.0	-3.0	0.0	0.8	0.0	0.0	0.0	-11.0	0.0	23
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	85	0.0	2000	57.3	0.0	-3.0	0.0	2.0	0.0	0.0	0.0	-12.0	0.0	17
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	78	0.0	4000	57.3	0.0	-3.0	0.0	6.8	0.0	0.0	0.0	-13.0	0.0	4
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	61	0.0	125	56.6	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	2
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	72	0.0	250	56.6	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	10
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	84	0.0	500	56.6	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	20
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	89	0.0	1000	56.6	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-11.0	0.0	24
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	87	0.0	2000	56.6	0.0	-3.0	0.0	1.8	0.0	0.0	0.0	-12.0	0.0	20
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	81	0.0	4000	56.6	0.0	-3.0	0.0	6.2	0.0	0.0	0.0	-13.0	0.0	8
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	67	0.0	63	57.7	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	11
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	80	0.0	125	57.7	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	20
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	84	0.0	250	57.7	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	21
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	87	0.0	500	57.7	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	22
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	89	0.0	1000	57.7	0.0	-3.0	0.0	0.8	0.0	0.0	0.0	-11.0	0.0	23
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	85	0.0	2000	57.7	0.0	-3.0	0.0	2.1	0.0	0.0	0.0	-12.0	0.0	16
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	78	0.0	4000	57.7	0.0	-3.0	0.0	7.1	0.0	0.0	0.0	-13.0	0.0	3
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	67	0.0	63	57.8	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	11
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	80	0.0	125	57.8	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	20
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	84	0.0	250	57.8	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	20
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	87	0.0	500	57.8	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	22
\$10	HVAC RTU	17652667.8	4787001.4	5.5	0	89	0.0	1000	57.8	0.0	-3.0	0.0	8.0	0.0	0.0	0.0	-11.0	0.0	22
\$10	HVAC RTU	17652667.8	4787001.4	5.5	0	85	0.0	2000	57.8	0.0	-3.0	0.0	2.1	0.0	0.0	0.0	-12.0	0.0	16
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	78	0.0	4000	57.8	0.0	-3.0	0.0	7.2	0.0	0.0	0.0	-13.0	0.0	3
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	67	0.0	63	57.8	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	11
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	80	0.0	125	57.8	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	20
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	84	0.0	250	57.8	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	20
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	87	0.0	500	57.8	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	22
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	89	0.0	1000	57.8	0.0	-3.0	0.0	0.8	0.0	0.0	0.0	-11.0	0.0	22
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	85	0.0	2000	57.8	0.0	-3.0	0.0	2.1	0.0	0.0	0.0	-12.0	0.0	16
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	78	0.0	4000	57.8	0.0	-3.0	0.0	7.2	0.0	0.0	0.0	-13.0	0.0	3
S36	HVAC RTU	17652710.3	4786988.4	5.5	0	61	0.0	125	58.3	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	1
S36	HVAC RTU	17652710.3	4786988.4	5.5	0	72	0.0	250	58.3	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-9.0	0.0	8
S36	HVAC RTU	17652710.3	4786988.4	5.5	0	84	0.0	500	58.3	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	18



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	41

Receiver Name	Receiver ID	X	Υ																
RP04	RP04	17652560.55 m	4786810.62 m	7.00 m															
Source ID	Source Name	٧	V	7	Refl.	Lw	L/A	Freq	Adiv	K0	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
\$36	HVAC RTU	17652710.3	4786988.4	5.5	0	89	0.0	1000	58.3	0.0	-3.0	0.0	0.9	0.0	0.0	0.0	-11.0	0.0	22
\$36	HVAC RTU	17652710.3	4786988.4	5.5	0	87	0.0	2000	58.3	0.0	-3.0	0.0	2.2	0.0	0.0	0.0	-12.0	0.0	18
S36	HVAC RTU	17652710.3	4786988.4	5.5	0	81	0.0	4000	58.3	0.0	-3.0	0.0	7.6	0.0	0.0	0.0	-13.0	0.0	5
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	67	0.0	63	59.1	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	10
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	80	0.0	125	59.1	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	19
\$34	HVAC RTU	17652772.1	4786953.1	5.5	0	84	0.0	250	59.1	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	19
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	87	0.0	500	59.1	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	20
\$34	HVAC RTU	17652772.1	4786953.1	5.5	0	89	0.0	1000	59.1	0.0	-3.0	0.0	0.9	0.0	0.0	0.0	-11.0	0.0	21
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	85	0.0	2000	59.1	0.0	-3.0	0.0	2.5	0.0	0.0	0.0	-12.0	0.0	15
\$34	HVAC RTU	17652772.1	4786953.1	5.5	0	78	0.0	4000	59.1	0.0	-3.0	0.0	8.4	0.0	0.0	0.0	-13.0	0.0	1
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	67	0.0	63	59.6	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	80	0.0	125	59.6	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	18
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	84	0.0	250	59.6	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	19
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	87	0.0	500	59.6	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	20
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	89	0.0	1000	59.6	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	85	0.0	2000	59.6	0.0	-3.0	0.0	2.6	0.0	0.0	0.0	-12.0	0.0	14
																	_		
\$06	HVAC RTU	17652777.1	4786972.9	5.5	0	67	0.0	63	59.6	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
\$06	HVAC RTU	17652777.1	4786972.9	5.5	0	80	0.0	125	59.6	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	18
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	84	0.0	250	59.6	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	19
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	87	0.0	500	59.6	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	20
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	89	0.0	1000	59.6	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	85	0.0	2000	59.6	0.0	-3.0	0.0	2.6	0.0	0.0	0.0	-12.0	0.0	14
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	65	0.0	63	59.0	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	8
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	78	0.0	125	59.0	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	17
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	83	0.0	250	59.0	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	18
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	87	0.0	500	59.0	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	20
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	87	0.0	1000	59.0	0.0	-3.0	0.0	0.9	0.0	0.0	0.0	-11.0	0.0	19
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	85	0.0	2000	59.0	0.0	-3.0	0.0	2.4	0.0	0.0	0.0	-12.0	0.0	15
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	81	0.0	4000	59.0	0.0	-3.0	0.0	8.3	0.0	0.0	0.0	-13.0	0.0	4
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	67	0.0	63	59.8	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	80	0.0	125	59.8	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	18
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	84	0.0	250	59.8	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	18
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	87	0.0	500	59.8	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	20
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	89	0.0	1000	59.8	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S21	HVAC RTU	17652529.4	4787083.3	5.5		85	0.0	2000	59.8	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	14
					0										_				
\$18	HVAC RTU	17652494.0	4787078.9	5.5	0	67	0.0	63	59.8	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	80	0.0	125	59.8	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	18
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	84	0.0	250	59.8	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	18
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	87	0.0	500	59.8	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	19
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	89	0.0	1000	59.8	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	85	0.0	2000	59.8	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	14
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	67	0.0	63	59.9	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	80	0.0	125	59.9	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	18
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	84	0.0	250	59.9	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	18



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	41

Receiver Name	Receiver ID	Х																	
RP04	RP04	17652560.55 m	4786810.62 m	7.00 m															
Source ID	Source Name	Х			Refl.	Lw	L/A	Freq	Adiv	K0	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	87	0.0	500	59.9	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	19
\$20	HVAC RTU	17652511.2	4787083.5	5.5	0	89	0.0	1000	59.9	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	85	0.0	2000	59.9	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	14
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	67	0.0	63	59.9	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	80	0.0	125	59.9	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	18
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	84	0.0	250	59.9	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	18
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	87	0.0	500	59.9	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	19
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	89	0.0	1000	59.9	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	85	0.0	2000	59.9	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	14
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	67	0.0	63	59.9	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	80	0.0	125	59.9	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	18
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	84	0.0	250	59.9	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	18
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	87	0.0	500	59.9	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	19
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	89	0.0	1000	59.9	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	85	0.0	2000	59.9	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	14
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	72	0.0	250	59.7	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	7
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	84	0.0	500	59.7	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	17
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	89	0.0	1000	59.7	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	87	0.0	2000	59.7	0.0	-3.0	0.0	2.6	0.0	0.0	0.0	-12.0	0.0	16
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	81	0.0	4000	59.7	0.0	-3.0	0.0	8.9	0.0	0.0	0.0	-13.0	0.0	3
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	76	0.0	125	49.8	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-4.9	0.0	24
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	79	0.0	250	49.8	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-8.9	0.0	23
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	84	0.0	500	49.8	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-10.0	0.0	27
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	83	0.0	1000	49.8	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-11.0	0.0	25
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	79	0.0	2000	49.8	0.0	-3.0	0.0	0.8	0.0	0.0	0.0	-12.0	0.0	19
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	73	0.0	4000	49.8	0.0	-3.0	0.0	2.8	0.0	0.0	0.0	-13.0	0.0	10
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	62	0.0	63	56.4	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	7
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	75	0.0	125	56.4	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	17
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	80	0.0	250	56.4	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	18
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	83	0.0	500	56.4	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	19
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	82	0.0	1000	56.4	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-11.0	0.0	17
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	80	0.0	2000	56.4	0.0	-3.0	0.0	1.8	0.0	0.0	0.0	-12.0	0.0	13
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	77	0.0	4000	56.4	0.0	-3.0	0.0	6.1	0.0	0.0	0.0	-13.0	0.0	5
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	76	0.0	125	50.1	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-4.9	0.0	24
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	79	0.0	250	50.1	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-8.9	0.0	23
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	84	0.0	500	50.1	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-10.0	0.0	27
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	83	0.0	1000	50.1	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-11.0	0.0	25
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	79	0.0	2000	50.1	0.0	-3.0	0.0	0.9	0.0	0.0	0.0	-12.0	0.0	19
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	73	0.0	4000	50.1	0.0	-3.0	0.0	3.0	0.0	0.0	0.0	-13.0	0.0	10
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	61	0.0	63	56.9	0.0	-3.0	4.3	0.0	0.0	0.0	0.0	-1.0	0.0	2
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	74	0.0	125	56.9	0.0	-3.0	4.7	0.1	0.0	0.0	0.0	-5.0	0.0	10
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	79	0.0	250	56.9	0.0	-3.0	5.2	0.2	0.0	0.0	0.0	-9.0	0.0	11
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	83	0.0	500	56.9	0.0	-3.0	5.9	0.4	0.0	0.0	0.0	-10.0	0.0	13
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	82	0.0	1000	56.9	0.0	-3.0	7.0	0.7	0.0	0.0	0.0	-11.0	0.0	9



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	41

Receiver Name	Receiver ID	X	Υ																
RP04	RP04	17652560.55 m	4786810.62 m	7.00 m															
Source ID	Source Name	Υ	٧	7	Refl.	Lw	L/A	Freq	Adiv	KO	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	81	0.0	2000	56.9	0.0	-3.0	8.5	1.9	0.0	0.0	0.0	-12.0	0.0	5
\$26	HVAC RTU	17652295.7	4786588.4	5.5	0	80	0.0	125	61.8	0.0	-3.0	11.3	0.1	0.0	0.0	0.0	-5.0	0.0	5
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	84	0.0	250	61.8	0.0	-3.0	14.0	0.4	0.0	0.0	0.0	-9.0	0.0	2
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	87	0.0	500	61.8	0.0	-3.0	16.8	0.7	0.0	0.0	0.0	-10.0	0.0	1
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	80	0.0	125	62.0	0.0	-3.0	11.9	0.1	0.0	0.0	0.0	-5.0	0.0	4
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	84	0.0	250	62.0	0.0	-3.0	14.6	0.4	0.0	0.0	0.0	-9.0	0.0	2
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	84	0.0	500	61.8	0.0	-3.0	5.8	0.7	0.0	0.0	0.0	-10.0	0.0	9
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	89	0.0	1000	61.8	0.0	-3.0	6.7	1.3	0.0	0.0	0.0	-11.0	0.0	11
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	87	0.0	2000	61.8	0.0	-3.0	8.0	3.3	0.0	0.0	0.0	-12.0	0.0	5
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	61	0.0	63	57.9	0.0	-3.0	4.4	0.0	0.0	0.0	0.0	-1.0	0.0	1
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	74	0.0	125	57.9	0.0	-3.0	4.8	0.1	0.0	0.0	0.0	-5.0	0.0	9
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	79	0.0	250	57.9	0.0	-3.0	5.4	0.2	0.0	0.0	0.0	-9.0	0.0	10
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	83	0.0	500	57.9	0.0	-3.0	6.2	0.4	0.0	0.0	0.0	-10.0	0.0	11
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	82	0.0	1000	57.9	0.0	-3.0	7.5	0.8	0.0	0.0	0.0	-11.0	0.0	8
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	81	0.0	2000	57.9	0.0	-3.0	9.1	2.1	0.0	0.0	0.0	-12.0	0.0	3
S03	HVAC RTU	17652813.6	4786860.2	8.0	0	74	0.0	125	59.2	0.0	-3.0	4.7	0.1	0.0	0.0	0.0	-5.0	0.0	8
					_				-										
S03	HVAC RTU	17652813.6	4786860.2	8.0	0	79	0.0	250	59.2	0.0	-3.0	5.3	0.3	0.0	0.0	0.0	-9.0	0.0	9
\$03	HVAC RTU	17652813.6	4786860.2	8.0	0	83	0.0	500	59.2	0.0	-3.0	6.0	0.5	0.0	0.0	0.0	-10.0	0.0	10
S03	HVAC RTU	17652813.6	4786860.2	8.0	0	82	0.0	1000	59.2	0.0	-3.0	7.1	0.9	0.0	0.0	0.0	-11.0	0.0	7
S03	HVAC RTU	17652813.6	4786860.2	8.0	0	81	0.0	2000	59.2	0.0	-3.0	8.7	2.5	0.0	0.0	0.0	-12.0	0.0	2
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	67	0.0	63	64.3	0.0	-3.6	0.0	0.1	0.0	0.0	0.0	-1.0	0.0	5
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	80	0.0	125	64.3	0.0	-3.6	0.0	0.2	0.0	0.0	0.0	-5.0	0.0	14
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	84	0.0	250	64.3	0.0	-3.6	0.0	0.5	0.0	0.0	0.0	-9.0	0.0	14
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	87	0.0	500	64.3	0.0	-3.6	0.0	0.9	0.0	0.0	0.0	-10.0	0.0	15
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	89	0.0	1000	64.3	0.0	-3.6	0.0	1.7	0.0	0.0	0.0	-11.0	0.0	16
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	85	0.0	2000	64.3	0.0	-3.6	0.0	4.5	0.0	0.0	0.0	-12.0	0.0	8
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	67	0.0	63	64.3	0.0	-3.6	0.0	0.1	0.0	0.0	0.0	-1.0	0.0	5
\$31	HVAC RTU	17652128.5	4786640.0	5.5	0	80	0.0	125	64.3	0.0	-3.6	0.0	0.2	0.0	0.0	0.0	-5.0	0.0	14
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	84	0.0	250	64.3	0.0	-3.6	0.0	0.5	0.0	0.0	0.0	-9.0	0.0	14
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	87	0.0	500	64.3	0.0	-3.6	0.0	0.9	0.0	0.0	0.0	-10.0	0.0	15
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	89	0.0	1000	64.3	0.0	-3.6	0.0	1.7	0.0	0.0	0.0	-11.0	0.0	16
\$31	HVAC RTU	17652128.5	4786640.0	5.5	0	85	0.0	2000	64.3	0.0	-3.6	0.0	4.5	0.0	0.0	0.0	-12.0	0.0	8
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	74	0.0	125	60.0	0.0	-3.0	4.8	0.1	0.0	0.0	0.0	-5.0	0.0	7
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	79	0.0	250	60.0	0.0	-3.0	5.4	0.3	0.0	0.0	0.0	-9.0	0.0	8
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	83	0.0	500	60.0	0.0	-3.0	6.2	0.5	0.0	0.0	0.0	-10.0	0.0	9
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	82	0.0	1000	60.0	0.0	-3.0	7.4	1.0	0.0	0.0	0.0	-11.0	0.0	6
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	81	0.0	2000	60.0	0.0	-3.0	9.1	2.7	0.0	0.0	0.0	-12.0	0.0	0
					_														
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	62	0.0	63	57.1	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	7
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	70	0.0	125	57.1	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	11
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	72	0.0	250	57.1	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	8
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	79	0.0	500	57.1	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	15
\$37	HVAC RTU	17652713.2	4786942.6	5.5	0	76	0.0	1000	57.1	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-11.0	0.0	10
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	75	0.0	2000	57.1	0.0	-3.0	0.0	2.0	0.0	0.0	0.0	-12.0	0.0	7
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	74	0.0	4000	57.1	0.0	-3.0	0.0	6.6	0.0	0.0	0.0	-13.0	0.0	1



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	41

Receiver Name	Receiver ID	Х																	
RP04	RP04	17652560.55 m	4786810.62 m	7.00 m	I														
Source ID	Source Name	Х	Υ	Z	Refl.	Lw	L/A	Freq	Adiv	K0	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	76	0.0	125	56.9	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	17
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	79	0.0	250	56.9	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	16
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	84	0.0	500	56.9	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	20
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	83	0.0	1000	56.9	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-11.0	0.0	17
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	79	0.0	2000	56.9	0.0	-3.0	0.0	1.9	0.0	0.0	0.0	-12.0	0.0	11
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	76	0.0	125	57.9	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	16
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	79	0.0	250	57.9	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	15
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	84	0.0	500	57.9	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	19
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	83	0.0	1000	57.9	0.0	-3.0	0.0	0.8	0.0	0.0	0.0	-11.0	0.0	16
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	79	0.0	2000	57.9	0.0	-3.0	0.0	2.1	0.0	0.0	0.0	-12.0	0.0	10
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	76	0.0	125	59.6	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	14
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	79	0.0	250	59.6	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	13
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	84	0.0	500	59.6	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	17
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	83	0.0	1000	59.6	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	15
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	79	0.0	2000	59.6	0.0	-3.0	0.0	2.6	0.0	0.0	0.0	-12.0	0.0	8
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	76	0.0	125	59.9	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	14
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	79	0.0	250	59.9	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	13
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	84	0.0	500	59.9	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	17
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	83	0.0	1000	59.9	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	14
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	79	0.0	2000	59.9	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	7
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	76	0.0	125	59.9	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	14
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	79	0.0	250	59.9	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	13
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	84	0.0	500	59.9	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	17
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	83	0.0	1000	59.9	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	14
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	79	0.0	2000	59.9	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	7



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	31

Receiver Name	Receiver ID	X																	
RP05	RP05	17652574.56 m	4786747.95 m	7.00 m															
	•																		
Source ID	Source Name	Χ	Υ	Z	Refl.	Lw	L/A	Freq	Adiv	KO	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	67	0.0	63	59.0	0.0	-3.0	9.7	0.0	0.0	0.0	0.0	-1.0	0.0	0
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	80	0.0	125	59.0	0.0	-3.0	12.5	0.1	0.0	0.0	0.0	-5.0	0.0	6
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	84	0.0	250	59.0	0.0	-3.0	15.4	0.3	0.0	0.0	0.0	-9.0	0.0	4
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	87	0.0	500	59.0	0.0	-3.0	18.3	0.5	0.0	0.0	0.0	-10.0	0.0	2
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	89	0.0	1000	59.0	0.0	-3.0	21.0	0.9	0.0	0.0	0.0	-11.0	0.0	0
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	80	0.0	125	59.2	0.0	-3.0	16.0	0.1	0.0	0.0	0.0	-5.0	0.0	3
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	80	0.0	125	59.2	0.0	-3.0	16.8	0.1	0.0	0.0	0.0	-5.0	0.0	2
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	80	0.0	125	59.6	0.0	-3.0	17.0	0.1	0.0	0.0	0.0	-5.0	0.0	1
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	80	0.0	125	59.6	0.0	-3.0	16.9	0.1	0.0	0.0	0.0	-5.0	0.0	1
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	80	0.0	125	60.1	0.0	-3.0	15.4	0.1	0.0	0.0	0.0	-5.0	0.0	2
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	80	0.0	125	60.6	0.0	-3.0	15.5	0.1	0.0	0.0	0.0	-5.0	0.0	2
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	80	0.0	125	60.6	0.0	-3.0	15.5	0.1	0.0	0.0	0.0	-5.0	0.0	2
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	78	0.0	125	60.1	0.0	-3.0	15.5	0.1	0.0	0.0	0.0	-5.0	0.0	0
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	80	0.0	125	60.9	0.0	-3.0	15.6	0.1	0.0	0.0	0.0	-5.0	0.0	1
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	67	0.0	63	61.1	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	8
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	80	0.0	125	61.1	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	17
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	84	0.0	250	61.1	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	17
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	87	0.0	500	61.1	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	18
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	89	0.0	1000	61.1	0.0	-3.0	0.0	1.2	0.0	0.0	0.0	-11.0	0.0	19
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	85	0.0	2000	61.1	0.0	-3.0	0.0	3.1	0.0	0.0	0.0	-12.0	0.0	12
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	67	0.0	63	61.3	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	8
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	80	0.0	125	61.3	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	17
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	84	0.0	250	61.3	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	17
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	87	0.0	500	61.3	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	18
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	89	0.0	1000	61.3	0.0	-3.0	0.0	1.2	0.0	0.0	0.0	-11.0	0.0	19
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	85	0.0	2000	61.3	0.0	-3.0	0.0	3.2	0.0	0.0	0.0	-12.0	0.0	12
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	80	0.0	125	61.6	0.0	-3.0	12.4	0.1	0.0	0.0	0.0	-5.0	0.0	4
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	84	0.0	250	61.6	0.0	-3.0	15.3	0.4	0.0	0.0	0.0	-9.0	0.0	1
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	80	0.0	125	61.6	0.0	-3.0	9.6	0.1	0.0	0.0	0.0	-5.0	0.0	7
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	84	0.0	250	61.6	0.0	-3.0	12.1	0.4	0.0	0.0	0.0	-9.0	0.0	4
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	87	0.0	500	61.6	0.0	-3.0	14.8	0.7	0.0	0.0	0.0	-10.0	0.0	3
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	89	0.0	1000	61.6	0.0	-3.0	17.5	1.2	0.0	0.0	0.0	-11.0	0.0	1
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	80	0.0	125	61.7	0.0	-3.0	11.2	0.1	0.0	0.0	0.0	-5.0	0.0	5
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	84	0.0	250	61.7	0.0	-3.0	13.9	0.4	0.0	0.0	0.0	-9.0	0.0	3
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	87	0.0	500	61.7	0.0	-3.0	16.8	0.7	0.0	0.0	0.0	-10.0	0.0	1
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	80	0.0	125	61.7	0.0	-3.0	10.4	0.1	0.0	0.0	0.0	-5.0	0.0	6
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	84	0.0	250	61.7	0.0	-3.0	13.0	0.4	0.0	0.0	0.0	-9.0	0.0	3
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	87	0.0	500	61.7	0.0	-3.0	15.8	0.7	0.0	0.0	0.0	-10.0	0.0	2
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	74	0.0	125	57.3	0.0	-3.0	14.2	0.1	0.0	0.0	0.0	-5.0	0.0	0
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	72	0.0	250	61.5	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-9.0	0.0	5
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	84	0.0	500	61.5	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	15
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	89	0.0	1000	61.5	0.0	-3.0	0.0	1.2	0.0	0.0	0.0	-11.0	0.0	18
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	87	0.0	2000	61.5	0.0	-3.0	0.0	3.3	0.0	0.0	0.0	-12.0	0.0	13
S28	HVAC RTU	17652287.5	4786523.9	5.5	0	72	0.0	250	62.2	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-9.0	0.0	4



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	31

Receiver Name	Receiver ID	Χ		Z															
RP05	RP05	17652574.56 m	4786747.95 m	7.00 m															
0 10	C N			_	5.0					140								D)	
Source ID	Source Name	Х		Z	Refl.	Lw	L/A	Freq	Adiv	K0	Agr	Abar	Aatm	Afol	Ahous		Dc	RL	Lr
S28	HVAC RTU	17652287.5	4786523.9	5.5	0	84	0.0	500	62.2	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-10.0	0.0	14
\$28	HVAC RTU	17652287.5	4786523.9	5.5	0	89	0.0	1000	62.2	0.0	-3.0	0.0	1.3	0.0	0.0	0.0	-11.0	0.0	17
S28	HVAC RTU	17652287.5	4786523.9	5.5	0	87	0.0	2000	62.2	0.0	-3.0	0.0	3.5	0.0	0.0	0.0	-12.0	0.0	13
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	75	0.0	125	59.0	0.0	-3.0	13.5	0.1	0.0	0.0	0.0	-5.0	0.0	0
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	67	0.0	63	64.2	0.0	-3.5	0.0	0.1	0.0	0.0	0.0	-1.0	0.0	5
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	80	0.0	125	64.2	0.0	-3.5	0.0	0.2	0.0	0.0	0.0	-5.0	0.0	14
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	84	0.0	250	64.2	0.0	-3.5	0.0	0.5	0.0	0.0	0.0	-9.0	0.0	14
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	87	0.0	500	64.2	0.0	-3.5	0.0	0.9	0.0	0.0	0.0	-10.0	0.0	15
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	89	0.0	1000	64.2	0.0	-3.5	0.0	1.7	0.0	0.0	0.0	-11.0	0.0	16
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	85	0.0	2000	64.2	0.0	-3.5	0.0	4.4	0.0	0.0	0.0	-12.0	0.0	8
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	67	0.0	63	64.2	0.0	-3.5	0.0	0.1	0.0	0.0	0.0	-1.0	0.0	5
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	80	0.0	125	64.2	0.0	-3.5	0.0	0.2	0.0	0.0	0.0	-5.0	0.0	14
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	84	0.0	250	64.2	0.0	-3.5	0.0	0.5	0.0	0.0	0.0	-9.0	0.0	14
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	87	0.0	500	64.2	0.0	-3.5	0.0	0.9	0.0	0.0	0.0	-10.0	0.0	15
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	89	0.0	1000	64.2	0.0	-3.5	0.0	1.7	0.0	0.0	0.0	-11.0	0.0	16
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	85	0.0	2000	64.2	0.0	-3.5	0.0	4.4	0.0	0.0	0.0	-12.0	0.0	8
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	76	0.0	125	54.3	0.0	-3.0	15.6	0.1	0.0	0.0	0.0	-4.9	0.0	4
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	84	0.0	500	54.3	0.0	-3.0	22.2	0.3	0.0	0.0	0.0	-10.0	0.0	0
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	76	0.0	125	54.5	0.0	-3.0	15.8	0.1	0.0	0.0	0.0	-4.9	0.0	4
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	76	0.0	125	61.4	0.0	-3.0	12.5	0.1	0.0	0.0	0.0	-5.0	0.0	0
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	76	0.0	125	62.4	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-5.0	0.0	12
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	79	0.0	250	62.4	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-9.0	0.0	10
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	84	0.0	500	62.4	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-10.0	0.0	14
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	83	0.0	1000	62.4	0.0	-3.0	0.0	1.4	0.0	0.0	0.0	-11.0	0.0	11
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	79	0.0	2000	62.4	0.0	-3.0	0.0	3.6	0.0	0.0	0.0	-12.0	0.0	4
S30	HVAC RTU	17652300.7	4786464.7	5.5	0	76	0.0	125	62.9	0.0	-3.1	0.0	0.2	0.0	0.0	0.0	-5.0	0.0	11
S30	HVAC RTU	17652300.7	4786464.7	5.5	0	79	0.0	250	62.9	0.0	-3.1	0.0	0.4	0.0	0.0	0.0	-9.0	0.0	10
S30	HVAC RTU	17652300.7	4786464.7	5.5	0	84	0.0	500	62.9	0.0	-3.1	0.0	0.8	0.0	0.0	0.0	-10.0	0.0	14
\$30	HVAC RTU	17652300.7	4786464.7	5.5	0	83	0.0	1000	62.9	0.0	-3.1	0.0	1.4	0.0	0.0	0.0	-11.0	0.0	11
S30	HVAC RTU	17652300.7	4786464.7	5.5	0	79	0.0	2000	62.9	0.0	-3.1	0.0	3.8	0.0	0.0	0.0	-12.0	0.0	3
			•																



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	31

Receiver Name	Receiver ID	Χ																	
RP06	RP06	17652586.84 m	4786749.91 m	7.00 m															
					-														
Source ID	Source Name	Х			Refl.	Lw	L/A	Freq	Adiv	KO	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	67	0.0	63	58.9	0.0	-3.0	6.2	0.0	0.0	0.0	0.0	-1.0	0.0	4
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	80	0.0	125	58.9	0.0	-3.0	7.7	0.1	0.0	0.0	0.0	-5.0	0.0	11
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	84	0.0	250	58.9	0.0	-3.0	9.8	0.3	0.0	0.0	0.0	-9.0	0.0	10
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	87	0.0	500	58.9	0.0	-3.0	12.3	0.5	0.0	0.0	0.0	-10.0	0.0	8
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	89	0.0	1000	58.9	0.0	-3.0	15.0	0.9	0.0	0.0	0.0	-11.0	0.0	6
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	67	0.0	63	59.0	0.0	-3.0	7.3	0.0	0.0	0.0	0.0	-1.0	0.0	3
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	80	0.0	125	59.0	0.0	-3.0	9.4	0.1	0.0	0.0	0.0	-5.0	0.0	10
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	84	0.0	250	59.0	0.0	-3.0	11.9	0.3	0.0	0.0	0.0	-9.0	0.0	7
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	87	0.0	500	59.0	0.0	-3.0	14.7	0.5	0.0	0.0	0.0	-10.0	0.0	6
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	89	0.0	1000	59.0	0.0	-3.0	17.6	0.9	0.0	0.0	0.0	-11.0	0.0	4
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	67	0.0	63	59.0	0.0	-3.0	9.2	0.0	0.0	0.0	0.0	-1.0	0.0	1
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	80	0.0	125	59.0	0.0	-3.0	12.0	0.1	0.0	0.0	0.0	-5.0	0.0	7
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	84	0.0	250	59.0	0.0	-3.0	15.1	0.3	0.0	0.0	0.0	-9.0	0.0	4
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	87	0.0	500	59.0	0.0	-3.0	18.1	0.5	0.0	0.0	0.0	-10.0	0.0	2
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	89	0.0	1000	59.0	0.0	-3.0	20.7	0.9	0.0	0.0	0.0	-11.0	0.0	0
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	67	0.0	63	59.4	0.0	-3.0	7.6	0.0	0.0	0.0	0.0	-1.0	0.0	2
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	80	0.0	125	59.4	0.0	-3.0	9.7	0.1	0.0	0.0	0.0	-5.0	0.0	9
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	84	0.0	250	59.4	0.0	-3.0	12.3	0.3	0.0	0.0	0.0	-9.0	0.0	7
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	87	0.0	500	59.4	0.0	-3.0	15.2	0.5	0.0	0.0	0.0	-10.0	0.0	5
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	89	0.0	1000	59.4	0.0	-3.0	18.1	1.0	0.0	0.0	0.0	-11.0	0.0	3
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	67	0.0	63	59.4	0.0	-3.0	7.5	0.0	0.0	0.0	0.0	-1.0	0.0	2
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	80	0.0	125	59.4	0.0	-3.0	9.6	0.1	0.0	0.0	0.0	-5.0	0.0	9
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	84	0.0	250	59.4	0.0	-3.0	12.1	0.3	0.0	0.0	0.0	-9.0	0.0	7
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	87	0.0	500	59.4	0.0	-3.0	15.0	0.5	0.0	0.0	0.0	-10.0	0.0	5
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	89	0.0	1000	59.4	0.0	-3.0	17.9	1.0	0.0	0.0	0.0	-11.0	0.0	3
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	67	0.0	63	59.8	0.0	-3.0	5.4	0.0	0.0	0.0	0.0	-1.0	0.0	4
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	80	0.0	125	59.8	0.0	-3.0	6.6	0.1	0.0	0.0	0.0	-5.0	0.0	12
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	84	0.0	250	59.8	0.0	-3.0	8.2	0.3	0.0	0.0	0.0	-9.0	0.0	10
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	87	0.0	500	59.8	0.0	-3.0	10.3	0.5	0.0	0.0	0.0	-10.0	0.0	9
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	89	0.0	1000	59.8	0.0	-3.0	12.7	1.0	0.0	0.0	0.0	-11.0	0.0	8
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	89	0.0	1000	59.1	0.0	-3.0	20.6	0.9	0.0	0.0	0.0	-11.0	0.0	0
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	67	0.0	63	60.3	0.0	-3.0	5.6	0.0	0.0	0.0	0.0	-1.0	0.0	3
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	80	0.0	125	60.3	0.0	-3.0	6.9	0.1	0.0	0.0	0.0	-5.0	0.0	11
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	84	0.0	250	60.3	0.0	-3.0	8.6	0.3	0.0	0.0	0.0	-9.0	0.0	9
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	87	0.0	500	60.3	0.0	-3.0	10.8	0.6	0.0	0.0	0.0	-10.0	0.0	8
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	89	0.0	1000	60.3	0.0	-3.0	13.4	1.1	0.0	0.0	0.0	-11.0	0.0	6
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	67	0.0	63	60.3	0.0	-3.0	5.6	0.0	0.0	0.0	0.0	-1.0	0.0	3
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	80	0.0	125	60.3	0.0	-3.0	6.8	0.1	0.0	0.0	0.0	-5.0	0.0	11
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	84	0.0	250	60.3	0.0	-3.0	8.6	0.3	0.0	0.0	0.0	-9.0	0.0	9
S06	HVACRTU	17652777.1	4786972.9	5.5	0	87	0.0	500	60.3	0.0	-3.0	10.8	0.6	0.0	0.0	0.0	-10.0	0.0	8
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	89	0.0	1000	60.3	0.0	-3.0	13.3	1.1	0.0	0.0	0.0	-11.0	0.0	6
S36	HVAC RTU	17652710.3	4786988.4	5.5	0	84	0.0	500	59.6	0.0	-3.0	13.5	0.5	0.0	0.0	0.0	-10.0	0.0	3
S36	HVAC RTU	17652710.3	4786988.4	5.5	0	89	0.0	1000	59.6	0.0	-3.0	16.3	1.0	0.0	0.0	0.0	-11.0	0.0	4
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	65	0.0	63	59.8	0.0	-3.0	5.5	0.0	0.0	0.0	0.0	-1.0	0.0	2



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	31

Receiver Name	Receiver ID	Х																	
RP06	RP06	17652586.84 m	4786749.91 m	7.00 m															
Source ID	Source Name	X			Refl.	Lw	L/A	Freq	Adiv	K0	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	78	0.0	125	59.8	0.0	-3.0	6.8	0.1	0.0	0.0	0.0	-5.0	0.0	9
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	83	0.0	250	59.8	0.0	-3.0	8.5	0.3	0.0	0.0	0.0	-9.0	0.0	9
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	87	0.0	500	59.8	0.0	-3.0	10.7	0.5	0.0	0.0	0.0	-10.0	0.0	9
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	87	0.0	1000	59.8	0.0	-3.0	13.2	1.0	0.0	0.0	0.0	-11.0	0.0	5
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	67	0.0	63	60.7	0.0	-3.0	5.8	0.0	0.0	0.0	0.0	-1.0	0.0	2
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	80	0.0	125	60.7	0.0	-3.0	7.1	0.1	0.0	0.0	0.0	-5.0	0.0	10
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	84	0.0	250	60.7	0.0	-3.0	9.0	0.3	0.0	0.0	0.0	-9.0	0.0	8
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	87	0.0	500	60.7	0.0	-3.0	11.3	0.6	0.0	0.0	0.0	-10.0	0.0	7
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	89	0.0	1000	60.7	0.0	-3.0	13.9	1.1	0.0	0.0	0.0	-11.0	0.0	5
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	67	0.0	63	61.4	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	7
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	80	0.0	125	61.4	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	16
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	84	0.0	250	61.4	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	17
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	87	0.0	500	61.4	0.0	-3.0	0.0	0.6	0.0	0.0	0.0	-10.0	0.0	18
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	89	0.0	1000	61.4	0.0	-3.0	0.0	1.2	0.0	0.0	0.0	-11.0	0.0	18
S26	HVAC RTU	17652295.7	4786588.4	5.5	0	85	0.0	2000	61.4	0.0	-3.0	0.0	3.2	0.0	0.0	0.0	-12.0	0.0	12
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	80	0.0	125	61.6	0.0	-3.0	11.9	0.1	0.0	0.0	0.0	-5.0	0.0	4
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	84	0.0	250	61.6	0.0	-3.0	14.9	0.4	0.0	0.0	0.0	-9.0	0.0	2
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	67	0.0	63	61.6	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	7
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	80	0.0	125	61.6	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	16
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	84	0.0	250	61.6	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-9.0	0.0	17
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	87	0.0	500	61.6	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-10.0	0.0	18
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	89	0.0	1000	61.6	0.0	-3.0	0.0	1.2	0.0	0.0	0.0	-11.0	0.0	18
S27	HVAC RTU	17652296.3	4786576.0	5.5	0	85	0.0	2000	61.6	0.0	-3.0	0.0	3.3	0.0	0.0	0.0	-12.0	0.0	11
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	61	0.0	63	56.8	0.0	-3.0	4.4	0.0	0.0	0.0	0.0	-1.0	0.0	2
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	74	0.0	125	56.8	0.0	-3.0	4.7	0.1	0.0	0.0	0.0	-5.0	0.0	10
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	79	0.0	250	56.8	0.0	-3.0	5.1	0.2	0.0	0.0	0.0	-9.0	0.0	11
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	83	0.0	500	56.8	0.0	-3.0	5.6	0.4	0.0	0.0	0.0	-10.0	0.0	13
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	82	0.0	1000	56.8	0.0	-3.0	6.4	0.7	0.0	0.0	0.0	-11.0	0.0	10
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	81	0.0	2000	56.8	0.0	-3.0	7.5	1.9	0.0	0.0	0.0	-12.0	0.0	6
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	80	0.0	125	61.7	0.0	-3.0	12.5	0.1	0.0	0.0	0.0	-5.0	0.0	4
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	84	0.0	250	61.7	0.0	-3.0	15.4	0.4	0.0	0.0	0.0	-9.0	0.0	1
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	80	0.0	125	61.7	0.0	-3.0	12.2	0.1	0.0	0.0	0.0	-5.0	0.0	4
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	84	0.0	250	61.7	0.0	-3.0	15.2	0.4	0.0	0.0	0.0	-9.0	0.0	1
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	80	0.0	125	61.7	0.0	-3.0	12.3	0.1	0.0	0.0	0.0	-5.0	0.0	4
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	84	0.0	250	61.7	0.0	-3.0	15.3	0.4	0.0	0.0	0.0	-9.0	0.0	1
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	61	0.0	63	57.7	0.0	-3.0	4.2	0.0	0.0	0.0	0.0	-1.0	0.0	1
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	74	0.0	125	57.7	0.0	-3.0	4.5	0.1	0.0	0.0	0.0	-5.0	0.0	10
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	79	0.0	250	57.7	0.0	-3.0	4.7	0.2	0.0	0.0	0.0	-9.0	0.0	11
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	83	0.0	500	57.7	0.0	-3.0	5.0	0.4	0.0	0.0	0.0	-10.0	0.0	13
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	82	0.0	1000	57.7	0.0	-3.0	5.3	0.8	0.0	0.0	0.0	-11.0	0.0	10
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	81	0.0	2000	57.7	0.0	-3.0	5.7	2.1	0.0	0.0	0.0	-12.0	0.0	7
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	84	0.0	500	61.9	0.0	-3.0	7.8	0.7	0.0	0.0	0.0	-10.0	0.0	7
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	89	0.0	1000	61.9	0.0	-3.0	9.6	1.3	0.0	0.0	0.0	-11.0	0.0	8
S25	HVAC RTU	17652250.3	4786658.2	5.5	0	87	0.0	2000	61.9	0.0	-3.0	11.8	3.4	0.0	0.0	0.0	-12.0	0.0	1



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	31

Receiver Mairie	Receiver ID	۸																	
RP06	RP06	17652586.84 m	4786749.91 m	7.00 m															
		·																	
Source ID	Source Name	Χ	Υ	Z	Refl.	Lw	L/A	Freq	Adiv	K0	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S28	HVAC RTU	17652287.5	4786523.9	5.5	0	72	0.0	250	62.5	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-9.0	0.0	4
S28	HVAC RTU	17652287.5	4786523.9	5.5	0	84	0.0	500	62.5	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-10.0	0.0	14
S28	HVAC RTU	17652287.5	4786523.9	5.5	0	89	0.0	1000	62.5	0.0	-3.0	0.0	1.4	0.0	0.0	0.0	-11.0	0.0	17
S28	HVAC RTU	17652287.5	4786523.9	5.5	0	87	0.0	2000	62.5	0.0	-3.0	0.0	3.6	0.0	0.0	0.0	-12.0	0.0	12
S03	HVAC RTU	17652813.6	4786860.2	8.0	0	74	0.0	125	59.0	0.0	-3.0	4.4	0.1	0.0	0.0	0.0	-5.0	0.0	8
S03	HVAC RTU	17652813.6	4786860.2	8.0	0	79	0.0	250	59.0	0.0	-3.0	4.6	0.3	0.0	0.0	0.0	-9.0	0.0	10
\$03	HVAC RTU	17652813.6	4786860.2	8.0	0	83	0.0	500	59.0	0.0	-3.0	4.8	0.5	0.0	0.0	0.0	-10.0	0.0	12
S03	HVAC RTU	17652813.6	4786860.2	8.0	0	82	0.0	1000	59.0	0.0	-3.0	4.9	0.9	0.0	0.0	0.0	-11.0	0.0	9
S03	HVAC RTU	17652813.6	4786860.2	8.0	0	81	0.0	2000	59.0	0.0	-3.0	5.0	2.4	0.0	0.0	0.0	-12.0	0.0	6
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	75	0.0	125	58.9	0.0	-3.0	11.8	0.1	0.0	0.0	0.0	-5.0	0.0	2
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	80	0.0	250	58.9	0.0	-3.0	14.8	0.3	0.0	0.0	0.0	-9.0	0.0	0
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	80	0.0	125	64.4	0.0	-3.6	5.8	0.2	0.0	0.0	0.0	-5.0	0.0	8
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	84	0.0	250	64.4	0.0	-3.6	7.0	0.5	0.0	0.0	0.0	-9.0	0.0	7
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	87	0.0	500	64.4	0.0	-3.6	8.6	0.9	0.0	0.0	0.0	-10.0	0.0	7
S32	HVAC RTU	17652130.5	4786637.7	5.5	0	89	0.0	1000	64.4	0.0	-3.6	10.6	1.7	0.0	0.0	0.0	-11.0	0.0	5
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	80	0.0	125	64.5	0.0	-3.6	5.9	0.2	0.0	0.0	0.0	-5.0	0.0	8
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	84	0.0	250	64.5	0.0	-3.6	7.1	0.5	0.0	0.0	0.0	-9.0	0.0	7
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	87	0.0	500	64.5	0.0	-3.6	8.8	0.9	0.0	0.0	0.0	-10.0	0.0	6
S31	HVAC RTU	17652128.5	4786640.0	5.5	0	89	0.0	1000	64.5	0.0	-3.6	10.8	1.7	0.0	0.0	0.0	-11.0	0.0	5
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	61	0.0	63	59.8	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	3
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	74	0.0	125	59.8	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	12
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	79	0.0	250	59.8	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	13
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	83	0.0	500	59.8	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	16
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	82	0.0	1000	59.8	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	13
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	81	0.0	2000	59.8	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	10
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	76	0.0	125	54.2	0.0	-3.0	11.4	0.1	0.0	0.0	0.0	-4.9	0.0	8
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	79	0.0	250	54.2	0.0	-3.0	14.4	0.2	0.0	0.0	0.0	-8.9	0.0	4
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	84	0.0	500	54.2	0.0	-3.0	17.4	0.3	0.0	0.0	0.0	-10.0	0.0	5
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	83	0.0	1000	54.2	0.0	-3.0	20.2	0.5	0.0	0.0	0.0	-11.0	0.0	0
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	76	0.0	125	54.3	0.0	-3.0	11.2	0.1	0.0	0.0	0.0	-4.9	0.0	9
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	79	0.0	250	54.3	0.0	-3.0	14.1	0.2	0.0	0.0	0.0	-8.9	0.0	5
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	84	0.0	500	54.3	0.0	-3.0	17.1	0.3	0.0	0.0	0.0	-10.0	0.0	5
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	83	0.0	1000	54.3	0.0	-3.0	19.9	0.5	0.0	0.0	0.0	-11.0	0.0	0
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	70	0.0	125	58.3	0.0	-3.0	7.8	0.1	0.0	0.0	0.0	-5.0	0.0	2
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	79	0.0	500	58.3	0.0	-3.0	12.4	0.4	0.0	0.0	0.0	-10.0	0.0	1
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	76	0.0	125	59.0	0.0	-3.0	10.5	0.1	0.0	0.0	0.0	-5.0	0.0	4
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	79	0.0	250	59.0	0.0	-3.0	13.3	0.3	0.0	0.0	0.0	-9.0	0.0	1
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	84	0.0	500	59.0	0.0	-3.0	16.3	0.5	0.0	0.0	0.0	-10.0	0.0	1
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	76	0.0	125	59.5	0.0	-3.0	9.4	0.1	0.0	0.0	0.0	-5.0	0.0	5
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	79	0.0	250	59.5	0.0	-3.0	11.9	0.3	0.0	0.0	0.0	-9.0	0.0	1
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	84	0.0	500	59.5	0.0	-3.0	14.7	0.5	0.0	0.0	0.0	-10.0	0.0	2
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	76	0.0	125	61.4	0.0	-3.0	11.9	0.1	0.0	0.0	0.0	-5.0	0.0	1
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	76	0.0	125	61.7	0.0	-3.0	11.7	0.1	0.0	0.0	0.0	-5.0	0.0	1
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	76	0.0	125	61.7	0.0	-3.0	11.8	0.1	0.0	0.0	0.0	-5.0	0.0	0



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	31

Receiver Marrie	Receiver ID	Λ																	
RP06	RP06	17652586.84 m	4786749.91 m	7.00 m															
Source ID	Source Name	Х			Refl.	Lw	L/A	Freq	Adiv	KO	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	76	0.0	125	62.6	0.0	-3.1	0.0	0.2	0.0	0.0	0.0	-5.0	0.0	11
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	79	0.0	250	62.6	0.0	-3.1	0.0	0.4	0.0	0.0	0.0	-9.0	0.0	10
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	84	0.0	500	62.6	0.0	-3.1	0.0	0.7	0.0	0.0	0.0	-10.0	0.0	14
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	83	0.0	1000	62.6	0.0	-3.1	0.0	1.4	0.0	0.0	0.0	-11.0	0.0	11
S29	HVAC RTU	17652331.9	4786466.0	5.5	0	79	0.0	2000	62.6	0.0	-3.1	0.0	3.7	0.0	0.0	0.0	-12.0	0.0	4
\$30	HVAC RTU	17652300.7	4786464.7	5.5	0	76	0.0	125	63.1	0.0	-3.2	0.0	0.2	0.0	0.0	0.0	-5.0	0.0	11
\$30	HVAC RTU	17652300.7	4786464.7	5.5	0	79	0.0	250	63.1	0.0	-3.2	0.0	0.4	0.0	0.0	0.0	-9.0	0.0	10
\$30	HVAC RTU	17652300.7	4786464.7	5.5	0	84	0.0	500	63.1	0.0	-3.2	0.0	0.8	0.0	0.0	0.0	-10.0	0.0	13
\$30	HVAC RTU	17652300.7	4786464.7	5.5	0	83	0.0	1000	63.1	0.0	-3.2	0.0	1.5	0.0	0.0	0.0	-11.0	0.0	11
S30	HVAC RTU	17652300.7	4786464.7	5.5	0	79	0.0	2000	63.1	0.0	-3.2	0.0	3.9	0.0	0.0	0.0	-12.0	0.0	3



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	41

Receiver Name	Receiver ID	X																	
RP07	RP07	17652566.00 m	4786807.33 m	7.00 m															
Source ID	Source Name	Χ			Refl.	Lw	L/A	Freq	Adiv	K0	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	67	0.0	63	56.7	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	12
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	80	0.0	125	56.7	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	21
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	84	0.0	250	56.7	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	22
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	87	0.0	500	56.7	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	23
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	89	0.0	1000	56.7	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-11.0	0.0	24
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	85	0.0	2000	56.7	0.0	-3.0	0.0	1.9	0.0	0.0	0.0	-12.0	0.0	18
S15	HVAC RTU	17652538.8	4786997.8	5.5	0	78	0.0	4000	56.7	0.0	-3.0	0.0	6.3	0.0	0.0	0.0	-13.0	0.0	5
\$08	HVAC RTU	17652671.6	4786985.8	5.5	0	67	0.0	63	57.3	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	12
\$08	HVAC RTU	17652671.6	4786985.8	5.5	0	80	0.0	125	57.3	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	21
\$08	HVAC RTU	17652671.6	4786985.8	5.5	0	84	0.0	250	57.3	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	21
\$08	HVAC RTU	17652671.6	4786985.8	5.5	0	87	0.0	500	57.3	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	22
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	89	0.0	1000	57.3	0.0	-3.0	0.0	0.8	0.0	0.0	0.0	-11.0	0.0	23
\$08	HVAC RTU	17652671.6	4786985.8	5.5	0	85	0.0	2000	57.3	0.0	-3.0	0.0	2.0	0.0	0.0	0.0	-12.0	0.0	17
S08	HVAC RTU	17652671.6	4786985.8	5.5	0	78	0.0	4000	57.3	0.0	-3.0	0.0	6.8	0.0	0.0	0.0	-13.0	0.0	4
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	61	0.0	125	56.8	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	2
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	72	0.0	250	56.8	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	10
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	84	0.0	500	56.8	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	20
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	89	0.0	1000	56.8	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-11.0	0.0	24
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	87	0.0	2000	56.8	0.0	-3.0	0.0	1.9	0.0	0.0	0.0	-12.0	0.0	20
S14	HVAC RTU	17652545.1	4787000.3	5.5	0	81	0.0	4000	56.8	0.0	-3.0	0.0	6.4	0.0	0.0	0.0	-13.0	0.0	8
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	67	0.0	63	57.7	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	11
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	80	0.0	125	57.7	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	20
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	84	0.0	250	57.7	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	21
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	87	0.0	500	57.7	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	22
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	89	0.0	1000	57.7	0.0	-3.0	0.0	0.8	0.0	0.0	0.0	-11.0	0.0	23
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	85	0.0	2000	57.7	0.0	-3.0	0.0	2.1	0.0	0.0	0.0	-12.0	0.0	16
S11	HVAC RTU	17652661.7	4787001.8	5.5	0	78	0.0	4000	57.7	0.0	-3.0	0.0	7.1	0.0	0.0	0.0	-13.0	0.0	3
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	67	0.0	63	57.8	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	11
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	80	0.0	125	57.8	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	20
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	84	0.0	250	57.8	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	21
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	87	0.0	500	57.8	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	22
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	89	0.0	1000	57.8	0.0	-3.0	0.0	0.8	0.0	0.0	0.0	-11.0	0.0	23
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	85	0.0	2000	57.8	0.0	-3.0	0.0	2.1	0.0	0.0	0.0	-12.0	0.0	16
S35	HVAC RTU	17652724.4	4786956.5	5.5	0	78	0.0	4000	57.8	0.0	-3.0	0.0	7.1	0.0	0.0	0.0	-13.0	0.0	3
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	67	0.0	63	57.8	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	11
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	80	0.0	125	57.8	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	20
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	84	0.0	250	57.8	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	20
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	87	0.0	500	57.8	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	22
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	89	0.0	1000	57.8	0.0	-3.0	0.0	0.8	0.0	0.0	0.0	-11.0	0.0	22
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	85	0.0	2000	57.8	0.0	-3.0	0.0	2.1	0.0	0.0	0.0	-12.0	0.0	16
S10	HVAC RTU	17652667.8	4787001.4	5.5	0	78	0.0	4000	57.8	0.0	-3.0	0.0	7.2	0.0	0.0	0.0	-13.0	0.0	3
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	67	0.0	63	59.0	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	10
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	80	0.0	125	59.0	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	19
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	84	0.0	250	59.0	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	19



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	41

Receiver Name	Receiver ID	Х																	
RP07	RP07	17652566.00 m	4786807.33 m	7.00 m															
		•	•																
Source ID	Source Name	Х	Υ	Z	Refl.	Lw	L/A	Freq	Adiv	K0	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	87	0.0	500	59.0	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	20
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	89	0.0	1000	59.0	0.0	-3.0	0.0	0.9	0.0	0.0	0.0	-11.0	0.0	21
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	85	0.0	2000	59.0	0.0	-3.0	0.0	2.4	0.0	0.0	0.0	-12.0	0.0	15
S34	HVAC RTU	17652772.1	4786953.1	5.5	0	78	0.0	4000	59.0	0.0	-3.0	0.0	8.3	0.0	0.0	0.0	-13.0	0.0	1
S36	HVAC RTU	17652710.3	4786988.4	5.5	0	61	0.0	125	58.3	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	1
S36	HVAC RTU	17652710.3	4786988.4	5.5	0	72	0.0	250	58.3	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-9.0	0.0	8
S36	HVAC RTU	17652710.3	4786988.4	5.5	0	84	0.0	500	58.3	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	18
S36	HVAC RTU	17652710.3	4786988.4	5.5	0	89	0.0	1000	58.3	0.0	-3.0	0.0	0.8	0.0	0.0	0.0	-11.0	0.0	22
S36	HVAC RTU	17652710.3	4786988.4	5.5	0	87	0.0	2000	58.3	0.0	-3.0	0.0	2.2	0.0	0.0	0.0	-12.0	0.0	18
S36	HVAC RTU	17652710.3	4786988.4	5.5	0	81	0.0	4000	58.3	0.0	-3.0	0.0	7.6	0.0	0.0	0.0	-13.0	0.0	5
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	67	0.0	63	59.5	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	80	0.0	125	59.5	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	18
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	84	0.0	250	59.5	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	19
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	87	0.0	500	59.5	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	20
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	89	0.0	1000	59.5	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	21
S05	HVAC RTU	17652774.7	4786972.8	5.5	0	85	0.0	2000	59.5	0.0	-3.0	0.0	2.6	0.0	0.0	0.0	-12.0	0.0	14
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	67	0.0	63	59.6	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	80	0.0	125	59.6	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	18
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	84	0.0	250	59.6	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	19
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	87	0.0	500	59.6	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	20
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	89	0.0	1000	59.6	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	21
S06	HVAC RTU	17652777.1	4786972.9	5.5	0	85	0.0	2000	59.6	0.0	-3.0	0.0	2.6	0.0	0.0	0.0	-12.0	0.0	14
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	65	0.0	63	59.0	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	8
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	78	0.0	125	59.0	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	17
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	83	0.0	250	59.0	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	18
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	87	0.0	500	59.0	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	20
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	87	0.0	1000	59.0	0.0	-3.0	0.0	0.9	0.0	0.0	0.0	-11.0	0.0	19
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	85	0.0	2000	59.0	0.0	-3.0	0.0	2.4	0.0	0.0	0.0	-12.0	0.0	15
S33	HVAC RTU	17652765.8	4786957.2	5.5	0	81	0.0	4000	59.0	0.0	-3.0	0.0	8.2	0.0	0.0	0.0	-13.0	0.0	4
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	67	0.0	63	59.9	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	80	0.0	125	59.9	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	18
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	84	0.0	250	59.9	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	18
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	87	0.0	500	59.9	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	19
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	89	0.0	1000	59.9	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S07	HVAC RTU	17652774.6	4786990.1	5.5	0	85	0.0	2000	59.9	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	14
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	67	0.0	63	59.9	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	80	0.0	125	59.9	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	18
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	84	0.0	250	59.9	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	18
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	87	0.0	500	59.9	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	19
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	89	0.0	1000	59.9	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S21	HVAC RTU	17652529.4	4787083.3	5.5	0	85	0.0	2000	59.9	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	14
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	67	0.0	63	60.0	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	80	0.0	125	60.0	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	18
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	84	0.0	250	60.0	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	18



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	41

Receiver Name	Receiver ID	Х	Y																
RP07	RP07	17652566.00 m	4786807.33 m	7.00 m															
	•																		
Source ID	Source Name	χ	Υ	7	Refl.	Lw	L/A	Freq	Adiv	KO	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	87	0.0	500	60.0	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	19
S18	HVAC RTU	17652494.0	4787078.9	5.5	0	89	0.0	1000	60.0	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
\$18	HVAC RTU	17652494.0	4787078.9	5.5	0	85	0.0	2000	60.0	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	14
\$20	HVAC RTU	17652511.2	4787083.5	5.5	0	67	0.0	63	60.0	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	9
\$20 \$20	HVAC RTU	17652511.2	4787083.5	5.5	0	80	0.0	125	60.0	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-5.0	0.0	18
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	84	0.0	250	60.0	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	18
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	87	0.0	500	60.0	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	19
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	89	0.0	1000	60.0	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S20	HVAC RTU	17652511.2	4787083.5	5.5	0	85	0.0	2000	60.0	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	14
																0.0			9
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	67	0.0	63	60.0	0.0	-3.0	0.0	0.0	0.0	0.0		-1.0	0.0	
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	80	0.0	125	60.0	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	18
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	84	0.0	250	60.0	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	18
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	87	0.0	500	60.0	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	19
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	89	0.0	1000	60.0	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S19	HVAC RTU	17652502.1	4787082.3	5.5	0	85	0.0	2000	60.0	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	14
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	72	0.0	250	59.8	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	6
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	84	0.0	500	59.8	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	17
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	89	0.0	1000	59.8	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	20
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	87	0.0	2000	59.8	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	16
S24	HVAC RTU	17652560.7	4787081.8	5.5	0	81	0.0	4000	59.8	0.0	-3.0	0.0	9.0	0.0	0.0	0.0	-13.0	0.0	2
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	76	0.0	125	50.0	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-4.9	0.0	24
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	79	0.0	250	50.0	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-8.9	0.0	23
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	84	0.0	500	50.0	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-10.0	0.0	27
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	83	0.0	1000	50.0	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-11.0	0.0	25
\$17	HVAC RTU	17652582.9	4786894.7	5.5	0	79	0.0	2000	50.0	0.0	-3.0	0.0	0.9	0.0	0.0	0.0	-12.0	0.0	19
S17	HVAC RTU	17652582.9	4786894.7	5.5	0	73	0.0	4000	50.0	0.0	-3.0	0.0	2.9	0.0	0.0	0.0	-13.0	0.0	10
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	76	0.0	125	50.3	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-4.9	0.0	24
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	79	0.0	250	50.3	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-8.9	0.0	23
\$16 \$16	HVAC RTU	17652589.2	4786896.6	5.5	0	84	0.0	500	50.3	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-10.0	0.0	27
	HVAC RTU	17652589.2	4786896.6	5.5	0	83	0.0	1000	50.3	0.0	-3.0	0.0	0.3	0.0	0.0		-11.0	0.0	24
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	79	0.0	2000	50.3	0.0	-3.0	0.0	0.9	0.0	0.0	0.0	-12.0	0.0	19
S16	HVAC RTU	17652589.2	4786896.6	5.5	0	73	0.0	4000	50.3	0.0	-3.0	0.0	3.0	0.0	0.0	0.0	-13.0	0.0	10
\$13	HVAC RTU	17652551.9	4786997.1	5.5	0	62	0.0	63	56.6	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	1/
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	75	0.0	125	56.6	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	16
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	80	0.0	250	56.6	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	18
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	83	0.0	500	56.6	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	19
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	82	0.0	1000	56.6	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-11.0	0.0	17
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	80	0.0	2000	56.6	0.0	-3.0	0.0	1.8	0.0	0.0	0.0	-12.0	0.0	13
S13	HVAC RTU	17652551.9	4786997.1	5.5	0	77	0.0	4000	56.6	0.0	-3.0	0.0	6.2	0.0	0.0	0.0	-13.0	0.0	4
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	61	0.0	63	56.7	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	6
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	74	0.0	125	56.7	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	15
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	79	0.0	250	56.7	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-9.0	0.0	17
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	83	0.0	500	56.7	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	19
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	82	0.0	1000	56.7	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-11.0	0.0	17



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	41

Receiver Name	Receiver ID	Х	Υ																
RP07	RP07	17652566.00 m	4786807.33 m	7.00 m															
Source ID	Source Name	χ	γ	7	Refl.	Lw	L/A	Freq	Adiv	KO	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	81	0.0	2000	56.7	0.0	-3.0	0.0	1.9	0.0	0.0	0.0	-12.0	0.0	14
S01	HVAC RTU	17652754.0	4786849.6	8.0	0	78	0.0	4000	56.7	0.0	-3.0	0.0	6.3	0.0	0.0	0.0	-13.0	0.0	5
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	61	0.0	63	57.7	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	5
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	74	0.0	125	57.7	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	14
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	79	0.0	250	57.7	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-9.0	0.0	16
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	83	0.0	500	57.7	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	18
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	82	0.0	1000	57.7	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-11.0	0.0	16
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	81	0.0	2000	57.7	0.0	-3.0	0.0	2.1	0.0	0.0	0.0	-12.0	0.0	12
S02	HVAC RTU	17652778.2	4786850.1	8.0	0	78	0.0	4000	57.7	0.0	-3.0	0.0	7.1	0.0	0.0	0.0	-13.0	0.0	3
\$02 \$03															_	0.0			
	HVAC RTU	17652813.6	4786860.2	8.0	0	61	0.0	63	59.1	0.0	-3.0	0.0	0.0	0.0	0.0		-1.0	0.0	4
S03	HVAC RTU	17652813.6	4786860.2	8.0	0	74	0.0	125	59.1	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	13
\$03	HVAC RTU	17652813.6	4786860.2	8.0	0	79	0.0	250	59.1	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	14
S03	HVAC RTU	17652813.6	4786860.2	8.0	0	83	0.0	500	59.1	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	16
\$03	HVAC RTU	17652813.6	4786860.2	8.0	0	82	0.0	1000	59.1	0.0	-3.0	0.0	0.9	0.0	0.0	0.0	-11.0	0.0	14
\$03	HVAC RTU	17652813.6	4786860.2	8.0	0	81	0.0	2000	59.1	0.0	-3.0	0.0	2.4	0.0	0.0	0.0	-12.0	0.0	11
\$03	HVAC RTU	17652813.6	4786860.2	8.0	0	78	0.0	4000	59.1	0.0	-3.0	0.0	8.3	0.0	0.0	0.0	-13.0	0.0	1
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	61	0.0	63	59.9	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	3
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	74	0.0	125	59.9	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	12
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	79	0.0	250	59.9	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	13
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	83	0.0	500	59.9	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	15
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	82	0.0	1000	59.9	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	13
S04	HVAC RTU	17652837.9	4786861.4	8.0	0	81	0.0	2000	59.9	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	10
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	62	0.0	63	57.0	0.0	-3.0	0.0	0.0	0.0	0.0	0.0	-1.0	0.0	7
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	70	0.0	125	57.0	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	11
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	72	0.0	250	57.0	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	8
\$37 \$37	HVAC RTU	17652713.2	4786942.6	5.5	0	79	0.0	500	57.0	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	15
	HVAC RTU	17652713.2	4786942.6	5.5	0	76	0.0	1000	57.0	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-11.0	0.0	10
S37	HVAC RTU	17652713.2	4786942.6	5.5	0	75	0.0	2000	57.0	0.0	-3.0	0.0	1.9	0.0	0.0	0.0	-12.0	0.0	7
\$37 \$12	HVAC RTU	17652713.2	4786942.6	5.5	0	74	0.0	4000	57.0	0.0	-3.0	0.0	6.6	0.0	0.0	0.0	-13.0	0.0	17
·	HVAC RTU	17652620.9	4786998.7	5.5	0	76	0.0	125	57.0	0.0	-3.0	0.0	0.1	0.0	0.0		-4.9	0.0	17
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	79	0.0	250	57.0	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	16
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	84	0.0	500	57.0	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	20
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	83	0.0	1000	57.0	0.0	-3.0	0.0	0.7	0.0	0.0	0.0	-11.0	0.0	17
S12	HVAC RTU	17652620.9	4786998.7	5.5	0	79	0.0	2000	57.0	0.0	-3.0	0.0	1.9	0.0	0.0	0.0	-12.0	0.0	11
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	76	0.0	125	57.9	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-4.9	0.0	16
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	79	0.0	250	57.9	0.0	-3.0	0.0	0.2	0.0	0.0	0.0	-8.9	0.0	15
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	84	0.0	500	57.9	0.0	-3.0	0.0	0.4	0.0	0.0	0.0	-10.0	0.0	19
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	83	0.0	1000	57.9	0.0	-3.0	0.0	0.8	0.0	0.0	0.0	-11.0	0.0	16
S09	HVAC RTU	17652676.8	4786999.6	5.5	0	79	0.0	2000	57.9	0.0	-3.0	0.0	2.1	0.0	0.0	0.0	-12.0	0.0	10
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	76	0.0	125	59.7	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	14
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	79	0.0	250	59.7	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	13
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	84	0.0	500	59.7	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	17
S38	HVAC RTU	17652531.6	4787077.3	5.5	0	83	0.0	1000	59.7	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	14
\$38	HVAC RTU	17652531.6	4787077.3	5.5	0	79	0.0	2000	59.7	0.0	-3.0	0.0	2.6	0.0	0.0	0.0	-12.0	0.0	8



1544 & 1546 Four Mile Creek Rd, Niagara-on-

Time Period	Total (dBA)
Day	41

Receiver Name	Receiver ID	X	Υ																
RP07	RP07	17652566.00 m	4786807.33 m	7.00 m]														
Source ID	Source Name	Х			Refl.	Lw	L/A	Freq	Adiv	K0	Agr	Abar	Aatm	Afol	Ahous	Cmet	Dc	RL	Lr
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	76	0.0	125	60.0	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	14
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	79	0.0	250	60.0	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	13
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	84	0.0	500	60.0	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	16
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	83	0.0	1000	60.0	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	14
S23	HVAC RTU	17652540.9	4787089.3	5.5	0	79	0.0	2000	60.0	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	7
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	76	0.0	125	60.1	0.0	-3.0	0.0	0.1	0.0	0.0	0.0	-5.0	0.0	14
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	79	0.0	250	60.1	0.0	-3.0	0.0	0.3	0.0	0.0	0.0	-9.0	0.0	13
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	84	0.0	500	60.1	0.0	-3.0	0.0	0.5	0.0	0.0	0.0	-10.0	0.0	16
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	83	0.0	1000	60.1	0.0	-3.0	0.0	1.0	0.0	0.0	0.0	-11.0	0.0	14
S22	HVAC RTU	17652529.8	4787088.9	5.5	0	79	0.0	2000	60.1	0.0	-3.0	0.0	2.7	0.0	0.0	0.0	-12.0	0.0	7





